



VRF multi-system Air-Conditioners Catalogue

KXZ series


2026



New Climate & Energy Solution

The new Mitsubishi Heavy Industries KXZ VRF series delivers high performance in cooling and heating for all commercial applications.

The KXZ series provides the highest level of design flexibility, efficiency as well as operational functions. This brochure highlights the key benefits and new and improved functions of our latest VRF technology.



2025 Design Award



reddot winner 2025

The RC-ES1 Series has been honored with the prestigious Red Dot Design Award 2025 in the Product Design Category.



The RC-ES1 Series has been honored with the prestigious Gold A' Design Award in the Repair, Restoration, and Maintenance Products Design Category.



Harmonize with the world
with the earth, people, buildings

Line-Up

KXZ3

FDC-KXZE3
FDC-KXZE3A

- Global Environment
- Wide Design Flexibility
- Improved Energy Efficiency

- Wellness & Comfort
- Toughness
- Serviceability



KXZ2

FDC-KXZE2

Heat Recovery
Systems

FDC-KXZRE2



Micro KXZ

FDC-KXZES1-W
FDC-KXZEN1-W
FDC-KXZES1
FDC-KXZEN1
FDC-KXZME1
FDC-KXZEME1A



KXZ Lite

FDC-KXZPE1



KXZ Water cooled series

FDC-KXZWE1



CONTENTS

Introduction	2	Indoor units	72	Ventilation	112
Outdoor units	4	Ceiling Cassette	86	Fresh Air Ventilation and Heat Exchange unit	112
KXZ3 series	8	Duct Connected	96	Fresh Air DX Assembly	113
KXZ2 series	38	Wall Mounted	103	Electronic Expansion Valve Kit	114
KXZ2 series Heat Recovery Systems	48	Ceiling Suspended	105	Control Systems	116
Micro KXZ series	60	Floor Standing	106	IoT Remote monitoring system	122
KXZ Lite series	65	Outdoor Air Processing unit	108	Building Management Systems	124
KXZ series Water cooled series	66	Hydro Module unit	110	Support tool	126
				Exterior dimensions	128



Outdoor units

Capacity	HP	4	5	6	8	10	12	14	16	17	18	19	20	22	24	26	28	30
	kW	12.1	14.0	15.5	22.4	28.0	33.5	40.0	45.0	47.5	50.0	53.0	56.0	61.5	67.0	73.5	80.0	85.0
KXZ3 New Standard																		
KXZ3 New Hi-COP combination																		
KXZ2 Standard																		
KXZ2 Hi-COP combination																		
KXZ2 Heat Recovery																		
KXZ2 Heat Recovery Hi-COP combination																		
Micro KXZ																		
Micro KXZ																		
KXZ Lite																		
KXZ Water cooled series																		

KXZ3

- S** Small Capacity Model
- M** Medium Capacity Model
- L** Large Capacity Model

KXZ 2

-  **Small** Capacity Model
-  **Large** Capacity Model

Combination

+

VRF MULTI SYSTEM

The KXZ is a Variable Refrigerant Flow (VRF) multi-system air conditioner from Mitsubishi Heavy Industries, designed to deliver superior cooling and heating performance for a wide range of commercial application.

Micro KXZ



KXZ2



KXZ3



Diverse Lineup

With **capacities ranging from 4HP to 72HP**, configurations can include either a single outdoor unit or combinations of up to three units to meet varying cooling and heating demands. A diverse selection of indoor units is also available, tailored to suit different applications and capacity requirements.

Exceptional Design Flexibility

KX series range includes compact units, such as the **Micro KXZ series**, ideal for small installation spaces, as well as larger units like the **KXZ2** and **KXZ3** series, featuring an **extended total refrigerant piping length of up to 1,000 meters**. This versatility makes the range suitable for a variety of applications, from small and medium-sized buildings to large structures.



Heat Recovery Technology

(Available on certain models)

These systems **provide both heating and cooling to individual indoor units** based on specific room requirements. Heat generated during the cooling process is efficiently re-purposed as a heat source for heating, delivering significant energy savings.

Low GWP Refrigerant

(KXZ3 and Micro KXZ series)

The KXZ3 utilizes R32 refrigerant, which has a **GWP of 675—approximately one-third that of the conventional R410A refrigerant (GWP 2088)**. This transition significantly reduces environmental impact, helping you achieve your net zero goals.

Sleek Design, that Harmonize With Buildings

(KXZ3)

The KXZ3 series has been designed to incorporate a blue ornamentation that creates a cohesive look when installed consecutively, resulting in a **modern aesthetic that blends seamlessly with any building**.

As part of its mission, the Mitsubishi Heavy Industries Group will continue driving innovation to achieve net-zero emissions society.

Mitsubishi Heavy Industries Thermal Systems, Ltd., a part of Mitsubishi Heavy Industries (MHI) Group, will contribute to the establishment of a sustainable society by underpinning industries and people's daily lives, by providing environmentally friendly thermal solutions that meet diverse market needs.



Development History of the MHI's VRF KX Series

MHI's VRF systems have a long history dating back to 1984. For the global market, the first lineup, the **KX Series**, was introduced in 1994. The upward flow type has continuously evolved, and now, with the introduction of the new mid- and large-capacity models, the **KXZ3 Series** represents the latest stage of this evolution.



VRF System Installation by Mitsubishi Heavy Industries Thermal Systems

Case study : Education



We're proud to have equipped Crossways Academy in Lewisham with our advanced VRF system, creating a more comfortable and conducive learning environment.

Maintaining an optimal temperature in spaces occupied by large groups of students presents unique challenges. These include frequent entry and exit movements, heat fluctuations from IT equipment, and managing glare with electric blinds.

The Mitsubishi Heavy Industries Thermal Systems VRF KX system offers an efficient solution. The building incorporates natural ventilation with electronically operated windows, and the air conditioning system is seamlessly integrated to automatically shut down when windows are open.

Specifically designed for retrofit applications, the VRF KX system delivers flexibility, energy efficiency, and comfort, making it the perfect fit for modern educational spaces.

Case study : Hotel and Leisure



Mitsubishi Heavy Industries (MHI) Thermal Systems' VRF heat recovery systems, part of the KX range, are expertly designed to meet the demanding needs of luxury hotels and high-traffic spaces like airport-style bus stations. Featuring advanced inverter technology, these systems adjust compressor output in real-time to precisely align with the cooling or heating demands of indoor units. This ensures maximum comfort and energy efficiency in even the most challenging environments.

By choosing our versatile heating and cooling solution, you're not only reducing energy consumption but also gaining fine-tuned control over room temperatures. Our system allows for customized heating and cooling in different areas based on specific needs.

For example, in sun-exposed, south-facing rooms where temperatures tend to rise, you can easily increase the cooling to maintain comfort. In contrast, in cooler or shaded areas, the system efficiently adjusts to provide necessary heating, ensuring a consistent and comfortable environment throughout the space.

This flexibility empowers you to optimize energy usage based on varying environmental conditions, improving both comfort and efficiency across your entire building.

KXZ3 series

KXZ3

The redesigned model with R32 refrigerant has been engineered by the following 6 concepts.

New Design - 6 concepts -

1 Global Environment

- Reduce CO2 emission by about 70%

2 Wide Design Flexibility

- New exterior design to fit the scenery
- Various types of indoor units available
- Wider limitation of piping installation
- Flexible selection of safety systems

3 Improved Energy Efficiency

- Higher SCOP & SEER
- New R32 scroll compressor
- Heat exchanger with small heat transfer pipe
- Optimized fan and flow path design
- VTCC⁺ : advanced variable temperature and capacity control

4 Wellness & Comfort

- Advanced continuous heating
- Four steps of capacity control

5 Toughness

- Cooling use in high ambient temperature
- Strengthened resistance against corrosion & frost
- Long life and efficiency for the system

6 Serviceability

- Easy access to replacement parts

Small Capacity Model




New

Medium Capacity Model



New

Large Capacity Model



Concept 1

Global Environment



Meet our new R32 KXZ3 series of heat pumps, the perfect climate solution for heating and cooling commercial and industrial applications.

By optimizing the series with R32 refrigerant the following has increased


- Energy efficiency
- Cost effectiveness
- Overall performance
- Reduction in environmental impact



R32

A Low GWP Refrigerant

The Decision by MHI to transition to a new refrigerant is driven by many factors. KXZ3 with the use of R32 refrigerant, lower GWP (675) than R410A (2088)



1. A single component, easy to handle refrigerant
2. Known as a component of the blend R410A (50% R32, 50% R125)
3. Already used in Air-Conditioning systems worldwide
4. Zero Ozone Depletion
5. Superior Energy Efficiency vs. R410A
6. Reduced refrigerant charge vs. R410A
7. Easy to recycle

Harmonize with buildings

Concept 2

Wide Design Flexibility

New exterior design to fit the scenery

1. Unobtrusive while a refined image

The **KXZ3** blends seamlessly into modern city architecture and various environments. The exterior has been engineered with consideration for various installation settings. It remains unobtrusive while providing a refined image to its surroundings.

Rounded corners make it slim and light. The blue line and fin guard's grid shape create a strong consistent image.

The front panel's flat, trenchless surface with screws in the blue ornamentation provides a smooth texture.

The design reflects these improvements. Distinctive features such as the blue line and the fin grid convey a clear but unobtrusive message, whether as a stand-alone unit or in a combined installation.

The design allows for seamless integration into various building environments in the society.



A'DESIGN AWARD 2025

The KXZ3 Series has been honored with the prestigious Platinum A'DESIGN AWARD 2025 in the Industrial Design Category, the highest distinction awarded by A'DESIGN AWARD, representing a first-place recognition among thousands of global entries for its exceptional design excellence and innovation.

The KXZ3 has an impactful exterior while remaining unobtrusive, providing a refined image to its surroundings. The unit has a unique exterior, however when installed, the unit blends in and provides the refined image to the installed buildings.



In combination use


Blue ornamentation and a grid-shaped fin guard

Gives the unit a striking yet sophisticated appearance, while enhancing its cohesive image when installed in combination



Parallel and Diagonal Fin Guard

The parallel and diagonal grid-shaped design also adds both visual impact and harmony to the overall aesthetic, contributing to a sleek and refined look for the buildings.



Continuous Horizontal Blue Line

When installed in combination, the blue ornamentation forms a continuous horizontal blue line, enhancing the unit's cohesive appearance.



2. Outdoor units

- Product line-up -

Our line-up and limitation of use make it possible to adopt wider range of installation on commercial buildings.

Compact design

One of the smallest in the industry

The **KXZ3 series** has reduced the installation space with the integral structure of the heat exchanger and the mechanical components.

The total footprint has become more compact compared to our previous model.

KXZ2

10 - 12HP



Comparing with 12HP

New

KXZ3

8 - 12HP



Footprint has become more compact (compared to previous model)

8 - 12HP

New 14 - 18HP

New 19 - 24HP

Small Capacity Model

Medium Capacity Model

Large Capacity Model



0.97

0.699 (m²)

KXZ2

0.97

0.93 (m²)

KXZ2


1.33 (m²)

KXZ2

KXZ3


(*1) Compared with
FDC335KXZE2 x 2

Compact or Hi-cop combination



Expand to 72HP

The new product line-up of our KXZ3 series has been extended to offer solutions delivering up to 72HP when using a combination of 3 outdoor units.



up to 72HP

By combining 3 outdoor units 72HP can be achieved.





Various types of indoor units available

3. Indoor units

- Product line-up -

Wide variety of
14 types 78 models



For KXZ3			Capacity : HP	0.5	0.8	1	1.25	1.6	2	2.5	3.2	4	5	6	8	10
			Model Code : kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0	22.4	28.0
Ceiling Cassette	4way	FDT					●	●	●	●	●	●	●	●	●	●
	4way Compact	FDTC		●	●	●	●	●	●	●						
	2way	FDTW				●			●	●	●	●	●	●		
	1way	FDTS						●		●						
	1way Compact	FDTQ			●	●	●									
Duct Connected	High Static Pressure	FDU						●	●	●	●	●	●	●	●	●
	Low/Middle Static Pressure	FDUM			●	●	●	●	●	●	●	●	●	●	●	
	Low Static Pressure (thin)	FDUT		●	●	●	●	●	●	●						
	Compact & Flexible	FDUH			●	●	●									
Wall mounted		FDK		●	●	●	●	●	●	●	●					
Ceiling Suspended		FDE						●	●	●	●	●	●	●		
Floor Standing	2way	FDFW				●			●	●						
	With Casing	FDL									●					
	Without Casing	FDFU				●			●	●	●					

Connectability

KXZ3 - Standard Connectable Indoor Units



Increased number of connectable units and max capacity connection.

Standard KXZE3	HP	8	10	12	14	16	18	19	20	22	24	26	28 - 72
	Numbers	22	28	33	40	45	50	53	56	61	67	73	80
	IU Capacity connection	50 - 150% ^{(*)2}											

(*)2 When connecting the indoor unit type FDK, FDFW, FDFL, FDFU series, limit the connectable capacity not higher than 130%.

Wider limitation of piping installation

4. Flexible pipe installation


Total length
1000 m

Furthest indoor unit
Actual length **160m**

The piping length of our KXZ series have been extended with a maximum height difference between indoor units of up to 30m enabling installation of indoor units on an extra three floors. Also, the furthest unit can be installed up to 160m from outdoor unit.

(*)1 : The difference between the longest and the shortest indoor unit piping from the first branch must be within 40m.

(*)2 : It is necessary to change the setting corresponding to each height difference in installation. The range of use is also different.



Flexible selection of safety systems

4. Safety system R32 refrigerant



R32 refrigerant is categorized as mildly flammable (A2L) by International Standard ISO817. Safety measures specified in safety standard IEC60335-2-40 Ed.6.0. must be observed when installing or using R32 refrigerant equipment. The necessity of safety measures and the type and number of required safety equipment depend on the conditions of each room in the building.

1. Refrigerant leak detector

2. Safety alarm

3. Shut-off valve

4. Ventilator

MHI option has not been prepared.

The necessity of safety measures and the type and number of required safety equipment depend on the conditions of each room in the building. Safety equipment units are grouped into the following categories.

Refrigerant leak detector (Safety alarm)



RLD-KIT-E

Remote Controller (Safety alarm)



RC-EX3D



RC-ES1

Shut-off valve




SV-KIT-S1N-E
SV-KIT-L1N-E

H254 x W489 x D297 mm
(without piping)

Example of the safety system

1. Refrigerant leak detected
2. Safety alarm is sounded, and flow of refrigerant is blocked.

- (a) : Refrigerant leak detector detects refrigerant leakage in the room.
- (b)-1 : Safety alarm sounds and light alerts to signal refrigerant leakage.
- (b)-2 : Shut-off valve in the refrigerant pipe closes and blocks the flow of refrigerant.



E23 Refrigerant is leaking. Ventilate room.
Phone No. 000-000-0000
F1:High power F2:Energy-saving

Leakage detection error [E23] is displayed on the remote control in the room where the air-conditioner is installed and the operation is stopped.

Our safety system offers wide flexibility of installation for safety measures. Safety system can be installed only to the rooms that are necessary.



System diagram

One indoor unit &
Multiple indoor units,
one shut-off valve

1

1 2 3

One indoor unit &
one shut-off valve

2

3

4 Multiple
indoor units &
one shut-off valve

5

Multiple indoor units without
shut-off valve and leak detector

KXZ3

Refrigerant leak detector and shut-off
valve may not be required depending
on the room size.

Available for
Micro KXZ / KXZ3 Series



Only indoor units from the KXZE3-W Series
with either the RC-EX3D or RC-ES1 remote
control are connectable.

Relay Kit

For the following models a relay kit is required
to connect to the shut off valve.

FDUT--KXZE3-W* **FDUH--KXZE3-W** **FDFW--KXZE3-W**
FDTQ--KXZE3-W **FDFL--KXZE3-W** **FDFU--KXZE3-W**

*Excluding FDUT71KXZE3-W




Improved Energy Efficiency

Higher SCOP & SEER


Increased seasonal efficiencies

Our KXZ3 series provide high performance and excellent energy savings across all ranges. This is achieved by the optimized heat exchangers with the increased capacities and the advanced energy efficient compressor.

Cooling mode Comparison of SEER



Heating mode Comparison of SCOP



SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281.
Temperature conditions for calculating SCOP are based on "Average climate".



Features

Improved seasonal efficiency is achieved by

- 1 New R32 scroll compressor with the improved scroll mechanism and motor.
- 2 Heat exchanger with small copper pipe (Φ7)
- 3 Optimized fan and airflow path design
- 4 Advanced VTCC⁺ control



New R32 scroll compressor with the improved scroll mechanism and motor

1 New scroll compressor

With the adaptation of new components and its optimization, the KXZ3 series is now available in R32 refrigerant with a higher efficiency and a wide operation range. The new compressor uses the latest compressor technology and has proven to be extremely reliable.

New Technology

1. New liquid injection structure to cool down the refrigerant

Leading to
the wide operation range

2. Redesign of the spiral structure of the scroll

Leading to
higher efficiency

3. Larger motor with an optimized winding structure of the coil

Leading to
the wide operation range
and improved efficiency


4. New oil circuit that returns the oil to the bottom of the compressor, decreasing the amount of discharge oil at high rotation range.

Leading to
higher efficiency




Expansion of minimum | Rotation speed of the compressor

Achieving precise performance control



Improved energy savings and comfort at set temperature



Heat exchanger with small heat transfer pipe ($\Phi 7.0$)

2 Improved heat exchanger



Adopting a slimmer 7.0mm copper pipe. By increasing the number of the copper pipe and fin, the performance level has improved while keeping the heat exchanger size small.



The adoption of the new slim heat exchanger has resulted in a more compact size and reduced refrigerant volume, while maintaining higher overall performance and efficiency compared to the previous model.

Heat exchanger:
(10HP)

-30%
in volume

-12%
in surface area



Slimmer heat exchanger and a dense copper piping



Optimized fan and flow path design

3 Optimized air flow structure


Pressure loss in air flow path is minimized with the newly designed impeller and optimized path, dedicating better energy efficiency. Regulated air flow by optimized flow path leads to more efficient heat exchange.



Extended external static pressure

Max: 90 Pa

Flexibility to meet installation location needs.



VTCC⁺ : advanced variable temperature and capacity control

4 KX VRF redesigned with VTCC⁺

New Variable Temperature and Capacity Control



New VRF control VTCC⁺ adjusts the target pressure of the refrigerant automatically according to the requirement load of the indoor rooms in partial load conditions. These smooth adjustments ensure an optimal capacity usage of the indoor units as well as maximised energy savings. Ultimately this also increases comfort for the user.

- Most balanced mode between capacity control and energy saving
- Target pressure is automatically adjusted according to heating/cooling requirement, which achieves energy saving
- Advanced capacity control achieves smooth temperature control close to set temperature
- Suitable for heating/cooling demand varies among the room in the building


New Saving mode

- Suitable for the building with strict energy target
- Target pressure would be fixed based on the selected eco level (Low / Medium / High / U-high)

Standard mode






- Capacity is maximised
- Suitable for high heating/cooling demand in the building
- Target pressure is adjusted steady to maximize the capacity

VTCC⁺ concept image



* Saving mode(U-High) compared to standard mode in the following conditions
Cooling : Outside temperature 20°CDB, Partial load factor 21%, Set temperature 27°C
Heating : Outside temperature 12°CDB/11°CWB, Partial load factor 15%, Set temperature 20°C

Better partial load performance



Wellness & Comfort




Advanced continuous heating

Continuous heating with two defrost modes


Two defrost modes are prepared, and the defrost is automatically switched according to the amount of frost formation. Hot gas defrost mode enables non-stop heating during defrost operation with of hot gas bypass.

Enhanced heating operation functions



The comparison between the air outlet temperature of normal defrost and hot gas defrost


- Reduction in the time period of temperature drop caused by defrost
- Mitigation in temperature drop caused by defrost



Four steps of capacity control

Capacity control with 80%, 60%, 40%, 0% (off)

The peak cut function can easily be set on the controller. This function makes the control of the capacity easier and allow a better energy management over the long term. Four steps of capacity control are available with 80%, 60%, 40%, 0% (off). Schedule can be set up to 4 operations/day.



Concept 5

Toughness

Cooling use in high ambient temperature


Wide range of operation

Our new advanced technology has expanded the heating and cooling operation range.

KXZ3 series permits an extensible system design with a heating range operation down to -25°C and a cooling range operation up to 52°C .



* With limitation to piping length and height difference between indoor and outdoor units.



Strengthened resistance against corrosion & frost

Blue fin


Due to application of **blue coated fins** on the heat exchanger of the new outdoor unit, corrosion resistance has been improved compared to previous models. Resistance against frost has been strengthened by adopting the energy efficient heat-exchanger.



Long life and efficiency for the system

Oil level control capability

Our **proprietary technology** adjusts the oil level when combining two or three outdoor units, achieving level operation rate, keeping performance of the units and ensuring long life of the system.



Energy efficient and environmentally conscious

Several radical design changes and engineering developments have brought about a vast improvement in energy efficiency and environmental protection.

SEER and SCOP is defined in European regulations listed below.

No.2016/2281: requirement for air-heating products, cooling products, high temperature process chillers and fan coil units.

Seasonal efficiency is the new way of rating the true efficiency of heating and cooling products over an entire year.

Set by the EU's new regulation implementing Eco-Design Directive for Energy related Product (ErP) which specifies the minimum efficiency of air-conditioners manufacturers must integrate into their products.

The new Seasonal Efficiency rating system that must be used for heating and cooling by all manufacturers are;

SEER - Seasonal Efficiency Ratio (value in cooling)

This ratio represents the annual cooling performance divided by the annual consumption of electricity for cooling.

SCOP - Seasonal Coefficient of Performance (value in heating)

This ratio is calculated as the divided reference annual heating performance by the annual consumption of electricity for heating.

RoHS - Restriction of Hazardous substances

In order to avoid the release of hazardous substances into the environment, all models have utilized lead-free solder application. It has been considered to be difficult to use lead-free solder for practical applications because it requires higher solder temperatures at assembly, which can jeopardize reliability.

However our PbF soldering method can produce a higher quality lead-free printed circuit board.



8-12 HP (22.4kW – 33.5kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SEER with advanced technology
- VTCC+ : advanced variable temperature and capacity control
- Compact design with a small total footprint
- Advanced continuous heating



The KXZ3 Series has been honored with the prestigious Platinum A' Design Award 2025 in the Industrial Design Category, the highest distinction awarded by A' Design Award, representing a first-place recognition among thousands of global entries for its exceptional design excellence and innovation.



FDC224-335

■ SPECIFICATIONS

Item	Model	FDC224KXZE3A	FDC280KXZE3A	FDC335KXZE3A	
Nominal horse power		8	10	12	
Power source		3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	22.4	28.0	33.5	
	Heating	22.4	28.0	33.5	
Max heating capacity	kW	25.0	31.5	37.5	
Power consumption	Cooling	5.52	8.05	9.69	
	Heating	4.58	6.35	7.98	
EER		4.06	3.48	3.46	
COP		4.90	4.41	4.20	
SEER		9.16	8.96	8.57	
SCOP		4.82	4.75	4.67	
Exterior dimensions (HxWxD)	mm	1750 x 920 x 760			
Net weight	kg	262			
Sound power level	Cooling	76.0	77.0	82.0	
	Heating	78.0	83.0	86.0	
Sound pressure level	Cooling	55.0	56.0	60.0	
	Heating	55.0	60.0	63.0	
Starting current	A		5		
Max current	A	20.7	23.2	25.7	
	Type / GWP	R32 / 675			
Refrigerant	Charge	kg	7.1	7.7	
	TCO ₂ Eq		4.793	5.198	
Refrigerant piping size	Liquid	mm	ø9.52 (3/8")	ø12.7 (1/2")	
	Gas	(in)	ø19.05 (3/4")	ø22.22 (7/8")	
Total piping length	m		1000		
Outdoor operating temperature range	Cooling	°CDB	-15 to 52		
	Heating	°CWB	-25 to 16		
Capacity connection	%		50-150		
Number of connectable indoor units		1 to 22	1 to 28	1 to 33	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No 2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

14-18 HP (40.0kW – 50.0kW)

VTCC⁺

Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC400-500

■ SPECIFICATIONS

Item	Model	FDC400KXZE3		FDC450KXZE3		FDC500KXZE3						
Nominal horse power		14		16		18						
Power source		3 Phase 380–415V, 50Hz										
Nominal capacity	Cooling	kW	40.0	45.0	50.0							
	Heating		40.0	45.0	47.5							
Max heating capacity		kW	45.0	50.0	56.0							
Power consumption	Cooling	kW	11.73	14.88	17.70							
	Heating		8.42	10.14	10.86							
EER			3.41	3.02	2.82							
COP			4.75	4.43	4.37							
SEER			8.58	8.10	7.90							
SCOP			4.52	4.59	4.45							
Exterior dimensions (HxWxD)	mm	1750 x 1220 x 760										
Net weight	kg	352										
Sound power level	Cooling	dB(A)	79.0	82.0	84.5							
	Heating		84.5	89.0	90.0							
Sound pressure level	Cooling	dB(A)	56.0	59.0	61.5							
	Heating		61.5	66.0	67.0							
Starting current	A	5										
Max current	A	32.4		36.3	40.5							
Refrigerant	Type / GWP	R32 / 675										
	Charge	kg	8.7									
	TCO ₂ Eq		5.873									
Refrigerant piping size	Liquid	mm (in)	ø12.7 (1/2")									
	Gas		ø28.58 (1-1/8")									
Total piping length	m	1000										
Outdoor operating temperature range	Cooling	°CDB	-15 to 52									
	Heating	°CWB	-25 to 16									
Capacity connection	%	50-150										
Number of connectable indoor units		1 to 40	1 to 45	1 to 50								

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

19-24 HP (53.0kW – 67.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC530-670

■ SPECIFICATIONS

Item	Model	FDC530KXZE3	FDC560KXZE3	FDC615KXZE3	FDC670KXZE3
Nominal horse power		19	20	22	24
Power source			3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	kW	53.0	56.0	61.5
	Heating		53.0	56.0	61.5
Max heating capacity		kW	59.0	61.5	69.0
Power consumption	Cooling	kW	15.20	16.20	18.77
	Heating		11.05	12.34	15.01
EER			3.48	3.45	3.27
COP			4.79	4.53	4.09
SEER			7.87	7.84	7.50
SCOP			4.68	4.66	4.49
Exterior dimensions (HxWxD)	mm		1750 x 1750 x 760		
Net weight	kg		445		
Sound power level	Cooling	dB(A)	81.5	82.0	85.0
	Heating		86.0	86.5	90.0
Sound pressure level	Cooling	dB(A)	59.0	59.5	62.5
	Heating		63.5	64.0	67.5
Starting current	A			8	
Max current	A		47.4	50.6	52.2
	Type / GWP			R32 / 675	
Refrigerant	Charge	kg		9.5	
	TCO ₂ Eq			6.413	
Refrigerant piping size	Liquid	mm		ø12.7 (1/2")	
	Gas	(in)		ø28.58 (1-1/8")	
Total piping length	m			1000	
Outdoor operating temperature range	Cooling	°CDB		-15 to 52	
	Heating	°CWB		-25 to 16	
Capacity connection	%			50-150	
Number of connectable indoor units		1 to 53	1 to 56	2 to 61	2 to 67

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

26-36 HP (73.5kW – 100.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC735



FDC800-1000

■ SPECIFICATIONS

Item	Model	FDC735KXZE3	FDC800KXZE3	FDC850KXZE3	FDC900KXZE3	FDC950KXZE3	FDC1000KXZE3
Combination		FDC335KXZE3A	FDC400KXZE3	FDC400KXZE3	FDC450KXZE3	FDC450KXZE3	FDC500KXZE3
		FDC400KXZE3	FDC400KXZE3	FDC450KXZE3	FDC450KXZE3	FDC500KXZE3	FDC500KXZE3
Nominal horse power		26	28	30	32	34	36
Power source				3 Phase 380-415V, 50Hz			
Nominal capacity	Cooling	kW	73.5	80.0	85.0	90.0	95.0
	Heating		73.5	80.0	85.0	90.0	95.0
Max heating capacity		kW	82.5	90.0	95.0	100.0	106.0
Power consumption	Cooling	kW	21.4	23.5	26.6	29.8	32.6
	Heating		16.4	17.7	19.3	20.8	21.0
EER			3.43	3.41	3.19	3.02	2.91
COP			4.48	4.51	4.40	4.32	4.39
SEER			8.57	8.58	8.34	8.10	8.00
SCOP			4.59	4.52	4.55	4.59	4.52
Net weight		kg	626		704		
Max current		A	58.1	64.8	68.7	72.6	76.8
Refrigerant piping size	Liquid				ø15.88 (5/8")		
	Gas	mm (in)			ø34.92 (1-3/8")		
	Oil equalization				ø12.7 (1/2")		
Total piping length		m			1000		
Outdoor operating temperature range	Cooling	°CDB			-15 to 52		
	Heating	°CWB			-25 to 16		
Capacity connection		%			50-150		
Number of connectable indoor units		2 to 73			2 to 80		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

38-48 HP (106.0kW – 134.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC+ : advanced variable temperature and capacity control
- Advanced continuous heating

New



■ SPECIFICATIONS

Item	Model	FDC1060KXZE3	FDC1120KXZE3	FDC1175KXZE3	FDC1230KXZE3	FDC1285KXZE3	FDC1340KXZE3
Combination		FDC530KXZE3	FDC560KXZE3	FDC560KXZE3	FDC615KXZE3	FDC615KXZE3	FDC670KXZE3
		FDC530KXZE3	FDC560KXZE3	FDC615KXZE3	FDC615KXZE3	FDC670KXZE3	FDC670KXZE3
Nominal horse power		38	40	42	44	46	48
Power source				3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	kW	106.0	112.0	117.5	123.0	128.5
	Heating		106.0	112.0	117.5	123.0	130.0
Max heating capacity		kW	118.0	123.0	130.5	138.0	144.0
Power consumption	Cooling	kW	30.5	32.5	35.0	37.6	43.3
	Heating		22.1	24.7	27.4	30.1	30.8
EER			3.48	3.45	3.35	3.27	2.97
COP			4.79	4.53	4.28	4.09	4.10
SEER			7.87	7.84	7.67	7.50	7.56
SCOP			4.62	4.57	4.52	4.49	4.56
Net weight		kg			890		
Max current		A	94.8	101.2	102.8	104.4	107.6
Refrigerant piping size	Liquid				ø19.05 (3/4")		
	Gas	mm (in)			ø34.92 (1-3/8")		
	Oil equalization				ø12.7 (1/2")		
Total piping length		m			1000		
Outdoor operating temperature range	Cooling	°CDB			-15 to 52		
	Heating	°CWB			-25 to 16		
Capacity connection		%			50–150		
Number of connectable indoor units			2 to 80			3 to 80	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

50–54 HP (140.0kW–150.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



■ SPECIFICATIONS

Item	Model	FDC1400KXZE3	FDC1450KXZE3	FDC1500KXZE3
Combination	FDC450KXZE3	FDC450KXZE3	FDC500KXZE3	
	FDC450KXZE3	FDC500KXZE3	FDC500KXZE3	
	FDC500KXZE3	FDC500KXZE3	FDC500KXZE3	
Nominal horse power	50	52	54	
Power source		3 Phase 380–415V, 50Hz		
Nominal capacity	Cooling Heating	kW	140.0 137.5	145.0 140.0
Max heating capacity		kW	156.0	162.0
Power consumption	Cooling Heating	kW	47.5 31.2	50.4 31.9
EER			2.94	2.87
COP			4.40	4.38
SEER			8.03	7.96
SCOP			4.54	4.49
Net weight	kg		1056	
Max current	A	113.1	117.3	121.5
Refrigerant piping size	Liquid Gas Oil equalization	mm (in)	ø19.05 (3/4") ø34.92(1-3/8") ø12.7 (1/2")	ø41.28(1-5/8")
Total piping length	m		1000	
Outdoor operating temperature range	Cooling Heating	°CDB °CWB	-15 to 52 -25 to 16	
Capacity connection	%		50–150	
Number of connectable indoor units			3 to 80	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

57-60 HP (159.0kW – 168.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC1560-1680

■ SPECIFICATIONS

Item	Model	FDC1560KXZE3	FDC1620KXZE3	FDC1680KXZE3
Combination	FDC530KXZE3	FDC530KXZE3	FDC560KXZE3	FDC560KXZE3
	FDC530KXZE3	FDC530KXZE3	FDC560KXZE3	FDC560KXZE3
	FDC530KXZE3	FDC560KXZE3	FDC560KXZE3	FDC560KXZE3
Nominal horse power	57	58	60	
Power source		3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	159.0	162.0	168.0
	Heating	159.0	162.0	168.0
Max heating capacity	kW	177.0	179.5	184.5
Power consumption	Cooling	45.7	46.7	48.7
	Heating	33.2	34.5	37.1
EER		3.48	3.46	3.45
COP		4.79	4.69	4.53
SEER		7.87	7.86	7.84
SCOP		4.68	4.67	4.66
Net weight	kg		1335	
Max current	A	142.2	145.4	151.8
Refrigerant piping size	Liquid	mm (in)	ø19.05 (3/4")	
	Gas		ø41.28 (1-5/8")	
	Oil equalization		ø12.7 (1/2")	
Total piping length	m		1000	
Outdoor operating temperature range	Cooling	°CDB	-15 to 52	
	Heating	°CWB	-25 to 16	
Capacity connection	%		50-150	
Number of connectable indoor units			3 to 80	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

62-72 HP (173.5kW – 201.0kW)

VTCC⁺

Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC1735–2010

■ SPECIFICATIONS

Item	Model	FDC1735KXZE3	FDC1790KXZE3	FDC1845KXZE3	FDC1900KXZE3	FDC1955KXZE3	FDC2010KXZE3
Combination	FDC560KXZE3	FDC560KXZE3	FDC615KXZE3	FDC615KXZE3	FDC615KXZE3	FDC615KXZE3	FDC670KXZE3
	FDC560KXZE3	FDC615KXZE3	FDC615KXZE3	FDC615KXZE3	FDC670KXZE3	FDC670KXZE3	FDC670KXZE3
	FDC615KXZE3	FDC615KXZE3	FDC615KXZE3	FDC670KXZE3	FDC670KXZE3	FDC670KXZE3	FDC670KXZE3
Nominal horse power		62	64	66	68	70	72
Power source				3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	173.5	179.0	184.5	190.0	195.5	201.0
	Heating	173.5	179.0	184.5	188.0	191.5	195.0
Max heating capacity		192.0	199.5	207.0	213.0	219.0	225.0
Power consumption	Cooling	51.3	53.8	56.4	62.1	67.7	73.4
	Heating	39.8	42.4	45.1	45.9	46.6	47.3
EER		3.38	3.32	3.27	3.06	2.88	2.74
COP		4.36	4.21	4.09	4.10	4.11	4.12
SEER		7.72	7.61	7.50	7.54	7.58	7.63
SCOP		4.60	4.54	4.49	4.53	4.58	4.63
Net weight	kg			1335			
Max current	A	153.4	155.0	156.6	159.8	163.0	166.2
Refrigerant piping size	Liquid	mm (in)					
	Gas						
	Oil equalization						
Total piping length	m			1000			
Outdoor operating temperature range	Cooling	°CDB		-15 to 52			
	Heating	°CWB		-25 to 16			
Capacity connection	%			50–150			
Number of connectable indoor units				4 to 80			

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

16-24 HP (44.8kW – 67.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating



FDC450-670

■ SPECIFICATIONS

Item	Model	FDC450KXZVE3	FDC500KXZVE3	FDC560KXZVE3	FDC615KXZVE3	FDC670KXZVE3
Combination	FDC224KXZE3A	FDC224KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC335KXZE3A	FDC335KXZE3A
	FDC224KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC335KXZE3A	FDC335KXZE3A	FDC335KXZE3A
Nominal horse power		16	18	20	22	24
Power source				3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	kW	44.8	50.4	56.0	61.5
	Heating		44.8	50.4	56.0	61.5
Max heating capacity		kW	50.0	56.5	63.0	69.0
Power consumption	Cooling	kW	11.0	13.6	16.1	17.7
	Heating		9.1	10.9	12.7	14.3
EER			4.06	3.71	3.48	3.46
COP			4.90	4.61	4.41	4.29
SEER			9.16	9.02	8.97	8.74
SCOP			4.82	4.78	4.75	4.70
Net weight		kg		524		536
Max current		A	41.4	43.9	46.4	48.9
Refrigerant piping size	Liquid	mm (in)		ø12.7 (1/2")		
	Gas			ø28.58 (1-1/8")		
	Oil equalization			ø12.7 (1/2")		
Total piping length		m		1000		
Outdoor operating temperature range	Cooling	°CDB		-15 to 52		
	Heating	°CWB		-25 to 16		
Capacity connection		%		50-150		
Number of connectable indoor units			1 to 45	1 to 50	1 to 56	2 to 61
						2 to 67

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

26–36 HP (72.8kW – 100.5kW)



VTCC⁺

Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating



FDC735-1000

■ SPECIFICATIONS

Item	Model	FDC735KXZVE3	FDC800KXZVE3	FDC850KXZVE3	FDC900KXZVE3	FDC950KXZVE3	FDC1000KXZVE3
Combination	FDC224KXZE3A	FDC224KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC335KXZE3A	FDC335KXZE3A
	FDC224KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC335KXZE3A	FDC335KXZE3A	FDC335KXZE3A
	FDC280KXZE3A	FDC280KXZE3A	FDC280KXZE3A	FDC335KXZE3A	FDC335KXZE3A	FDC335KXZE3A	FDC335KXZE3A
Nominal horse power	26	28	30	32	34	36	
Power source			3 Phase 380–415V, 50Hz				
Nominal capacity	Cooling	kW	72.8	78.4	84.0	89.5	95.0
	Heating		72.8	78.4	84.0	89.5	95.0
Max heating capacity		kW	81.5	88.0	94.5	100.5	106.5
Power consumption	Cooling	kW	19.1	21.6	24.1	25.8	27.4
	Heating		15.5	17.3	19.0	20.7	22.3
EER			3.81	3.62	3.48	3.47	3.46
COP			4.69	4.53	4.41	4.32	4.25
SEER			9.07	9.02	8.97	8.81	8.68
SCOP			4.79	4.78	4.75	4.72	4.69
Net weight	kg		786		798	810	822
Max current	A	64.6	67.1	69.6	72.1	74.6	77.1
Refrigerant piping size	Liquid	mm (in)			ø15.88 (5/8")		
	Gas				ø34.92 (1-3/8")		
	Oil equalization				ø12.7 (1/2")		
Total piping length	m				1000		
Outdoor operating temperature range	Cooling	°CDB			-15 to 52		
	Heating	°CWB			-25 to 16		
Capacity connection	%				50–150		
Number of connectable indoor units	2 to 73				2 to 80		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

38, 40 HP (107.0kW, 113.5kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



■ SPECIFICATIONS

Item	Model		FDC1060KXZVE3	FDC1120KXZVE3		
Combination			FDC335KXZE3A	FDC335KXZE3A		
			FDC335KXZE3A	FDC400KXZE3		
			FDC400KXZE3	FDC400KXZE3		
Nominal horse power			38	40		
Power source			3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	kW	107.0	113.5		
	Heating		107.0	113.5		
Max heating capacity		kW	120.0	127.5		
Power consumption	Cooling	kW	31.1	33.1		
	Heating		24.4	24.8		
EER			3.44	3.42		
COP			4.39	4.57		
SEER			8.57	8.58		
SCOP			4.62	4.57		
Net weight		kg	900	978		
Max current		A	83.8	90.5		
Refrigerant piping size	Liquid	mm (in)	ø19.05 (3/4")			
	Gas		ø34.92 (1-3/8")			
	Oil equalization		ø12.7 (1/2")			
Total piping length		m	1000			
Outdoor operating temperature range	Cooling	°CDB	-15 to 52			
	Heating	°CWB	-25 to 16			
Capacity connection		%	50–150			
Number of connectable indoor units			2 to 80			

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

42-48 HP (120.0kW – 135.0kW)



Technical focus

- Available in the R32 refrigerant
- New exterior design containing cutting edge technology
- High SCOP & SEER with advanced technology
- VTCC⁺ : advanced variable temperature and capacity control
- Advanced continuous heating

New



FDC1175-1340

■ SPECIFICATIONS

Item	Model	FDC1175KXZVE3	FDC1230KXZVE3	FDC1285KXZVE3	FDC1340KXZVE3
Combination	FDC400KXZE3	FDC400KXZE3	FDC400KXZE3	FDC450KXZE3	FDC450KXZE3
	FDC400KXZE3	FDC400KXZE3	FDC450KXZE3	FDC450KXZE3	FDC450KXZE3
	FDC400KXZE3	FDC450KXZE3	FDC450KXZE3	FDC450KXZE3	FDC450KXZE3
Nominal horse power	42	44	46	48	
Power source		3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	120.0	125.0	130.0	135.0
	Heating	120.0	125.0	130.0	135.0
Max heating capacity	kW	135.0	140.0	145.0	150.0
Power consumption	Cooling	35.2	38.4	41.5	44.7
	Heating	25.3	27.0	28.7	30.5
EER		3.41	3.25	3.13	3.02
COP		4.75	4.62	4.52	4.43
SEER		8.58	8.42	8.26	8.10
SCOP		4.52	4.54	4.57	4.59
Net weight	kg		1056		
Max current	A	97.2	101.1	105.0	108.9
Refrigerant piping size	Liquid	mm (in)	ø19.05 (3/4")		
	Gas		ø34.92 (1-3/8")		
	Oil equalization		ø12.7 (1/2")		
Total piping length	m		1000		
Outdoor operating temperature range	Cooling	°CDB	-15 to 52		
	Heating	°CWB	-25 to 16		
Capacity connection	%		50–150		
Number of connectable indoor units			3 to 80		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2018 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.


KXZ2 series

KXZ2



Flexible Design

The KXZ2 series has a layered design and a refined new form. The flexibility in design and ease of installation are further enhanced to provide optimum response to medium and large building air-conditioning systems.




- 1 Highly efficient Heat exchanger
- 2 Optimised duct shape
- 3 Inverter control
- 4 DC Fan Motor
- 5 Rounded design
- 6 Compressor

The compressor has improved the units efficiency by innovating the thrust plate. Resulting a reduced friction loss, and increased reliability.

Wide range operation

Cooling range operation up to **52°C***




* With limitation to piping length and height difference between indoor and outdoor units.

Extended external static pressure

Max:
50 Pa to 85 Pa

Flexibility to meet installation location needs.



Indoor unit capacity connection

Increased number of connectable units and max capacity connection

(compared to KXZE1)



HP	10	12	14	16	17	18	20	22	24	26	28	30	32	34
Numbers	37	44	53	60	50	53	59	65	71	78		80		
IU Capacity connection	50 - 200% (*1)													50 - 160% (*1)

HP	36	38	40	42	44	46	48	50	52	54	56	58	60
Numbers	80												
IU Capacity connection	50 - 130% (*1)												

(*1) When connecting the indoor unit type FDK, FDFL, FDFU or FDFW series, limit the connectable capacity not higher than 130%.

Technology

CHCC

Continuous Heating Capacity Control

Our CHCC defrosting control has been added to our KXZ2 system and allows to achieve greater capacities than that of our previous model in low ambient temperature conditions. CHCC controls the target pressure automatically before the capacity drops, which increases the period of heating operation and reduces the systems defrosting time.

Long Pipe length

Total length	Furthest indoor unit
1000m	Actual length 160m
	Equivalent length 185m

The maximum height difference between indoor units is a maximum of 30m, and the maximum height difference between the outdoor unit and indoor unit is 90m.

For with few limitations, contributes to system design flexibility.

*1 The difference between the longest and the shortest indoor unit piping from the first branch must be within 40m. (MAX85m)

*2 It is necessary to change the setting corresponding to each height difference in installation. The range of use is also different.

VTCC


Variable Temperature and Capacity Control

Energy Savings*

34%


VTCC adjusts the target pressure of the refrigerant cycle in the outdoor unit automatically according to the demand of the indoor units in partial load conditions. These smooth adjustments ensure optimal usage of the indoor units as well as maximised energy savings. Ultimately this also increases comfort for the user.

* 34% energy savings are based on comparison with a KXZ standard model with VTCC vs. a KXZ standard model both under partial load condition.



Field service with smart device

Android™ only




Monitoring and service task could now be done with a smartphone or a tablet by connecting to the Mente PC converter.

"Android" is a trademark or registered trademark of Google LLC.



The data collected via the smart device could also be sent and viewed with our service software Mente PC.



To your PC monitoring and service tasks made simple with our service software ("Mente PC").

10, 12 HP (28.0kW • 33.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.86
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



Uniform footprint of models allows continuous side-by-side installation



FDC280 • 335

■ SPECIFICATIONS

Item	Model	FDC280KXZE2	FDC335KXZE2
Nominal horse power		10HP	12HP
Power source		3 Phase 380-415V, 50Hz	
Nominal capacity	Cooling	28.0	33.5
	Heating	31.5	37.5
Max heating capacity	kW	31.5	37.5
Power consumption ¹	Cooling	7.25	8.98
	Heating	7.41	9.03
EER ¹		3.86	3.73
COP ¹		4.25	4.15
SEER ¹		7.30	7.54
SCOP ¹		4.88	4.68
SEER ²		7.15	7.40
SCOP ²		4.88	4.68
Exterior dimensions (HxWxD)	mm	1697x1350x720	
Net weight	kg	288	
Sound power level ¹	Cooling	75	82
	Heating	76	81
Sound pressure level	Cooling	56	63
	Heating	57	62
Starting current	A	5	
Max current	A	20.1	
Refrigerant	Type / GWP	R410A / 2088	
Refrigerant	Charge	kg	11.0
	TCO ₂ Eq		22.968
Refrigerant piping size	Liquid	mm	ø9.52(3/8")
	Gas	(in)	ø22.22(7/8")
Total piping length	m		1000
Outdoor operating temperature range	Cooling	°CDB	-15 to 52
	Heating	°CWB	-20 to 15.5
Capacity connection	%		50-200
Number of connectable indoor units		37	44

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 Lot 6/21 performances.

*2 Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

14-20 HP (40.0kW – 56.0kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.64
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



Uniform footprint of all models allows continuous side-by-side installation



FDC400-560

■ SPECIFICATIONS

Item	Model	FDC400KXZE2	FDC450KXZE2	FDC475KXZE2	FDC500KXZE2	FDC560KXZE2
Nominal horse power		14HP	16HP	17HP	18HP	20HP
Power source				3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	kW	40.0	45.0	47.5	50.0
	Heating		45.0	50.0	53.0	56.0
Max heating capacity	kW		45.0	50.0	53.0	56.0
Power consumption ¹	Cooling	kW	10.98	13.98	13.97	14.01
	Heating		10.23	12.50	12.99	13.56
EER ¹			3.64	3.22	3.40	3.57
COP ¹			4.40	4.00	4.08	4.13
SEER ¹			7.12	7.01	6.84	7.29
SCOP ¹			4.87	4.36	4.45	4.58
SEER ²			7.00	6.90	6.68	7.12
SCOP ²			4.87	4.36	4.45	4.58
Exterior dimensions (HxWxD)	mm			2052x1350x720		
Net weight	kg		332			378
Sound power level ¹	Cooling	dB(A)	80	81	81	81
	Heating		82	82	81	82
Sound pressure level	Cooling	dB(A)	60	61	61	61
	Heating		62	62	61	62
Starting current	A		5			8
Max current	A		32.0			40.2
Refrigerant	Type / GWP			R410A / 2088		
Charge	kg			11.5		
TCO ₂ Eq				24.012		
Refrigerant piping size	Liquid	mm		ø12.7(1/2")		
	Gas	(in)	ø25.4(1") [ø28.58(1 1/8")]		ø28.58(1 1/8")	
Total piping length	m			1000		
Outdoor operating temperature range	Cooling	°CDB		-15 to 52		
	Heating	°CWB		-20 to 15.5		
Capacity connection	%		50-200		50-160	
Number of connectable indoor units		53	60	50	53	59

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 Lot 6/21 performances.

*2 Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

22-26 HP (61.5kW – 73.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.79
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



FDC615 • 670



FDC735

■ SPECIFICATIONS

Item	Model	FDC615KXZE2	FDC670KXZE2	FDC735KXZE2
Combination (FDC)		280KXZE2	335KXZE2	335KXZE2
		335KXZE2	335KXZE2	400KXZE2
Nominal horse power		22HP	24HP	26HP
Power source		3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	kW	61.5	67.0
	Heating		69.0	75.0
Power consumption	Cooling	kW	16.24	17.96
	Heating		16.44	18.06
EER		3.79	3.73	3.68
COP		4.20	4.15	4.28
Net weight		kg	576	620
Starting current		A	10	
Max current		A	40.2	52.1
Refrigerant	Type / GWP		R410A / 2088	
	Charge	kg	11.0+11.0	
Refrigerant piping size	Liquid	mm (in)	ø12.7(1/2")	
	Gas		ø28.58(1 1/8")	
	Oil equalization		ø9.52 (3/8")	
Total piping length		m	1000	
Outdoor operating temperature range	Cooling	°CDB	-15 to 52	
	Heating	°CWB	-20 to 15.5	
Capacity connection		%	50-160	
Number of connectable indoor units		65	71	78

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

28-40 HP (80.0kW – 112.0kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.64
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



FDC800-1120

■ SPECIFICATIONS

Item	Model	FDC800KXZE2	FDC850KXZE2	FDC900KXZE2	FDC950KXZE2	FDC1000KXZE2	FDC1060KXZE2	FDC1120KXZE2				
Combination (FDC)	400KXZE2	400KXZE2	450KXZE2	475KXZE2	500KXZE2	500KXZE2	560KXZE2	560KXZE2				
	400KXZE2	450KXZE2	450KXZE2	475KXZE2	500KXZE2	560KXZE2	560KXZE2	560KXZE2				
Nominal horse power	28HP	30HP	32HP	34HP	36HP	38HP	40HP					
Power source				3 Phase 380-415V, 50Hz								
Nominal capacity	Cooling	kW	80.0	85.0	90.0	95.0	100.0	106.0				
	Heating		90.0	95.0	100.0	106.0	112.0	119.0				
Power consumption	Cooling	kW	21.96	24.96	27.95	27.94	28.02	31.51				
	Heating		20.45	22.73	25.00	25.98	27.12	32.31				
EER		3.64	3.41	3.22	3.40	3.57	3.36	3.20				
COP		4.40	4.18	4.00	4.08	4.13	4.01	3.90				
Net weight	kg	664			756							
Starting current	A	10			16							
Max current	A	64.0			80.4							
Refrigerant	Type / GWP		R410A / 2088									
	Charge	kg	11.5+11.5									
Refrigerant piping size	Liquid	mm (in)	ø15.88(5/8")					ø19.05(3/4")				
	Gas		ø31.75(1 1/4") [ø34.92(1 3/8")]					ø38.1(1 1/2") [ø34.92(1 3/8")]				
	Oil equalization		ø9.52 (3/8")									
Total piping length	m	1000										
Outdoor operating temperature range	Cooling	°CDB	-15 to 52									
	Heating	°CWB	-20 to 15.5									
Capacity connection	%	50-160				50-130						
Number of connectable indoor units		80										

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

42-50 HP (120.0kW – 142.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.64
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



FDC1200-1425

■ SPECIFICATIONS

Item	Model	FDC1200KXZE2	FDC1250KXZE2	FDC1300KXZE2	FDC1350KXZE2	FDC1425KXZE2
Combination (FDC)	400KXZE2	400KXZE2	400KXZE2	450KXZE2	475KXZE2	
	400KXZE2	400KXZE2	450KXZE2	450KXZE2	475KXZE2	
	400KXZE2	450KXZE2	450KXZE2	450KXZE2	475KXZE2	
Nominal horse power		42HP	44HP	46HP	48HP	50HP
Power source			3 Phase 380-415V, 50Hz			
Nominal capacity	Cooling	kW	120.0	125.0	130.0	135.0
	Heating		135.0	140.0	145.0	150.0
Power consumption	Cooling	kW	32.94	35.94	38.93	41.93
	Heating		30.68	32.95	35.23	37.50
EER		3.64	3.48	3.34	3.22	3.40
COP		4.40	4.25	4.12	4.00	4.08
Net weight		kg	996			1134
Starting current		A	15			24
Max current		A	96.0			120.6
Refrigerant	Type / GWP		R410A / 2088			
	Charge	kg	11.5+11.5+11.5			
Refrigerant piping size	Liquid	mm (in)	ø19.05(3/4")			
	Gas		ø38.1(1 1/2") [ø34.92(1 3/8")]			
	Oil equalization		ø9.52 (3/8")			
Total piping length		m	1000			
Outdoor operating temperature range	Cooling	°CDB	-15 to 52			
	Heating	°CWB	-20 to 15.5			
Capacity connection		%	50-130			
Number of connectable indoor units			80			

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

52-60 HP (145.0kW – 168.0kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.57
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



FDC1450-1680

■ SPECIFICATIONS

Item	Model	FDC1450KXZE2	FDC1500KXZE2	FDC1560KXZE2	FDC1620KXZE2	FDC1680KXZE2
Combination (FDC)	475KXZE2	500KXZE2	500KXZE2	500KXZE2	500KXZE2	560KXZE2
	475KXZE2	500KXZE2	500KXZE2	560KXZE2	560KXZE2	560KXZE2
	500KXZE2	500KXZE2	560KXZE2	560KXZE2	560KXZE2	560KXZE2
Nominal horse power	52HP	54HP	56HP	58HP	60HP	
Power source			3 Phase 380-415V, 50Hz			
Nominal capacity	Cooling	kW	145.0	150.0	156.0	162.0
	Heating		162.0	168.0	175.0	182.0
Power consumption	Cooling	kW	41.95	42.03	45.52	49.01
	Heating		39.54	40.68	43.27	45.87
EER		3.46	3.57	3.43	3.31	3.20
COP		4.10	4.13	4.04	3.97	3.90
Net weight	kg			1134		
Starting current	A			24		
Max current	A			120.6		
Refrigerant	Type / GWP			R410A / 2088		
	Charge	kg		11.5+11.5+11.5		
Refrigerant piping size	Liquid	mm (in)		ø19.05(3/4")		
	Gas			ø38.1(1-1/2") [ø34.92(1-3/8")]		
	Oil equalization			ø9.52 (3/8")		
Total piping length	m			1000		
Outdoor operating temperature range	Cooling	°CDB		-15 to 52		
	Heating	°CWB		-20 to 15.5		
Capacity connection	%			50-130		
Number of connectable indoor units				80		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

20–32 HP (56.0kW – 89.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.86
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



FDC560



FDC850 · 900

■ SPECIFICATIONS

Item	Model	FDC560KXZXE2	FDC850KXZXE2	FDC900KXZXE2
Combination (FDC)	280KXZE2	280KXZE2	280KXZE2	280KXZE2
	280KXZE2	280KXZE2	280KXZE2	280KXZE2
	-	280KXZE2	335KXZE2	
Nominal horse power	20HP	30HP	32HP	
Power source		3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	56.0	84.0	89.5
	Heating	63.0	94.5	100.5
Power consumption	Cooling	14.51	21.76	23.49
	Heating	14.82	22.23	23.85
EER		3.86	3.86	3.81
COP		4.25	4.25	4.21
Net weight	kg	576	864	
Starting current	A	10	15	
Max current	A	40.2	60.3	
Refrigerant	Type / GWP		R410A / 2088	
	Charge	kg	11.0+11.0	
Refrigerant piping size	Liquid	mm	ø12.7(1/2")	
	Gas	(in)	ø28.58(1-1/8")	
	Oil equalization		ø31.75(1-1/4") [ø34.92(1-3/8")] ø9.52 (3/8")	
Total piping length	m		1000	
Outdoor operating temperature range	Cooling	°CDB	-15 to 52	
	Heating	°CWB	-20 to 15.5	
Capacity connection	%		80–160	
Number of connectable indoor units		59	80	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

34–40 HP (95.0kW – 113.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.77
- VTCC : advanced variable temperature and capacity control
- Total piping length up to 1000m and a maximum height difference between indoor unit is maximum of 30m.
- Wide range of operation.



■ SPECIFICATIONS

Item	Model	FDC950KXZXE2	FDC1000KXZXE2	FDC1060KXZXE2	FDC1120KXZXE2
Combination (FDC)		280KXZE2	335KXZE2	335KXZE2	335KXZE2
		335KXZE2	335KXZE2	335KXZE2	400KXZE2
		335KXZE2	335KXZE2	400KXZE2	400KXZE2
Nominal horse power		34HP	36HP	38HP	40HP
Power source		3 Phase 380-415V, 50Hz			
Nominal capacity	Cooling	kW	95.0	100.5	107.0
	Heating		106.5	112.5	120.0
Power consumption	Cooling	kW	25.22	26.94	28.94
	Heating		25.47	27.09	28.29
EER			3.77	3.73	3.70
COP			4.18	4.15	4.24
Net weight	kg	864		908	952
Starting current	A			15	
Max current	A	60.3		72.2	84.1
Refrigerant	Type / GWP		R410A / 2088		
	Charge	kg	11.0+11.0+11.0		11.0+11.0+11.5
Refrigerant piping size	Liquid	mm (in)	ø15.88(5/8")		ø19.05(3/4")
	Gas		ø31.75(1-1/4") [ø34.92(1-3/8")]		ø38.1(1-1/2") [ø34.92(1-3/8")]
	Oil equalization		ø9.52 (3/8")		
Total piping length	m	1000			
Outdoor operating temperature range	Cooling	°CDB	-15 to 52		
	Heating	°CWB	-20 to 15.5		
Capacity connection	%	80–160	80–130		
Number of connectable indoor units		80			

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

KXZ2 series

Heat Recovery Systems

for simultaneous heating and cooling



KXZ2

Up to 24HP [67.0kW]
with 1 single outdoor unit


Flexibility and Performance

The heat recovery systems operate with 3 inter-connecting pipes, commonly referred to as a '3-pipe system'.

The systems provide both heating and cooling operations simultaneously to individual indoor units according to room conditions or user requirements. The systems incorporate highly sophisticated controls transferring heat load energy from the entire building to provide an efficient, comfortable heating and cooling environment.


The range starts from a cooling capacity of 8 HP (22.4 kW) and expands up to 24 HP (67.0kW) using a single outdoor unit. Outdoor units can also be used as a modular system (twin or triple) providing up to 60 HP (168.0 kW) of cooling capacity.

Example of simultaneous heating and cooling



Heat recovery systems

The system interconnecting pipework has a unique arrangement, with two of the interconnecting pipes routed through a PFD Distribution Controller, and the third pipe connected directly to each indoor unit from the main pipe run. This reduces installation time, and the number of brazed connections on site. The PFD Distribution Controllers are available for single connection, or as a combined PFD 4-way connection, with each connected unit having independent cooling or heating operation.



During defrosting or during automatic protection of a compressor, which is activated every several hours in heating operation, heating operation temporarily stops and restarts after some period. The series has the same automatic protection of compressor in cooling operation also. During this protection period air flow only comes on and cooling operation restarts after some period.

These models are not suitable for year round cooling applications -such as server rooms- especially in areas where the outdoor air temperature goes below 5°C.



Heat recovery features

High efficiency in simultaneous heating and cooling mode

Highly efficient operation mode is automatically determined inside the refrigerant system during simultaneous cooling and heating operation. Heat recovery efficiency is maximized by this control and Max COP 9.0 (*) is achieved during operation with simultaneous cooling and heating.

* Conditions for simultaneous cooling and heating (Our estimation in 8HP operation and the following conditions: Temperature outside the room DB16°C/WB12°C, temperature in the cooled room DB27°C/19°C, and temperature in the heated room DB20°C/WB14.5°C)

Energy efficiency in heat recovery mode




Technology


High Efficiency

The graphs below highlight the improved efficiencies of the KXZR and Hi-COP models compared to the previous models.

Comparison of EER in cooling mode



Comparison of COP in heating mode



Continuous Heating Capacity Control (CHCC) -

Our CHCC defrosting control achieves more capacity than that of previous model in low ambient temperature condition. Target pressure is controlled automatically before capacity drops, which makes longer period of heating operation and shorter defrosting time.

Improved cooling capacity in low ambient temperature


Small split heat exchanger and pressure control make it possible for the outdoor unit to work in cooling operation even at low ambient temperature condition, which achieves more capacity in such low ambient condition as -5°C, compared to previous model.

In previous model, when high demand for heating and low cooling demand are required at the same time in low ambient temperature condition, pressure control is adjusted to keep more heating capacity than the cooling capacity.

Adopted heat exchanger and pressure control in KXZR series, has improved its capacity for both heating and cooling capacity at the same time. (*)

(*) Refrigerant system will prioritize required heating mode more than low cooling demand, in case most of the indoor units are operated in heating mode.

Blown air temperature in the cooled room



Design Flexibility

Indoor unit capacity connection

	HP	8	10	12	14	16	17	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54	56	58	60	
KXZR	Numbers	29	37	44	53	60	50	53	59	65	71	78																		
	IU Capacity connection	50-200%				50-160%										50-130%														
KXZRX	HP	16	18	20	22	24	26	28	30	32	34	36																		
	Numbers	60	53	59	65	71	78																							
	IU Capacity connection	50-200%				50-160%										50-130%														


Connectable indoor units

Up to 80 indoor units can be connected to the largest capacity outdoor unit, with a range of 15 types of exposed or concealed indoor unit, in several capacities, a choice of 82 indoor units is available.

- In case that capacity connection is more than 130%, additional charge of refrigerant is required on site.
- In case of 8-34HP of the systems, if one or more indoor units of FDK, FDFL, FDFU and/or FDFW series are connected to the system, the total connecting capacity of indoor units should not exceed 130%.

Wide Range of Operation

KXZR series permits an extensible system design with a heating range operation under a low temperature condition down to -20°C and a cooling range operation up to 46°C




Long Pipe Length

Total length	1000m
Furthest indoor unit	
Actual length	160m
Equivalent length	185m

The maximum height difference between indoor units is a maximum of 18m, and the maximum height difference between the outdoor unit and indoor unit is 50m.

For with few limitations, contributes to system design flexibility.

*1 The difference between the longest and the shortest indoor unit piping from the first branch must be within 40m.



Improvement of the PFD controller noise level

Sound insulation box design specification, reducing the level of noises from the PFD controller generated due to the flow of refrigerant or other causes.

Sound insulation design



8-12 HP (22.4kW – 33.5kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.89
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m

- for simultaneous **heating** and **cooling**



Uniform footprint of models allows continuous side-by-side installation



FDC224-335

■ SPECIFICATIONS

Item	Model	FDC224KXZRE2	FDC280KXZRE2	FDC335KXZRE2
Nominal horse power		8HP	10HP	12HP
Power source			3 Phase 380-415V, 50Hz	
Nominal capacity	Cooling	22.4	28.0	33.5
	Heating	22.4	28.0	33.5
Max heating capacity	kW	25.0	31.5	37.5
Power consumption ¹	Cooling	5.76	7.39	9.65
	Heating	5.27	6.86	8.44
EER ¹		3.89	3.79	3.47
COP ¹		4.25	4.08	3.97
SEER ¹		6.21	6.36	7.15
SCOP ¹		4.06	4.02	4.43
SEER ²		6.21	6.36	7.15
SCOP ²		4.05	4.01	4.42
Exterior dimensions (HxWxD)	mm		1697x1350x720	
Net weight	kg		305	
Sound power level ¹	Cooling	75	75	82
	Heating	77	76	82
Sound pressure level	Cooling	56	55	63
	Heating	58	57	63
Starting current	A		5	
Max current	A	16.0	20.0	21.2
Refrigerant	Type / GWP		R410A / 2088	
Refrigerant	Charge	kg	11.5	
	TCO ₂ Eq		24.012	
Refrigerant piping size	Liquid	mm	ø9.52(3/8")	ø12.7(1/2")
	Suction gas	(in)	ø19.05(3/4")	ø25.4(1") [ø22.22(7/8")]
	Discharge gas		ø15.88(5/8")	ø19.05(3/4")
Total piping length	m		1000	
Outdoor operating temperature range	Cooling	°CDB	-15 to 46	
	Heating	°CWB	-20 to 15.5	
Capacity connection	%		50-200	
Number of connectable indoor units		29	37	44

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 Lot 6/21 performances.

*2 Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

14-24 HP (40.0kW – 67.0kW)



VTCC

Technical focus

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.46
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m

- for simultaneous **heating** and **cooling**



Uniform footprint of all models allows continuous side-by-side installation



FDC400-670

■ SPECIFICATIONS

Item	Model	FDC400KXZRE2	FDC450KXZRE2	FDC475KXZRE2	FDC500KXZRE2	FDC560KXZRE2	FDC615KXZRE2	FDC670KXZRE2
Nominal horse power		14HP	16HP	17HP	18HP	20HP	22HP	24HP
Power source								
Nominal capacity	Cooling	kW	40.0	45.0	47.5	50.0	56.0	61.5
	Heating		40.0	45.0	47.5	50.0	56.0	61.5
Max heating capacity		kW	45.0	50.0	53.0	56.0	63.0	63.0
Power consumption ¹	Cooling	kW	11.56	14.47	14.84	15.20	19.31	21.35
	Heating		9.76	11.39	11.67	12.69	14.93	16.14
EER ¹			3.46	3.11	3.20	3.29	2.90	2.88
COP ¹			4.10	3.95	4.07	3.94	3.75	3.81
SEER ¹			6.78	6.29	6.60	7.01	6.26	6.05
SCOP ¹			4.39	4.33	4.27	4.39	4.29	4.34
SEER ²			6.78	6.29	6.60	7.01	6.26	6.05
SCOP ²			4.38	4.32	4.26	4.39	4.29	4.34
Exterior dimensions (HxDxW)	mm				2052x1350x720			
Net weight	kg		372			420		
Sound power level ¹	Cooling	dB(A)		81			84	
	Heating			82		82		83
Sound pressure level	Cooling	dB(A)		61		64		65
	Heating			62		63		64
Starting current	A		5			8		
Max current	A	30.0	32.0	40.4	41.0	41.6	42.0	42.4
Refrigerant	Type / GWP				R410A / 2088			
Charge	kg				11.5			
	TCO ₂ Eq				24.012			
Refrigerant piping size	Liquid				ø12.7(1/2")			
	Suction gas	mm (in)	ø25.4(1") [ø28.58(1-1/8"")]			ø28.58(1-1/8")		
	Discharge gas			ø22.22(7/8")			ø25.4(1") [ø22.22(7/8"")]	
Total piping length	m				1000			
Outdoor operating temperature range	Cooling	°CDB			-15 to 46			
	Heating	°CWB			-20 to 15.5			
Capacity connection	%	50-200			50-160			
Number of connectable indoor units		53	60	50	53	59	65	71

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. "tonne(s) of CO₂ equivalent" means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 Lot 6/21 performances.

*2 Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

26-40 HP (73.5kW – 112.0kW)



VTCC

Technical focus

- for simultaneous **heating** and **cooling**

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.47
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m



FDC735



FDC800-1120

■ SPECIFICATIONS

Item	Model	FDC735KXZRE2	FDC800KXZRE2	FDC850KXZRE2	FDC900KXZRE2	FDC950KXZRE2	FDC1000KXZRE2	FDC1060KXZRE2	FDC1120KXZRE2		
Combination (FDC)	335KXZRE2	400KXZRE2	400KXZRE2	450KXZRE2	450KXZRE2	475KXZRE2	500KXZRE2	500KXZRE2	560KXZRE2		
	400KXZRE2	400KXZRE2	450KXZRE2	450KXZRE2	475KXZRE2	500KXZRE2	500KXZRE2	560KXZRE2	560KXZRE2		
Nominal horse power		26HP	28HP	30HP	32HP	34HP	36HP	38HP	40HP		
Power source					3 Phase 380-415V, 50Hz						
Nominal capacity	Cooling	kW	73.5	80.0	85.0	90.0	95.0	100.0	106.0		
	Heating		73.5	80.0	85.0	90.0	95.0	100.0	106.0		
Power consumption	Cooling	kW	21.21	23.12	26.03	28.94	29.68	30.40	34.51		
	Heating		18.20	19.52	21.15	22.78	23.34	25.38	27.62		
EER		3.47	3.46	3.27	3.11	3.20	3.29	3.07	2.90		
COP		4.04	4.10	4.02	3.95	4.07	3.94	3.84	3.75		
Net weight	kg	677		744			840				
Starting current	A			10				16			
Max current	A	51.2	60.0	62.0	64.0	80.8	82.0	82.6	83.2		
Refrigerant	Type / GWP				R410A / 2088						
	Charge	kg			11.5+11.5						
Refrigerant piping size	Liquid				ø15.88(5/8")						
	Suction gas	mm (in)			ø31.75(1-1/4") [ø34.92(1-3/8")]			ø38.1(1-1/2") [ø34.92(1-3/8")]			
	Discharge gas		ø25.4(1") [ø28.58(1-1/8")]		ø28.58(1-1/8")			ø31.75(1-1/4") [ø28.58(1-1/8")]			
	Oil equalization				ø9.52 (3/8")						
Total piping length	m				1000						
Outdoor operating temperature range	Cooling	°CDB			-15 to 46						
	Heating	°CWB			-20 to 15.5						
Capacity connection	%		50-160					50-130			
Number of connectable indoor units		78			80						

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

42-50 HP (120.0kW – 142.5kW)



VTCC

Technical focus

- for simultaneous **heating** and **cooling**

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.46
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m



■ SPECIFICATIONS

Item	Model	FDC1200KXZRE2	FDC1250KXZRE2	FDC1300KXZRE2	FDC1350KXZRE2	FDC1425KXZRE2
Combination (FDC)		400KXZRE2	400KXZRE2	400KXZRE2	450KXZRE2	475KXZRE2
		400KXZRE2	400KXZRE2	450KXZRE2	450KXZRE2	475KXZRE2
		400KXZRE2	450KXZRE2	450KXZRE2	450KXZRE2	475KXZRE2
Nominal horse power		42HP	44HP	46HP	48HP	50HP
Power source		3 Phase 380-415V, 50Hz				
Nominal capacity	Cooling	kW	120.0	125.0	130.0	135.0
	Heating		120.0	125.0	130.0	135.0
Power consumption	Cooling	kW	34.68	37.59	40.50	43.41
	Heating		29.28	30.91	32.54	34.17
EER			3.46	3.33	3.21	3.11
COP			4.10	4.04	4.00	3.95
Net weight	kg			1116		1260
Starting current	A			15		24
Max current	A		90.0	92.0	94.0	96.0
Refrigerant	Type / GWP				R410A / 2088	
	Charge	kg			11.5+11.5+11.5	
Refrigerant piping size	Liquid	mm (in)			ø19.05(3/4")	
	Suction gas				ø38.1(1 1/2") [ø34.92(1 3/8")]	
	Discharge gas				ø31.75(1 1/4") [ø28.58(1 1/8")]	
	Oil equalization				ø9.52 (3/8")	
Total piping length	m				1000	
Outdoor operating temperature range	Cooling	°CDB			-15 to 46	
	Heating	°CWB			-20 to 15.5	
Capacity connection	%				50-130	
Number of connectable indoor units					80	

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

52-60 HP (145.0kW – 168.0kW)



VTCC

Technical focus

- for simultaneous **heating** and **cooling**

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.29
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m



■ SPECIFICATIONS

Item	Model	FDC1450KXZRE2	FDC1500KXZRE2	FDC1560KXZRE2	FDC1620KXZRE2	FDC1680KXZRE2
Combination (FDC)	475KXZRE2	500KXZRE2	500KXZRE2	500KXZRE2	560KXZRE2	560KXZRE2
	475KXZRE2	500KXZRE2	500KXZRE2	560KXZRE2	560KXZRE2	560KXZRE2
	500KXZRE2	500KXZRE2	560KXZRE2	560KXZRE2	560KXZRE2	560KXZRE2
Nominal horse power		52HP	54HP	56HP	58HP	60HP
Power source		3 Phase 380-415V, 50Hz				
Nominal capacity	Cooling	kW	145.0	150.0	156.0	162.0
	Heating		145.0	150.0	156.0	162.0
Power consumption	Cooling	kW	44.88	45.60	49.71	53.82
	Heating		36.03	38.07	40.31	42.55
EER		3.23	3.29	3.14	3.01	2.90
COP		4.02	3.94	3.87	3.81	3.75
Net weight	kg			1260		
Starting current	A			24		
Max current	A	121.8	123.0	123.6	124.2	124.8
Refrigerant	Type / GWP			R410A / 2088		
	Charge	kg		11.5+11.5+11.5		
Refrigerant piping size	Liquid	mm (in)		ø19.05(3/4")		
	Suction gas			ø38.1(1-1/2") [ø34.92(1-3/8")]		
	Discharge gas			ø31.75(1-1/4") [ø28.58(1-1/8")]		
	Oil equalization			ø9.52 (3/8")		
Total piping length	m			1000		
Outdoor operating temperature range	Cooling	°CDB		-15 to 46		
	Heating	°CWB		-20 to 15.5		
Capacity connection	%			50-130		
Number of connectable indoor units				80		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

16-24 HP (45.0kW – 67.0kW)



VTCC

Technical focus

- for simultaneous **heating** and **cooling**

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.91
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m



FDC450-670

■ SPECIFICATIONS

Item	Model	FDC450KXZRXE2	FDC500KXZRXE2	FDC560KXZRXE2	FDC615KXZRXE2	FDC670KXZRXE2
Combination (FDC)	224KXZRE2	224KXZRE2	280KXZRE2	280KXZRE2	335KXZRE2	335KXZRE2
	224KXZRE2	280KXZRE2	280KXZRE2	335KXZRE2	335KXZRE2	335KXZRE2
Nominal horse power	16HP	18HP	20HP	22HP	24HP	
Power source			3 Phase 380-415V, 50Hz			
Nominal capacity	Cooling	kW	45.0	50.0	56.0	61.5
	Heating		45.0	50.0	56.0	61.5
Power consumption	Cooling	kW	11.52	13.15	14.78	17.04
	Heating		10.54	12.13	13.72	15.30
EER		3.91	3.80	3.79	3.61	3.47
COP		4.27	4.12	4.08	4.02	3.97
Net weight	kg			610		
Starting current	A			10		
Max current	A	32.0	36.0	40.0	41.2	42.4
Refrigerant	Type / GWP			R410A / 2088		
	Charge	kg		11.5+11.5		
	Liquid			ø12.7(1/2")		
Refrigerant piping size	Suction gas	mm (in)		ø28.58(1-1/8")		
	Discharge gas		ø22.22(7/8")		ø25.4(1") [ø22.22(7/8")]	
	Oil equalization			ø9.52 (3/8")		
Total piping length	m			1000		
Outdoor operating temperature range	Cooling	°CDB		-15 to 46		
	Heating	°CWB		-20 to 15.5		
Capacity connection	%	80-200		80-160		
Number of connectable indoor units		60	53	59	65	71

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

3. Refrigerant piping size applicable to European installations are shown in parentheses.

26-36 HP (73.5kW – 100.0kW)



VTCC

Technical focus

- for simultaneous **heating** and **cooling**

- The KXZ2 series has a layered design and a refined new form
- High efficiency with EER up to 3.89
- VTCC : advanced variable temperature and capacity control
- Continuous heating capacity control
- Total piping length up to 1000m and a maximum pipe run of 160m



FDC735-1000

■ SPECIFICATIONS

Item	Model	FDC735KXZRXE2	FDC800KXZRXE2	FDC850KXZRXE2	FDC900KXZRXE2	FDC950KXZRXE2	FDC1000KXZRXE2
Combination (FDC)	224KXZRE2	224KXZRE2	280KXZRE2	280KXZRE2	280KXZRE2	335KXZRE2	335KXZRE2
	224KXZRE2	280KXZRE2	280KXZRE2	280KXZRE2	335KXZRE2	335KXZRE2	335KXZRE2
	280KXZRE2	280KXZRE2	280KXZRE2	335KXZRE2	335KXZRE2	335KXZRE2	335KXZRE2
Nominal horse power	26HP	28HP	30HP	32HP	34HP	36HP	
Power source			3 Phase 380-415V, 50Hz				
Nominal capacity	Cooling	kW	73.5	80.0	85.0	90.0	95.0
	Heating		73.5	80.0	85.0	90.0	95.0
Power consumption	Cooling	kW	18.91	20.54	22.17	24.43	26.69
	Heating		17.40	18.99	20.58	22.16	23.74
EER	3.89	3.89	3.83	3.68	3.56	3.45	
COP	4.22	4.21	4.13	4.06	4.00	3.95	
Net weight	kg			915			
Starting current	A			15			
Max current	A	52.0	56.0	60.0	61.2	62.4	63.6
Refrigerant	Type / GWP			R410A / 2088			
	Charge	kg		11.5+11.5+11.5			
Refrigerant piping size	Liquid	mm (in)		ø15.88(5/8")			
	Suction gas			ø31.75(1-1/4") [ø34.92(1-3/8")]			
	Discharge gas		ø25.4(1") [ø28.58(1-1/8")]	ø28.58(1-1/8")			
	Oil equalization			ø9.52 (3/8")			
	Total piping length	m		1000			
Outdoor operating temperature range	Cooling	°CDB		-15 to 46			
	Heating	°CWB		-20 to 15.5			
Capacity connection	%		80-160				80-130
Number of connectable indoor units		78		80			

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 2. Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
 3. Refrigerant piping size applicable to European installations are shown in parentheses.

PFD refrigerant flow branch control

Branch control	Total downstream indoor unit capacity
PFD1124-E	less than 11.2kW
PFD1804-E	less than 18.0kW
PFD2804-E	28.0kW or less
PFD1124X4-E	less than 37.1kW (less than 11.2kW x 4 branches)



Relay kit
(Relay kit comes attached to the branch control)



4-Way PFD box

Design flexibility

A total of 37.1 kW group of indoor units can be connected to a PFD box single branch. All connected units will operate in the same mode only (cooling or heating).

The recent 4-way PFD control PFD1124X4-E can connect to up to four indoor units with individual control – allowing for simultaneous cooling or heating.

- The remote control setting (as individual indoor unit on-off, temperature setting other than cooling/heating mode control) is possible with one remote control connected to each indoor unit, while at the same time, Center Control (SC-SL1N/SL2NA/SL4-AE3) can be used together with the individual remote control.
- It is necessary to set the central control to use this function. Please refer to the Installation Manual for details.
- In case of mode changeover from cooling to heating and from heating to cooling, by the use of only the indoor units and PFD box combination, the mode changeover noise is reduced. All this made possible without turning off the compressor and at the same time without the reduction of capacity.


The risk of refrigerant leakage is reduced by changing piping connection at the PFD box to brazing method.

- The use of optional PFD box extension cable that has a connector at ends, makes it possible to further separate the indoor unit and PFD box. This will enable the PFD box to be located away from the indoor unit and help reduce the influence of sound caused by PFD box and refrigerant flow.




Branch control	Total downstream capacity	Connectable indoor units
PFD1124-E	less than 112	1-5
PFD1804-E	112 or more but less than 180	1-8
PFD2804-E	180 or more but less than 280	1-10
PFD1124X4-E	less than 371 (less than 112 per branch)	Up to 16

*Refer to Data Book for details



Easy installation

PFD control box design allows to directly connect the liquid pipe from indoor unit to outdoor unit by bypassing the PFD box. As a result, the piping connections per indoor unit are reduced by a third, thus reducing installation time and cost.





extension cable 15m



PFD4-15WR-E (Option)

The PFD is connected to the indoor unit by 3 core signal wire via a relay kit (supplied) to be located within 2m of each other. The indoor unit however can be up to 40m away. Power to the PFD can be connected from the indoor unit or other supply.



Micro KXZ series

Micro KXZ

Space saving

for small offices, shops applications



Micro 4–6HP



1 Heat Exchanger

2 Inverter Control Vector Inverter Control system

3 DC Fan Motor Compact & High efficiency

4 Twin Rotary Compressor

5 System Control

1 Compact high efficient Heat Exchanger



- Optimizing relationship of the air flow velocity & fin pattern
- Improvement of air distribution
- Maximizing efficiency of heat exchanger



5 Optimum Refrigerant System Control


- Optimum heat exchanger refrigerant distribution
- Advanced refrigerant liquid return protection control system
- High speed system control by Superlink system

Micro 8–12HP



Previous

Micro KXZ



1 DC Fan motor Compact & High efficiency

2 Inverter Control Compact & Vector Inverter Control system

3 Downsized accumulator

4 Receiver in fan section

5 Scroll Compressor


Design Flexibility

Connectable indoor units & Indoor unit capacity connection


Micro KXZ	HP	4	5	6	8	10	12
	Numbers	8	10*	22	24		
IU Capacity connection	80 – 150%				50 – 150%		

*When connecting 9 units or more, set the total capacity as follows :
5HP : 110% or less, 6HP : 100% or less. In the case of R410A.

KXZ Lite	HP	8	10
	Numbers	8	
IU Capacity connection	50 – 120%		




Wide range operation




*With limitation to height difference between indoor and outdoor units and installation space.

Long Pipe length

Micro 4–6HP




Micro 8–12HP




Easy Transportation & Installation

Due to realization of significant reduction in size and footprint which is one of the smallest in the industry, transportation in an elevator made for six persons (Width:1400mm, Depth:850, Open area:800mm) is possible, eliminating cost of a crane and reducing labor.



Transportation in an elevator made for six persons



4-6 HP (12.1kW – 15.5kW)



Technical focus

- Compact & flexible design
- High efficiency with EER up to 4.08
- Easy maintenance & Quick installation
- Available in 1-phase (KXZEN1-W) and 3-Phase (KXZES1-W)
- Total piping length up to 100m and a maximum pipe run of 70m



FDC121-155

■ SPECIFICATIONS

Item	Model	FDC121KXZEN1-W	FDC140KXZEN1-W	FDC155KXZEN1-W	FDC121KXZES1-W	FDC140KXZES1-W	FDC155KXZES1-W
Nominal horse power		4HP	5HP	6HP	4HP	5HP	6HP
Power source		1 Phase 220-240V, 50Hz			3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	12.1	14.0	15.5	12.1	14.0	15.5
	Heating	12.1	14.0	15.5	12.1	14.0	15.5
Max heating capacity	kW	12.5	16.0	16.3	12.5	16.0	16.3
Power consumption ¹	Cooling	2.97	4.00	5.20	2.97	4.00	5.20
	Heating	2.88	3.52	4.06	2.88	3.52	4.06
EER ¹		4.08	3.50	2.98	4.08	3.50	2.98
COP ¹		4.20	3.98	3.82	4.20	3.98	3.82
SEER ¹		9.67	8.82	8.17	9.67	8.82	8.17
SCOP ¹		4.67	4.62	4.58	4.67	4.62	4.58
SEER ²		8.39	7.98	7.57	8.39	7.98	7.57
SCOP ²		4.40	4.43	4.41	4.40	4.43	4.41
Exterior dimensions (HxWxD)	mm			845x970x370			
Net weight	kg		85			87	
Sound power level ¹	Cooling	68	69	70	68	69	70
	Heating	71	73	73	71	73	73
Sound pressure level	Cooling	54	54	54	54	54	54
	Heating	56	58	58	56	58	58
Starting current	A			5			
Max current	A		23.0			13.5	
Refrigerant	Type / GWP			R32 / 675			
	Charge	kg		4.2			
	TCO ₂ Eq			2.835			
Refrigerant piping size	Liquid	mm		ø9.52(3/8")			
	Gas	(in)		ø15.88(5/8")			
Total piping length	m			100			
Outdoor operating temperature range	Cooling	°CDB		-15 to 43			
	Heating	°CWB		-20 to 15.5			
Capacity connection	%			80-150			
Number of connectable indoor units		8	10	10	8	10	10

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 Lot 6/21 performances.

*2 Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

4–6 HP (12.1kW – 15.5kW)



Technical focus

- Compact & flexible design
- High efficiency with EER up to 3.82
- Easy maintenance & Quick installation
- Available in 1-phase (KXZEN1) and 3-Phase (KXZES1)
- Total piping length up to 100m and a maximum pipe run of 70m



FDC121-155

■ SPECIFICATIONS

Item	Model	FDC121KXZEN1	FDC140KXZEN1	FDC155KXZEN1	FDC121KXZES1	FDC140KXZES1	FDC155KXZES1
Nominal horse power		4HP	5HP	6HP	4HP	5HP	6HP
Power source		1 Phase 220-240V, 50Hz			3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	12.1	14.0	15.5	12.1	14.0	15.5
	Heating	12.1	14.0	15.5	12.1	14.0	15.5
Max heating capacity	kW	12.5	16.0	16.3	12.5	16.0	16.3
Power consumption ¹	Cooling	3.16	3.96	5.20	3.16	3.96	5.20
	Heating	3.09	3.66	4.28	3.09	3.66	4.28
EER ¹		3.82	3.54	2.98	3.82	3.54	2.98
COP ¹		3.91	3.83	3.62	3.91	3.83	3.62
SEER ¹		8.15	7.73	7.21	8.15	7.73	7.21
SCOP ¹		4.63	4.59	4.55	4.63	4.59	4.55
SEER ²		7.37	7.06	6.68	7.37	7.06	6.68
SCOP ²		4.52	4.52	4.41	4.52	4.52	4.41
Exterior dimensions (HxWxD)	mm			845x970x370			
Net weight	kg		85			87	
Sound power level ¹	Cooling	70	71	71	70	71	71
	Heating	72	72	74	72	72	74
Sound pressure level	Cooling	53	53	54	53	53	54
	Heating	56	57	57	56	57	57
Starting current	A			5			
Max current	A		28.0			13.5	
Refrigerant	Type / GWP			R410A / 2088			
Refrigerant	Charge	kg		5.0			
	TCO ₂ Eq			10.44			
Refrigerant piping size	Liquid	mm		ø9.52(3/8")			
	Gas	(in)		ø15.88(5/8")			
Total piping length	m			100			
Outdoor operating temperature range	Cooling	°CDB		-15 to 43			
	Heating	°CWB		-20 to 15.5			
Capacity connection	%			80–150			
Number of connectable indoor units		8	10 ³	10 ³	8	10 ³	10 ³

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

¹ Lot 6/21 performances.

² Seasonal efficiency of Eurovent certification condition SEER/SCOP certified value according to the max air flow limit of 275m³/h/kW stated in the Eurovent certification rules.

³ When connecting 9 units or more, set the total capacity as follows : 5HP : 110% or less, 6HP : 100% or less. In the case of R410A.

8-12 HP (22.4kW – 33.5kW)



Technical focus

- Compact & flexible design
- High efficiency with EER up to 4.00
- Easy transportation & Quick installation
- Connect up to 24 indoor units / up to 150% capacity
- Total piping length up to 510m and a maximum pipe run of 160m



FDC224-335

■ SPECIFICATIONS

Item	Model	FDC224KXZME1	FDC280KXZME1	FDC335KXZME1A
Nominal horse power		8HP	10HP	12HP
Power source			3 Phase 380-415V, 50Hz	
Nominal capacity	Cooling	kW	22.4	28.0
	Heating		22.4	28.0
Max heating capacity		kW	25.0	31.5
Power consumption	Cooling	kW	5.59	7.90
	Heating		4.97	6.53
EER			4.00	3.54
COP			4.50	4.28
SEER			6.55	6.03
SCOP			4.55	4.54
Exterior dimensions (HxWxD)	mm		1675x1080x480	
Net weight	kg		221	224
Sound power level	Cooling	dB(A)	73	75
	Heating		75	76
Sound pressure level	Cooling	dB(A)	58	60
	Heating		59	60
Starting current	A		5	
Max current	A		20.0	23.0
Refrigerant	Type / GWP		R410A / 2088	
Refrigerant	Charge	kg	11.5	
	TCO ₂ Eq		24.012	
Refrigerant piping size	Liquid	mm	ø9.52(3/8")	ø12.7(1/2")
	Gas	(in)	ø19.05(3/4")	ø25.4(1") [ø22.22(7/8")]
Total piping length	m		510	
Outdoor operating temperature range	Cooling ^{**}	°CDB	-15 to 46	
	Heating	°CWB	-20 to 15.5	
Capacity connection	%		50-150	
Number of connectable indoor units		22	24	24

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".

3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.

5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.

6. Refrigerant piping size applicable to European installations are shown in parentheses.

*1 With limitation to height difference between indoor and outdoor units and installation space.


8, 10 HP (22.4kW · 28.0kW)



Technical focus

- Compact & flexible design
- High efficiency with EER up to 4.00
- KXZ Lite extends a cooling range operation up to 50°C.
- Connect up to 8 indoor units / up to 120% capacity
- Total piping length up to 150m and a maximum pipe run of 120m
- External static pressure is available up to 35 Pa
- Improved installation items

Improved freedom of piping layout



Hole size became 120% bigger.

A transparent rain cover

Attached as a standard for easy maintenance.



Wire insertion holes for fall prevention



Fixing screws to service panel

Decreased number of screws from 5 to 2, installation & service speed is improved.

FDC224 · 280

■ SPECIFICATIONS

Item	Model	FDC224KXZPE1		FDC280KXZPE1
Nominal horse power		8HP		10HP
Power source		3 Phase 380-415V, 50Hz		
Nominal capacity	Cooling	kW	22.4	28.0
	Heating		22.4	28.0
Power consumption	Cooling	kW	5.6	7.87
	Heating		4.8	6.47
EER		4.00		3.56
COP		4.67		4.33
SEER		6.65		6.68
SCOP		4.34		4.50
Exterior dimensions (HxWxD)		mm 1505x970x370		
Net weight		kg 165		
Sound power level	Cooling	dB(A)	72	74
	Heating		73	76
Sound pressure level	Cooling	dB(A)	59	60
	Heating		60	63
Starting current		A 5		
Max current		A 21.0		22.0
		Type / GWP R410A / 2088		
Refrigerant	Charge	kg	8.9	
	TCO ₂ Eq		18.583	
Refrigerant piping size	Liquid	mm (in)	ø9.52(3/8")	
	Gas		ø22.22(7/8")	
Total piping length		m 150		
Outdoor operating temperature range	Cooling	°CDB	-15 to 50	
	Heating	°CWB	-20 to 15.5	
Capacity connection		% 50-120		
Number of connectable indoor units		8		

1. The data are measured under the following conditions (ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
2. SEER/SCOP are based on EN14825:2016 and Commission regulation (EU) No.2016/2281. Temperature conditions for calculating SCOP are based on "Average climate".
3. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
4. 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.
5. Refrigerant contained in the products is a fluorinated greenhouse gas listed in Regulation (EU) No 517/2014.
6. Refrigerant piping size applicable to European installations are shown in parentheses.

KXZ series



Water cooled series

8–36 HP (22.4kW – 100.0kW)



Technical focus

1. High efficiency (EER/COP)

- Energy saving → Reduction of operation cost

2. Compact design

- Easy transportation and installation
- Carriable by elevator

3. BMS (Building Management System)

- Can use the same BMS as air cooled KX
- Available to large-scale and fine control

4. Serviceability & Maintenance

- Service and maintenance of main parts can be done from the front side only
- Useful service tools (Mente-PC, SL-Checker etc.)



FDC224-335



FDC450-670



FDC730-1000

■ SPECIFICATIONS

Item	Model	FDC224KXZWE1	FDC280KXZWE1	FDC335KXZWE1	FDC450KXZWE1	FDC500KXZWE1	FDC560KXZWE1
Combination (FDC)		–	–	–	224KXZWE1	224KXZWE1	280KXZWE1
		–	–	–	224KXZWE1	280KXZWE1	280KXZWE1
		–	–	–	–	–	–
Nominal horse power		8HP	10HP	12HP	16HP	18HP	20HP
Power source				3 Phase 380–415V, 50Hz			
Nominal capacity	Cooling	kW	22.4	28.0	33.5	45.0	50.0
	Heating		25.0	31.5	37.5	50.0	56.0
Power consumption	Cooling	kW	4.23	5.75	8.13	8.49	9.83
	Heating		4.24	5.10	6.30	8.47	9.27
EER			5.30	4.87	4.12	5.30	5.09
COP			5.90	6.18	5.95	5.90	6.04
Exterior dimensions (HxWxD)	mm		1100x780x550			–	
Net weight	kg		185			185x2	
Sound pressure level	Cooling	dB(A)	48	50	52	51	52
	Heating						53
Refrigerant	Type / GWP				410A / 2088		
	Charge	kg				9.9+9.9	
	TCO ₂ Eq			20.671		–	
Refrigerant piping size	Liquid	mm (in)	ø9.52(3/8")		ø12.7(1/2")		
	Gas		ø19.05(3/4")	ø22.22(7/8")	ø25.4(1") [ø22.22(7/8")]	ø28.58(1-1/8")	
	Oil equalization		–	–	–	ø9.52(3/8")	
Water piping size	Water inlet				R1 1/4		
	Water outlet				R1 1/4		
	Drain outlet				Rp 1/2(internal thread)		
Total piping length	m				510		
Capacity connection	%				50–150		
Number of connectable indoor units		22	28	33	44	50	56

1.The data are measured at the following condition:

Cooling: Indoor temp. of 27 °CDB, 19 °CWB, and heat source unit inlet water temp. of 30 °C, water flow rate 96 L/min


Heating: Indoor temp. of 20 °CDB, 15 °CWB, and heat source unit inlet water temp. of 20 °C, water flow rate 96 L/min

2.Refrigerant piping size applicable to European installations are shown in parentheses.

1. High-rise Building

- 100m or higher in height


Heat source units on every floor
- New building projects -



2. Glass-exterior facade Building

- Possible to hide KXZW units and to keep fine sight

Heat source units in the machine room
- Renovation projects -



FDC615KXZWE1	FDC670KXZWE1	FDC730KXZWE1	FDC775KXZWE1	FDC850KXZWE1	FDC900KXZWE1	FDC950KXZWE1	FDC1000KXZWE1
280KXZWE1	335KXZWE1	224KXZWE1	224KXZWE1	280KXZWE1	280KXZWE1	280KXZWE1	335KXZWE1
335KXZWE1	335KXZWE1	224KXZWE1	280KXZWE1	280KXZWE1	280KXZWE1	335KXZWE1	335KXZWE1
-	-	280KXZWE1	280KXZWE1	280KXZWE1	335KXZWE1	335KXZWE1	335KXZWE1
22HP	24HP	26HP	28HP	30HP	32HP	34HP	36HP
3 Phase 380-415V, 50Hz							
61.5	67.0	73.0	77.5	85.0	90.0	95.0	100.0
69.0	75.0	82.5	90.0	95.0	100.0	106.0	112.0
13.7	16.3	14.2	15.5	17.5	19.5	21.7	24.3
11.4	12.6	13.8	14.8	15.4	16.4	17.6	18.8
4.49	4.11	5.14	5.00	4.86	4.62	4.38	4.12
6.05	5.95	5.98	6.08	6.17	6.10	6.02	5.96
-	-	-	-	-	-	-	-
370				555			
54	55	54	55		56		57
R410A / 2088							
9.9+9.9				9.9x3			
-				-			-
ø12.7(1/2")				ø15.88(5/8")			
ø28.58(1-1/8")			ø31.75(1-1/4") [ø34.92(1-3/8")]			ø38.1(1-1/2")	[ø34.92(1-3/8")]
			ø9.52(3/8")				
			R1 1/4				
			R1 1/4				
			Rp 1/2(internal thread)				
			510				
			50-150				
61	67	72	78		80		

Refrigerant piping

Installation of Interconnecting Pipework

KXZ equipment is manufactured to meet the highest standards of quality and reliability. It is imperative that the method of installation and the materials used are also to the high standards, to ensure trouble free operation and long term reliability.

The interconnecting pipework must be installed by a competent and trained engineer. Refrigeration quality copper tube must be used, soft copper coils or half-hard straight lengths. The refrigeration quality tube must be soft drawn seamless high grade copper pipe. The copper tube must be selected taking into account the higher operating pressures of R32 • R410A refrigerant, and that high pressures will occur throughout the system because of the reverse cycle operation. All pipework material used should comply with EN12735 European standard.

The supplied branch pipe kits, must be used to make connections to indoor units, and the supplied manifold kits must be used to make connections between outdoor units (where applicable); it is not permitted to use standard fittings such as elbows, tees etc. The branch pipes shall be installed in accordance with the manufacturer's instructions, allowing unrestricted flow of refrigerant, and in accordance with European standard EN378.

All brazed joints shall be made with dry nitrogen purge to ensure the prevention of oxidisation of the internal surface of the copper pipes.

The ingress of moisture, dirt and any other contaminants to the interior of the copper pipes, and air-conditioning units, must be prevented during the installation procedure.

After the installation of pipework, prior to the connection of the outdoor units, and sealing of insulation joints, the pipework must be pressure tested for leakage, using dry nitrogen.

Additional Refrigerant

Only R32 • R410A refrigerant shall be used, it must be charged by weight only, using electronic scales. The amount of additional refrigerant must be accurately calculated from the manufacturer's data, based on the length and diameter of each section of the liquid refrigerant pipework of the system.

The products contains fluorinated greenhouse gases covered by Kyoto protocol.

Refrigerant piping size selection

Outdoor unit		Micro KXZ		
		121	140	155
Gas pipe	Furthest indoor unit =<70m	ø15.88		
Liquid pipe		ø9.52		

Outdoor unit		Micro KXZ			KXZ Lite	
		224	280	335	224	280
Gas pipe	Furthest indoor unit =<90m	ø19.05	ø22.22	ø25.4(ø22.22)	ø19.05	ø22.22
Liquid pipe		ø9.52	ø12.7		ø9.52	
Gas pipe	90m =<Furthest indoor unit	ø22.22	ø25.4(ø22.22)		ø22.22	ø25.4/ ø28.58
Liquid pipe			ø12.7			ø9.52

Standard (Outdoor unit side branching pipe – Indoor unit side first branching pipe)

If the longest distance (measured between the outdoor unit and the farthest indoor unit) is 90m or longer (actual length), please change the main pipe size according to the table below.


Outdoor unit	Main pipe size (normal)		Pipe size for an actual length of 90m or longer	
	Gas pipe	Liquid pipe	Gas pipe	Liquid pipe
224	ø19.05 x t1.0		ø22.22 x t1.0	
280	ø22.22 x t1.0		ø25.4 (ø22.22) x t1.0	
335	ø25.4 (ø22.22) x t1.0			
400	ø25.4 (ø28.58) x t1.0		ø28.58 x t1.0	
450				
475				
500				
560				
615				
670				
735				
800				
850	ø31.8 x t1.1 (ø34.92 x t1.2)		ø15.88 x t1.0	
900				
950				
1000				
1060				
1120				
1200				
1250				
1300				
1350	ø38.1 x t1.35 (ø34.92 x t1.2)		ø38.1 x t1.35 (ø34.92 x t1.2)	
1425				
1450				
1500				
1560				
1620				
1680				

mm	inch
ø9.52	3/8"
ø12.7	1/2"
ø15.88	5/8"
ø19.05	3/4"
ø22.22	7/8"
ø25.4	1"

mm	inch
ø28.58	1-1/8"
ø31.8	1-1/4"
ø34.92	1-3/8"
ø38.1	1-1/2"
ø44.5	1-3/4"
ø50.8	2"

Please use C1220T-1/2H for ø19.05 or larger pipes.
Pipe sizes applicable to European installations are shown in parentheses.

Single outdoor unit piping examples:



Branch pipes



DIS-22-1G/DIS-180-1G




DIS-371-1G/DIS-540-3

Header pipe






HEAD4-22-1G
HEAD6-180-1G
HEAD8-371-2



DOS-2A-3
DOS-3A-3

Combination outdoor unit piping examples:



Outdoor unit side branching pipe set

Outdoor unit	KXZ3	KXZ2
For two units	DOS-2A-4	DOS-2A-3, DOS-2A-4
For three units	DOS-3A-4	DOS-3A-3, DOS-3A-4

Indoor unit side branching pipe set

Total capacity downstream	For KXZ3 OU	For KXZ2 OU
Less than 180		DIS-22-1G
180 or more but less than 371		DIS-180-1G
371 or more but less than 540		DIS-371-1G
540 or more	DIS-540-4	DIS-540-3, DIS-540-4

Indoor unit side Header set

Total capacity downstream	For KXZ3 OU	For KXZ2 OU	Number of branches
Less than 180	HEAD4-22-1G		4 branches at the most
180 or more but less than 371	HEAD6-180-1G		6 branches at the most
371 or more but less than 540	HEAD8-371-2		8 branches at the most
540 or more	HEAD8-540-4	HEAD8-540-3, HEAD8-540-4	8 branches at the most

Heat recovery systems (Outdoor unit side branching pipe – Indoor unit side first branching pipe)

If the longest distance (measured between the outdoor unit and the farthest indoor unit) is 90m or longer (actual length), please change the main pipe size according to the table below.

※ Even if the longest distance exceeds 90m (actual length), you do not need to change the size of discharge gas pipes.

Outdoor unit	Main pipe size (normal)			Pipe size for an actual length of 90m or longer			mm	inch
	Suction gas pipe	Discharge gas pipe	Liquid pipe	Suction gas pipe	Discharge gas pipe	Liquid pipe		
224	ø19.05 x t1.0	ø15.88 x t1.0						
280	ø22.22 x t1.0		ø19.05 x t1.0					
335	ø25.4 (ø22.22) x t1.0							
400	ø25.4 (ø28.58) x t1.0							
450								
475								
500								
560								
615								
670								
735								
800								
850								
900								
950								
1000								
1060								
1120								
1200								
1350								
1425								
1450								
1500								
1560								
1620								
1680								

Please use C1220T-1/2H for ø19.05 or larger pipes.

Pipe sizes applicable to European installations are shown in parentheses.

Branch pipes






DIS-22-1-RG/DIS-180-1-RG


Combination outdoor unit manifold



DOS-2A-3-R
DOS-3A-3-R



Combination outdoor unit piping examples:



Outdoor unit's branch piping set


Outdoor unit	Branch piping set
2 units	DOS-2A-3-R
3 units	DOS-3A-3-R

Indoor unit's first branch piping set

Total capacity of indoor units	Branch piping set
Less than 180	DIS-22-1-RG
180 or more but less than 371	DIS-180-1-RG
371 or more but less than 540	DIS-371-2-RG
540 or more	DIS-540-2-RG

In the Down Stream of branching control

Total capacity of indoor units	Branch piping set
Less than 180	DIS-22-1G
180 or more but less than 371	DIS-180-1G
371 or more but less than 540	DIS-371-1G
540 or more	DIS-540-3



KXZ series product Line up

Indoor units



18 types of exposed or concealed indoor units available in a wide range of capacities. The best solution of indoor units for all applications is available from our full lineup.

		1.5kW	2.2kW	2.8kW	3.6kW	4.5kW	
		0.5HP	0.8HP	1HP	1.25HP	1.6HP	
Ceiling Cassette	4way FDT			●	●	●	●
	4way Compact FDTC	●	●	●	●	●	●
	2way FDTW			●	●		●
	1way FDTS					●	●
	1way Compact FDTQ		●	●	●	●	
Duct Connected	High Static Pressure FDU					●	●
	Low/Middle Static Pressure FDUM		●	●	●	●	●
	Low Static Pressure(thin) FDUT	●	●	●	●	●	●
	Compact & Flexible FDUH		●	●	●	●	
Wall Mounted FDK		●	●	●	●	●	●
Ceiling Suspended FDE					●	●	●
Floor Standing	2way FDFW			●	●	●	●
	With Casing FDFL						
	Without Casing FDFU			●	●	●	●
OA Processing unit FDU-F *							
Hydro module unit HMU							
Air flow m ³ /h		150	250	350	500		
Fresh Air Ventillation & Heat Exchange unit SAF		●	●	●	●		
Fresh Air Assembly SAF-DX			●	●	●		

* Can not be connected to the Micro model(4-6HP), KXZ Lite.

Combination for KXZ outdoor units

Refrigerant	R32 : KXZ3 Micro KXZ	R410A : KXZ2 Micro KXZ
-------------	----------------------	------------------------



For the R32 Micro KXZ series the safety system of MHI has not been prepared.


	5.6kW	7.1kW	9.0kW	11.2kW	14.0kW	16.0kW	22.4kW	28.0kW
	2HP	2.5HP	3.2HP	4HP	5HP	6HP	8HP	10HP
	● ●	● ●	● ●	● ●	● ●	● ●		
	● ●							
	● ●	● ●	● ●	● ●	● ●			
		● ●						
	● ●	● ●	● ●	● ●	● ●	● ●	● ● *	● ● *
	● ●	● ●	● ●	● ●	● ●	● ●		
	● ●	● ●						
	● ●	● ●	● ●					
	● ●	● ●		● ●	● ●			
	● ●							
		● ●						
				●				
					●			
						●	●	
					●			●
	800	1000						
	●	●						
	●	●						

New Generation FDT




New **Automatic anti-draft control**

A corner-mounted motion sensors detects human presence and activity in a room, enhancing comfort.




1. Air flow based on human position



New

Thermal sensing soothing comfort

A Sensor to optimize the air flow



Direct flow control

The louvers are controlled to blow towards human position.



Draft less control

Draft prevention panel is activated based on human position.



New *Improved performance*

Power consumption decreased by:

1. Adopting new designed impeller and flow path


improves the aerodynamic performance of the unit.



2. $\Phi 5.0$ heat exchanger tube is adopted to improve the performance

Slimmer heat exchanger and a dense copper piping.

20% decrease



Draft Prevention Panel (Option)

Keep maximum comfort with minimal draft : FDT & FDTC control flaps with more flexibility.



Each of the 4 flaps can be controlled individually at each operation mode. They change air flow direction and prevent drafts occurring. This function also provides flexible control for air flow direction.

User can position Draft Prevention Panel panels by using only the remote controller (RC-EX3D, Wireless kit).

- It can also prevent user from being directly blown by hot drafts in heating mode.



Draft Prevention Panel provides a comfortable air flow without any draft feeling. Whether cooling or heating a room, the remote control can be used to instantly suppress any warm or cool drafts. This accurately assists how air flow is directed out of the indoor unit.

Motion sensor (Option)



Three Steps Control

1 Power Control

Motion sensor (option) detects human activity. Energy saving control is achieved by shifting set temperature according to detected amount of activity.

2 Stand by

Unit will go on stand-by mode when no activity is detected. When the motion sensor detects activity again, the unit will automatically re-start operation.



3 Auto Off

Unit will go off automatically when no activity is detected for 12 hours.

Operation mode and Control of Motion sensor

eco operation comfort operation

		Operation mode				
		Auto	Cool	Heat	Dry	Fan
Power Control *1	Low	+3°C +3°C	+3°C	+3°C	—	—
	High	-3°C -3°C	-3°C	-3°C	—	—
	None	-3°C -3°C	-3°C	-3°C	—	—
	Auto Off *2	●	●	●	●	●

*1 Set temperature is revised maximum $\pm 3^{\circ}\text{C}$ at Cooling/Heating mode by detecting heat volume movement.

*2 Absence for 1 hour \Rightarrow Operation stops ("Stand-by") 12 hours absence \Rightarrow Operation stops completely

Wireless Control System

Now available in our FDT series

Control your air-conditioner from anywhere, anytime.

If you turn on the air-conditioner when you're on the go, you'll be comfortable when you get to the office. Even if you forget to turn it off, you can turn it off when you are out and about.



WF-PAC-E



You can control the air-conditioner at home or on the go by installing App (Smart M-Air) on your smartphone or tablet.



Search for "Smart M-Air" from the Google Play™ store for Android™ and App Store for iPhone.



Application compatible model:

Please check the app stores for the latest supported OS version information.

App Store and iPhone are registered trademark of Apple Inc.
Google Play and the Google Play logo are trademarks of Google LLC.




Functions

- 1 Turn ON/OFF
- 2 Change operation mode (Auto, Cool, Heat, Fan, Dry)
- 3 Control temperature
- 4 Set Timers
- 5 Favourite setting

Notification Function

- 1 Shut-off reminder alert
- 2 Accidentally left running
It will be sent to your smart device if the air-conditioner is accidentally left running
- 3 Watching function

Weekly Timer




Timers can be set for different days of the week. They can also be set from the calendar.

System configuration

Smartphone / Tablet



Internet



WF-PAC-E

* For the units that does not include wireless LAN the function could be used by adopting an option (WF-PAC-E)

*SC-BIKN2-E cannot be used simultaneously for system configuration.

Indoor unit

Serviceability & workability


Easy and quick installation and maintenance

Indoor unit is easily positioned and installed

1 Adjustable easier positioning of unit by new slits

FDT

New shape of slit is suitable to install the unit with more flexibility, compatible with many kinds of suspending bolt pitch on site. Any rectangular or squared pitch of suspending bolts are available with this slit.



Compatible with both square or rectangular bolt pitch


2 New slit in panel allows easier installation on site

FDT FDTC

Flexible positioning is available, which helps adjusting the direction of panel accordingly to lines or pattern on the ceiling.



4 long slits are available.




Quick installation and maintenance

1 Easy access to component part for easy maintenance

FDT

1. The control box and bell mouth can be removed together.
2. Easy access to impeller and fan motor.





Control box
Bell mouth

2 New shape of path of wiring

FDT


New shape of path gives easy wiring work for installation.



3 No need to remove screws to open the controller cover

FDT



It is possible to loose and slide open the cover without removing the screws. This prevents the cover from falling and causing damage on site.



4 More safe installation by stopper of washer

FDT FDTC

When unit is installed with hook between washers, this stopper helps to install the unit safely, without adjusting washer.




Easy installation and maintenance

For smooth and easy working

1 Easy and flexible hook to remove the filter

FDT FDTC



Hook of soft material helps to remove the filter without dust spreading.



2 Securely fix the corner lid by strap

FDT


The direction of the strap hook part has been changed from longitudinal to lateral. Furthermore, a barb has been added to the hook pin to prevent the strap from coming off.



3 Drain-up-lift increases up to 850 mm

FDT FDTC


The drain can be lifted up to 850 mm from the ceiling surface.



4 New port to check drain water flow


FDT

A water supply port has been provided in the piping lid for easier testing of the drain water flow.
(The port is usually sealed with a rubber cap.)



5 Re-use of packages during construction work


FDT FDTC



6 More flexible outlet for ducting

FDT FDTC

Both $\Phi 125$ and $\Phi 200$ (oval shaped) are available.



Remote Control

Simple use with advanced settings REMOTE CONTROL

RC-EX3D

Intuitive touch controller with
Liquid Crystal Display

Function Switch

The function switch allows you to select and set two functions of your choice among the seven available functions shown. These functions can be used by simply pressing the button after they are set, allowing you to use your preferable functions immediately.

1. Draft prevention ON/OFF



Anti draft can be turned ON/OFF with a single tap of the button.

2. High Power Mode



High Power Mode achieves excessive cooling / heating capacity in 15 minutes to quickly adjust the room temperature to a comfortable level.

3. Energy Saving Mode



Temperature is set to be optimized to save energy without losing comfort.

5. Home Leave Mode



Home leave mode maintains the room temperature at a moderate level.

4. Quiet Mode



Outdoor unit starts to operate quietly by activating this mode. The time of this mode can be set in conjunction with Indoor Silent Timer.

6. Favourite Mode



Operation mode, set temperature, fan speed and air flow direction will automatically be adjusted to the programmed favourite setting.


7. Filter Sign



Announces the due time for cleaning the air filter.


Favourite Mode

Operation mode, set temperature, fan speed and air flow direction are memorized and allocated to two buttons that can be operated by one touch.



Adjustable Brightness of the Operation Lamp



The brightness of the operation lamp behind Run/Stop switch can be adjusted by 10 stages.



Draft Prevention Setting



(only for FDT•FDTC series)

User can enable/disable the motion of Draft prevention panel for each blow outlet for each operation mode. This function can be set while operating.



Easy Adjustment of the Air Flow

User can visually confirm and set the direction of flaps using the visual display on the remote controller.




Motion Sensor Control

Presence of humans and activity are detected by a motion sensor to perform various controls.

① Select Enable / Disable Motion sensor control



Enable/Disable




Select [Enable]/[Disable] for the motion sensor of the indoor unit connected to the R/C.

② Select Enable / Disable per control

- Power control
- Auto-off



Enable/Disable



Backup Control

Control restricted to two indoor units (two groups)




Fault backup control



Keep back up all the time!

If one of the two indoor units malfunctions and stops its operation, the other starts backup operation so that users' comfort will not be compromised.




Capacity backup control



Maintains users' comfort!

When the control system detects either of its two units operating with overload, the other unit covers the capacity.




Rotational operation control



Energy saving and longer life!

By operating two indoor units alternately, their chronological changes are equalized. (The alternate operation cycle can be specified in a range from 1 to 999 hours in increments of 1 hours.)



New

Stylish Remote Control

2025 Design Award



reddot winner 2025

The RC-ES1 Series has been honored with the prestigious Red Dot Design Award 2025 in the Product Design Category.



The RC-ES1 Series has been honored with the prestigious Gold A' Design Award in the Repair, Restoration, and Maintenance Products Design Category.



RC-ES1

- Stylish and sophisticated design
- Compact size (86×86mm)
- Remote control with Bluetooth® wireless technology



Optimized User Interface



The functions available on the remote have been minimized to focus on users' core needs, simplifying operation and avoiding overly complex settings. A wide range of functions, including service settings, remains accessible through the app.



You can control the air-conditioner by installing App on your smart phone



Search for "M-Air PRO" from the Google Play™ store for Android™ and App Store for iPhone.

Please check the app stores for the latest supported OS version information.
App Store and iPhone are registered trademark of Apple Inc.
Google Play and the Google Play logo are trademarks of Google LLC.

Wireless connection


- Remote control with Bluetooth® wireless technology
- Easy set-up of indoor units
- Notifications of abnormal conditions or operational data from the remote control will be sent to your smartphone.



Central management by smart phone

You can select and change the settings of multiple rooms with only one action on your smartphone.*

Easy setup and management of up to 20 units via smartphone and tablets, up to 10 settings could be saved in the app.



*The function would be available when the smartphone is connected to the remote control with Bluetooth® wireless technology.

Easy to instinctively operate with simplified icons

Operation settings	Common settings	Display & sound settings
<p> Operation mode Heating / Cooling / Fan / Dry /Auto</p> <p> High power ON / OFF</p> <p> Ventilation ON / OFF</p> <p> Timer Set ON / OFF timer by hour Set ON / OFF timer by clock</p> <p> Air direction Upper / lower flap, Flap direction</p>	<p> Bluetooth ON / OFF</p> <p> Pairing mode Make a new Bluetooth pairing</p> <p> App QR code QR code for the app</p>	<p> Brightness 1-10</p> <p> Lighting time 1-10</p> <p> Operation sound Sound On / Sound Off</p>

Information screen

Temporary stop	High power operation	Motion sensor control	On timer setting
Thermo-off	Eco operation	Anti draft control	OFF timer setting
Fan operation	Set temp. shift	Demand control	Weekly timer setting
Cooling test run	Warm up operation	Filter cleaning time	Sleep timer setting
Static pressure adjustment	Heating preparation	Back-up control in operation	
Dew drop prevention control	Defrost operation	Fault back-up control in operation	
Home leave operation	Outdoor silent operation	Periodical check indication	

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by MITSUBISHI HEAVY INDUSTRIES THERMAL SYSTEMS, LTD. is under license. Other trademarks and trade names are those of their respective owners.

"QR Code" is a registered trademark of DENSO WAVE INCORPORATED.

Information screen


By looking at the information screen, you can check the current operating conditions at a glance.



Easy installation with the new casing structure

The casing is separated into the lower and the upper case.

By inserting the upper case into the lower case embedded to the wall, the remote could be easily installed.



Indoor unit benefits Summary

Benefits Series



When using RC-EX3D (Remote control),
functions with symbol ● are available.

However, for RC-E5 (Remote control),
functions with ★ are not available.

Energy Saving 	Inverter technology	Inverter control technology delivers high efficiency and a smooth operation from high speed to low speed. A smooth sine voltage wave is attained.
	Energy-saving ★	Since the capacity is controlled automatically based on the outdoor temperature, energy can be saved without losing comfort.
	Motion sensor ★	This sensor detects human activity and shifts the temperature setting according to the amount of activity in the room.
	Home leave operation ★	This function ensures that when the room is unoccupied for long periods of time, the unit will maintain a moderate indoor temperature, avoiding extremely hot or cool temperatures.
	Set temperature auto return ★	This function allows the user to program a preferred set temperature that the unit will return to each time it is operated.
Comfort 	Automatic operation	This function automatically selects the required heating or cooling function based on the current room conditions.
	Silent operation	This function allows the user to program periods where the unit will operate with reduced noise levels, perfect for night time and an uninterrupted sleep.
	Hi power operation ★	Use the high power function to quickly reach your optimum temperature level when you first turn on the unit. This function will operate for a maximum of 15 minutes before returning to normal operation.
Air flow 	Flap control system	This function allows the user to set the upper and lower limit positions of the flap at each air outlet individually, providing you with complete control over interior air flow.
	Vertical auto swing	The vertical louvers on your unit will move up and down continuously during operation. This function allows you to set the up/down swing position of the louver to the preferred operation angle.
	Draft prevention setting ★	Draft Prevention setting provides a comfortable air flow without any draft feeling. Whether cooling or heating a room, the remote control can be used to instantly suppress any warm or cool drafts. This accurately assists how air flow is directed out of the indoor unit.
	Automatic fan speed	The unit's on-board microcomputer continuously monitors the room's air temperature and adjusts the air flow automatically.
Timer 	Sleep timer	This function allows the user to set a pre-determined amount of time between 30 and 240 minutes that your unit will operate for before switching off.
	Peak-cut timer ★	This function lets the user to preset the capacity limit during certain periods of the day, minimising energy consumption during peak billing times, thus reducing operation costs.
	Weekly timer	Set the unit to turn on and off automatically on a weekly basis to suit your usual room usage on each day.
Convenient 	Function Switch ★	From the eight available functions on the unit, this function allows the user to set two functions to operate automatically.
	Favourite setting ★	Operation mode, set temperature, fan speed and air flow direction automatically adjust to the programmed favourite setting.
	Static pressure adjustment	This is operable when connecting duct type indoor units equipped with the external static pressure adjustment function. It will adjust the air flow accordingly based on the connected duct static pressure.
	Select the language ★	Set the language to be displayed on the remote control.
	Air filter	The air filter in the unit traps and removes airborne dust particles and other allergens to provide you clean air.
	Filter sign	This warning alerts when the filter needs to be cleaned.
	Outside air intake	This function provides clean fresh air into the room through the external air intake, avoiding the constant recycling of internal air.
Others	Self diagnostics	The internal microcomputer automatically runs a diagnostic of the system in the event of a malfunction. This enables authorised dealers to isolate and repair any issues.
	Built in drain pump	The built-in drain pump, allows greater flexibility with installation, offering a great solution for applications with limited space.
	Improved serviceability	The fan unit (comprised of impeller and motor) is easily accessible from either the side or bottom of the unit and can be slid out for easy maintenance.

*1 : Except 224•280

*2 : Except 1800•2400

Ceiling Cassette -4way-FDT **New**



FDT28-160

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.



Draft Prevention Panel
(Option)

Remote control (Option)

Wired



Wireless



RCN-T-5BW-E2(White)
RCN-T-5BB-E2(Black)

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E




Panel select pattern			(Option)		
	Receiver	Sensor	Sensor	Receiver	Interface
KXZE3-W	Standard Panel	T-PSA-5CW(B)-E	Thermal sensor kit LC-T-5CW(B)-E	●	●
	Draft Prevention Panel	T-PSAE-5CW(B)-E	Motion sensor kit LB-T-5BW(B)-E	●	●
KXZE1	Standard Panel	T-PSA-5BW(B)-E	—	●	—
	Draft Prevention Panel	T-PSAE-5BW(B)-E	—	●	—

Automatic anti-draft control

Thermal sensor kit

LC-T-5CW-E
LC-T-5CB-E



1. Automatic anti-draft control


Automatically activates the louvers when the room temperature is hotter or colder than the set temperature. After detecting the room temperature at the set temperature, the draft prevention panel is activated.

2. Direct flow control


The louvers are controlled to blow towards human position.

3. Draft less control

Draft prevention panel is activated based on human position



Automatically activates Draft prevention panel




Space for 4-way direction are sensed.

Draft Prevention Panel (Option)



This prevents cold/hot draft being blown directly on the user. It is possible to set Draft Prevention Panel for each air outlet.




User can position panels by using the remote controller (RC-EX3D, Wireless kit) only when Draft Prevention Panel is available.

Motion Sensor (Option)

Motion sensor is equipped in the corner of the panel and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.




LB-T-5BW-E(White)
LB-T-5BB-E(Black)







Individual flap control system

According to room conditions, four directions of air flow can be controlled individually by utilizing the flap control system. Individual flap control is available even after installation.



Flap can swing within an upper and lower flap range position that can be selected with a wired remote control.

* The wireless remote control is not applicable to the Individual flap control system.



Power consumption decreased by new technologies

1. Adopting new impeller and flow path.

New designed impeller

improves the aerodynamic performance of the unit.





New designed component has better aerodynamic performance and achieve lower noise.

2. Ø5.0 heat exchanger tubes is adopted to improve the performance.

Slimmer heat exchanger

and a dense copper piping.




Wireless Control System Now available in our FDT series

Control your air-conditioner from anywhere, anytime. If you turn on the air-conditioner when you're on the go, you'll be comfortable when you get to the office. Even if you forget to turn it off, you can turn it off when you are out and about.



850mm Drain Pump

Drain can be discharged upwards up to 850mm from the ceiling surface, allowing a piping layout with a high degree of freedom. Thanks to the 185mm flexible hose, equipment supports easy workability.



■ SPECIFICATIONS

Indoor unit	FDT		28KXZE3-W	36KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	90KXZE3-W	112KXZE3-W	140KXZE3-W	160KXZE3-W									
Power source	1 Phase 220-240V, 50Hz																			
Nominal capacity	Cooling	kW	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0									
	Heating		3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0	18.0									
Power consumption	Cooling	W	40-40			70-70	80-80	130-130												
	Heating																			
Sound power level ¹⁾	Cooling	dB(A)	55			60	62	65												
	Heating																			
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	40/31/30/28	40/34/30/28	40/34/31/28	45/34/31/29	47/35/32/28	49/38/36/31	49/39/37/31	49/42/39/32	49/42/40/33									
	Heating		40/31/26/23	40/33/26/23	40/33/30/23															
Exterior dimensions (H × W × D)	Unit	mm	236 × 840 × 840				298 × 840 × 840													
	Panel		35 × 950 × 950				35 × 950 × 950													
Net weight	Unit	kg	21		22	24	28													
	Panel		Standard panel : 5, Draft prevention panel : 6																	
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	19/12/10/9	19/14/10/9	19/14/12/9	25/15/13/11	28/16/14/12	37/24/21/16	37/24/22/16	37/27/24/17	37/28/25/18									
	Heating																			
Outside air intake																				
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")													
	Gas		ø9.52(3/8")	ø12.7(1/2")			ø15.88(5/8")													
Panel (Option)																				
Air filter, Q'ty																				
White : T-PSA-5CW-E, T-PSAE-5CW-E Black : T-PSA-5CB-E, T-PSAE-5CB-E																				
Pocket plastic net × 1(Washable)																				

Indoor unit	FDT		28KXZE1	36KXZE1	45KXZE1	56KXZE1	71KXZE1	90KXZE1	112KXZE1	140KXZE1	160KXZE1									
Power source	1 Phase 220-240V, 50Hz																			
Nominal capacity	Cooling	kW	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0									
	Heating		3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0	18.0									
Power consumption	Cooling	W	40-40			70-70	80-80	130-130	140-140											
	Heating																			
Sound power level ¹⁾	Cooling	dB(A)	55			60	62	65	66											
	Heating																			
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	38/33/30/28		38/33/31/29	44/33/31/29	47/35/32/28	49/38/36/31	49/39/37/31	49/42/39/32	49/42/39/33									
	Heating																			
Exterior dimensions (H × W × D)	Unit	mm	236 × 840 × 840				298 × 840 × 840													
	Panel		35 × 950 × 950				35 × 950 × 950													
Net weight	Unit	kg	20		21.5			25												
	Panel		Standard panel : 5, Draft prevention panel : 6																	
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	20/14/12/10	20/14/12/10	20/15/13/10	26/16/13/11	28/17/14/12	37/25/22/15	38/26/23/17	38/28/25/18	38/29/26/19									
	Heating																			
Outside air intake																				
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")													
	Gas		ø9.52(3/8")	ø12.7(1/2")			ø15.88(5/8")													
Panel (Option)																				
White : T-PSA-5BW-E, T-PSAE-5BW-E Black : T-PSA-5BB-E, T-PSAE-5BB-E																				
Pocket plastic net × 1(Washable)																				

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions



Ceiling Cassette - 4way Compact FDTC



New



FDTC15-56

Honeycomb type



Draft Prevention Panel (Option)



Grid type

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-TC-5AW-E3

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E

Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Panel select pattern


(Option)

		Wireless receiver	Motion Sensor	Motion sensor	Wireless receiver	Motion sensor & Wireless receiver	
				LB-TC-5W-E	RCN-TC-5AW-E3	LB-TC-5W-E	RCN-TC-5AW-E3
Honeycomb type	Standard Panel	TC-PSA-5AW-E	●	●		●	
	Draft Prevention Panel	TC-PSAE-5AW-E	●	●		●	
Grid type	Standard Panel	TC-PSAG-5AW-E	●	●		●	
	Draft Prevention Panel	TC-PSAGE-5AW-E	●	●		●	

European design & Flat panel

Unique Grille Design

A grille designed with a unique structure and a clean white panel that blends with the room.




Integrated ceiling system design 600x600

Easy installation - with a weight of only 14kg, a thin panel, and a main body size of only 248mm.



Draft Prevention Panel

This prevents cold/hot draft being blown directly on the user. It is possible to set Draft Prevention Panel for each air outlet.



User can position panels by using the remote controller (RC-EX3D, Wireless kit) only when Draft Prevention Panel is available.


Individual flap control system

According to room temperature conditions, four directions of air flow can be controlled individually by following Flap control system. Individual flap control is available even after installation.



The flap can swing within the range of upper and lower flap position selected with wired remote control.


*The wireless remote control is not applicable to the Individual flap control system.



Motion Sensor

(Option)


Motion sensor is equipped in the corner of the panel and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-TC-5W-E


Suitable for High ceilings

The Powerful blowout carries comfortable air flow to the floor even in high ceiling applications. It is ideal for high ceiling offices, stores, etc., with a wide, uniform air flow throughout the room.



850mm Drain Pump


Drain can be discharged upward by 850 mm from the ceiling surface close to the indoor unit. It allows a piping layout with a high degree of freedom depending on the installation location.



Taking OA (Outside Air) into inside

Fresh air can be taken in without optional parts. When the fresh air is insufficient, optional parts can be used.

OA Spacer TC-OAS-E2 (Option)
Joint Duct TC-OAD-E (Option)



■ SPECIFICATIONS

Indoor unit	FDTC		15KXZE3-W	22KXZE3-W	28KXZE3-W	36KXZE3-W	45KXZE3-W	56KXZE3-W							
Power source			1 Phase 220-240V, 50Hz												
Nominal capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6							
	Heating		1.7	2.5	3.2	4.0	5.0	6.3							
Power consumption	Cooling	W	30-30			40-40	50-50	60-60							
	Heating		47	49	54	58	60								
Sound power level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	46			53	57								
	Heating		33/30/28/25		35/32/29/25	39/36/31/26	43/39/36/28	47/43/39/31							
Exterior dimensions (H × W × D)	Unit	mm	248 × 570 × 570												
	Panel		10 × 620 × 620												
Net weight	Unit	kg	12.5	13	14										
	Panel		Standard panel : 2.5, Draft prevention panel : 3												
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	8/7/6/5	9/8/7/6	10/9/8/6	12/10/9/7	14/12/10/8								
	Heating		Possible												
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")												
	Gas		ø9.52(3/8")												
Panel (Option)		Honeycomb : TC-PSA-5AW-E, TC-PSAE-5AW-E Grid : TC-PSAG-5AW-E, TC-PSAGE-5AW-E													
Air filter, Q'ty		Pocket plastic net × 1(Washable)													

Indoor unit	FDTC		15KXZE1	22KXZE1	28KXZE1	36KXZE1	45KXZE1	56KXZE1							
Power source			1 Phase 220-240V, 50Hz												
Nominal capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6							
	Heating		1.7	2.5	3.2	4.0	5.0	6.3							
Power consumption	Cooling	W	30-30			40-40	50-50	60-60							
	Heating		47	49	54	58	60								
Sound power level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	46			53	57								
	Heating		33/30/28/25		35/32/29/25	39/36/31/26	43/39/36/28	47/43/39/31							
Exterior dimensions (H × W × D)	Unit	mm	248 × 570 × 570												
	Panel		10 × 620 × 620												
Net weight	Unit	kg	12.5	13	14										
	Panel		Standard panel : 2.5, Draft prevention panel : 3												
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	8/7/6/5	9/8/7/6	10/9/8/6	12/10/9/7	14/12/10/8								
	Heating		Possible												
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")												
	Gas		ø9.52(3/8")												
Panel (Option)		Honeycomb : TC-PSA-5AW-E, TC-PSAE-5AW-E Grid : TC-PSAG-5AW-E, TC-PSAGE-5AW-E													
Air filter, Q'ty		Pocket plastic net × 1(Washable)													

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.



Ceiling Cassette -2way-FDTW



New

FDTW28-71




FDTW90-140

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.


Individual flap control system

We've optimised our outlet design with advanced technology to allow you to control up to four directions of air flow. Allowing you to control air direction via the flap systems and room temperature.



The flap can swing within the range of upper and lower flap position selected with wired control.

*The wireless remote control is not applicable with the individual flap control system.



Installation workability

Drainage flow test can be done easily by use of this drainage spout.



850mm Drain Pump

The drain discharge system allows for a piping layout with a high degree of freedom (dependent on installation location). Discharge from above 850mm from a ceiling surface to the indoor unit.

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-TW-E2

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E




Motion Sensor


(Option)

Motion sensor is equipped in the corner of the panel and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.

LB-TW-6W



Transparent access hole to drain pan



Transparent access hole to drain pan

■ SPECIFICATIONS

Indoor unit	FDTW		28KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	90KXZE3-W	112KXZE3-W	140KXZE3-W			
Power source		1 Phase 220-240V, 50Hz										
Nominal capacity	Cooling	kW	2.8	4.5	5.6	7.1	9.0	11.2	14.0			
	Heating		3.2	5.0	6.3	8.0	10.0	12.5	16.0			
Power consumption		W	90-90	100-100		140-140	190-190					
Sound power level ¹⁾			dB(A)	57	58		63					
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)		dB(A)	42/38/34/31				48/45/41/37					
Exterior dimensions (H × W × D)	Unit	mm	325 × 820 × 620				325 × 1535 × 620					
	Panel		20 × 1120 × 680				20×1835×680					
Net weight	Unit	kg	20	21	23	35						
	Panel		8.5	8.5	8.5	13						
Air flow (P-Hi/Hi/Me/Lo)		m ³ /min	14.5/12/10/9				31/27/23/20					
Outside air intake			Possible									
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")			ø9.52(3/8")						
	Gas		ø9.52(3/8")	ø12.7(1/2")		ø15.88(5/8")						
Panel (Option)		TW-PSA-26W-E						TW-PSA-46W-E				
Air filter, Q'ty		Pocket plastic net × 2 (Washable)					Pocket plastic net × 3 (Washable)					

Indoor unit	FDTW		28KXE6F	45KXE6F	56KXE6F	71KXE6F	90KXE6F	112KXE6F	140KXE6F			
Power source		1 Phase 220-240V, 50Hz										
Nominal capacity	Cooling	kW	2.8	4.5	5.6	7.1	9.0	11.2	14.0			
	Heating		3.2	5.0	6.3	8.0	10.0	12.5	16.0			
Power consumption		W	90-90	100-100		140-140	190-190					
Sound power level ¹⁾			dB(A)	58			65					
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)		dB(A)	42/38/34/31				48/45/41/37					
Exterior dimensions (H × W × D)	Unit	mm	325 × 820 × 620				325 × 1535 × 620					
	Panel		20 × 1120 × 680				20×1835×680					
Net weight	Unit	kg	20	21	23	35						
	Panel		8.5	8.5	8.5	13						
Air flow (P-Hi/Hi/Me/Lo)		m ³ /min	14.5/12/10/9				31/27/23/20					
Outside air intake			Possible									
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")			ø9.52(3/8")						
	Gas		ø9.52(3/8")	ø12.7(1/2")		ø15.88(5/8")						
Panel (Option)		TW-PSA-26W-E					TW-PSA-46W-E					
Air filter, Q'ty		Pocket plastic net × 2(Washable)					Pocket plastic net × 3(Washable)					

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Ceiling Cassette -1way-FDTs



New



*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.


Individual flap control system

Two directions of air flow can be controlled individually by flap control system.




The flap can swing within the range of upper and lower flap position selected with wired control.

*The wireless remote control is not applicable with the individual flap control system.



Compact design

Indoor unit size (W:1150 x D:565) brings easy installation for 1200 x 600 ceiling and Panel size (1250 x 650) is suitable for 1200 x 600 ceiling. Height is the industry's lowest height level 220mm and weight is only 27, 28kg.



SPECIFICATIONS

Indoor unit	FDTs		45KXZE3-W	71KXZE3-W	45KXE6F	71KXE6F					
Power source											
Nominal capacity	Cooling	kW	4.5	7.1	4.5	7.1					
	Heating		5.0	8.0	5.0	8.0					
Power consumption	Cooling	W	40-40	90-90	40-40	90-90					
	Heating										
Sound power level ¹⁾	Cooling	dB(A)	52	60	60	61					
	Heating										
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	40/39/37/35	49/46/41/36	42/40/38/35	49/46/41/36					
	Heating										
Exterior dimensions (H x W x D)	Unit	mm	220 x 1150 x 565								
	Panel		35 x 1250 x 650								
Net weight	Unit	kg	27	28	27	28					
	Panel		5	5	5	5					
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	13/12/11/9.5	17/15/12/10	13/12/11/9.5	17/15/12/10					
	Heating										
Outside air intake											
Possible											
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")	ø9.52(3/8")	ø6.35(1/4")	ø9.52(3/8")					
	Gas		ø12.7(1/2")	ø15.88(5/8")	ø12.7(1/2")	ø15.88(5/8")					
Panel (Option)											
TS-PSA-3AW-E											
Air filter, Q'ty											
Pocket plastic net x 2(Washable)											

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Remote control (Option)

Wired



RC-EX3D



RC-E5

Wireless



RC-ES1



RCN-TS-E2

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E




Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Motion Sensor

(Option)

Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



850mm Drain Pump

Drain can be discharged upward by 850mm from the ceiling surface close to the indoor unit.
It allows a piping layout with a high degree of freedom depending on the installation location.

Ceiling Cassette -1way Compact-FDTQ

New



FDTQ22-36

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.

Compact design

- Comfortable effective cooling for small rooms, with low fan speed air flow at just 5.4m³/min.



Optional wide panel shown for solid ceiling

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



For this model a relay kit (SV-RLY-E) is required to connect to the shut-off valve.



Remote control (Option)


Wired




Wireless



RCN-KIT4-E2



- Condensate drain pump included as standard



- Ultra slim design at just 250mm above the ceiling

Motion Sensor

(Option)

Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-KIT2

SPECIFICATIONS

Indoor unit	FDTQ	22KXZE3-W	28KXZE3-W	36KXZE3-W	22KXE6F	28KXE6F	36KXE6F				
Panel Name	Direct blow panel										
Panel (Option)	TQ-PSA-15W-E (Short Panel) TQ-PSB-15W-E (Wide Panel)										
Power source	1 Phase 220-240V, 50Hz										
Nominal capacity	Cooling Heating	kW	2.2 2.5	2.8 3.2	3.6 4.0	2.2 2.5	2.8 3.2				
Power consumption	Cooling Heating	W	50-70								
Sound power level ¹	Cooling Heating	dB(A)	56			60					
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Cooling Heating	dB(A)	45/41/38/34			45/41/38/33					
Exterior dimensions (H × W × D)	Unit Panel	mm	250 × 570 × 570 35 × 625 × 650 (TQ-PSA-15W-E), 35 × 780 × 650 (TQ-PSB-15W-E)								
Net weight	Unit Panel	kg	19 2.5(TQ-PSA-15W-E), 3(TQ-PSB-15W-E)								
Air flow (P-Hi/Hi/Me/Lo)	Cooling Heating	m ³ / min	8/7/6/5								
Outside air intake	Possible										
Refrigerant piping size (Flare)	Liquid Gas	mm (in)	ø6.35(1/4") ø12.7(1/2")								
Air filter, Q'ty	Pocket plastic net × 1(Washable)										

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Duct Connected -High Static Pressure- FDU

New



FDU45-160





FDU224 • 280

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.


Static pressure could be adjusted via the remote control



The static pressure of the air duct could simply be adjusted via the remote control thereby work above the ceiling to adjust is no longer required.




Reduction of sound pressure level



Motion Sensor

(Option)

Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-KIT2

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-KIT4-E2

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E

Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Thin design

The height of FDU (45-160) models are only 280mm




Transparent inspection window

Dirt condition of the bottom of the drain pan can be checked through this transparent inspection window without removing drain pan. (Please refer to P92)


Improvement of the serviceability

Fan unit (impeller and motor) can be pulled out from the right side of the unit. Maintenance can be carried out from the right side or the bottom side of the unit.

Unit image



Opening from the side



Opening from the bottom

For washing and replacing the heat exchanger
For washing the drain pan

■ SPECIFICATIONS

Indoor unit	FDU		45KXZE3-W	56KXZE3-W	71KXZE3-W	90KXZE3-W	112KXZE3-W	140KXZE3-W	160KXZE3-W	224KXZE3-W	280KXZE3-W						
Power source																	
Nominal capacity	Cooling	kW	4.5	5.6	7.1	9.0	11.2	14.0	16.0	22.4	28.0						
	Heating		5.0	6.3	8.0	10.0	12.5	16.0	18.0	25.0	31.5						
Power consumption	Cooling	W	100-100		240-250		310-320	350-360	420-430	1.160-1.200							
Sound power level ¹	Cooling	dB(A)	58		63		68		72	78							
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Heating	dB(A)	60		65		69										
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	34/29/27/25		37/31/27/22		40/36/34/28	41/37/34/28	45/38/34/29	52/50/47/44							
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Heating	dB(A)	35/30/29/25		39/33/28/23		41/36/34/28										
Exterior dimensions (H × W × D)	mm	280 × 750 × 635		280 × 950 × 635		280 × 1368 × 738			379 × 1600 × 893								
Net weight	kg	29		34		54			89								
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	13/10/9/8		24/19/15/10		36/28/25/19	39/32/26/20	48/35/28/22	80/72/64/56							
Available static pressure	Pa	200															
Outside air intake	Possible																
Refrigerant piping size	Liquid	mm	ø6.35(1/4") (Flare)		ø9.52(3/8") (Flare)				ø9.52(3/8") (Brazing)								
	Gas	(in)	ø12.7(1/2") (Flare)		ø15.88(5/8") (Flare)				ø19.05(3/4") (Brazing)	ø22.22(7/8") (Brazing)							
Air filter, Q'ty	Procure locally																

Indoor unit	FDU		45KXE6F	56KXE6F	71KXE6F	90KXE6F	112KXE6F	140KXE6F	160KXE6F	224KXZE1	280KXZE1						
Power source																	
Nominal capacity	Cooling	kW	4.5	5.6	7.1	9.0	11.2	14.0	16.0	22.4	28.0						
	Heating		5.0	6.3	8.0	10.0	12.5	16.0	18.0	25.0	31.5						
Power consumption	Cooling	W	100-100		240-250		310-320	350-360	420-430	1.160-1.200							
Sound power level ¹	Cooling	dB(A)	60		65		71	72	74	75							
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Heating	dB(A)	37/32/29/26		38/33/29/25		44/38/36/30	45/40/34/29	47/40/35/30	52/50/47/45							
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	35/30/29/26		39/33/28/23		41/36/34/28										
Exterior dimensions (H × W × D)	mm	280 × 750 × 635		280 × 950 × 635		280 × 1368 × 740			379 × 1600 × 893								
Net weight	kg	29		34		54			89								
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	13/10/9/8		24/19/15/10		36/28/25/19	39/32/26/20	48/35/28/22	80/72/64/56							
Available static pressure	Pa	200															
Outside air intake	Possible																
Refrigerant piping size	Liquid	mm	ø6.35(1/4") (Flare)		ø9.52(3/8") (Flare)				ø9.52(3/8") (Brazing)								
	Gas	(in)	ø12.7(1/2") (Flare)		ø15.88(5/8") (Flare)				ø19.05(3/4") (Brazing)	ø22.22(7/8") (Brazing)							
Air filter, Q'ty	Procure locally																


1. The data are measured under the following conditions (ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.


Round duct adapter (Available for FDU 45–160, FDUM 22–160)

Company: AIRZONE
URL: <http://www.airzone.es>

All-in-one solution: the whole zoning system in a plug&play device perfectly adapted to the indoor DX unit



Main components



Duct Connected -Low/Middle Static Pressure- FDUM



New



FDUM22-160

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.



*Filter pressure loss:5Pa

Filter kit (Option)

UM-FL1EF : for 22-56
UM-FL2EF : for 71, 90
UM-FL3EF : for 112, 140, 160

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-KIT4-E2

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E





Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Static pressure could be adjusted via the remote control




The static pressure of the air duct could simply be adjusted via the remote control thereby work above the ceiling to adjust is no longer required.



Motion Sensor (Option)

Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-KIT2

Improvement of the serviceability

Fan unit (impeller and motor) can be pulled out from the right side of the unit. Maintenance can be carried out from the right side or the bottom side of the unit.

Round duct adapter

In case of requirements of round duct adapter, please refer to P97.

Company URL [AIRZONE](http://www.airzone.es)




Thin design

The height of all FDUM models only 280mm


Transparent inspection window

Dirt condition of the bottom of the drain pan can be checked through this transparent inspection window without removing drain pan.
(Please refer to P92)

Unit image



Opening from the side



Opening from the bottom

For washing and replacing the heat exchanger
For washing the drain pan

■ SPECIFICATIONS

Indoor unit	FDUM		22KXZE3-W	28KXZE3-W	36KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	90KXZE3-W	112KXZE3-W	140KXZE3-W	160KXZE3-W							
Power source	1 Phase 220-240V, 50Hz																		
Nominal capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0							
	Heating		2.5	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0	18.0							
Power consumption	Cooling	W	80-80				160-160		250-250	260-260	380-380								
	Heating		60				65		69		72								
Sound power level ¹	Cooling	dB(A)	57		58		63		68										
	Heating		60		60		65		69										
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	33/27/25/23		34/29/27/25		37/31/27/22		40/36/34/28	41/37/34/28	45/38/34/29								
	Heating		36/30/29/25		35/30/29/25		39/33/28/23		41/36/34/28	41/37/34/28	45/38/34/29								
Exterior dimensions (H × W × D)	mm		280 × 750 × 635				280 × 950 × 635		280 × 1368 × 738										
Net weight	kg		29				34		54										
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	13/10/9/8				24/19/15/10		36/28/25/19	39/32/26/20	48/35/28/22								
	Heating		60				65		71										
Available static pressure	Pa		100				Possible												
Outside air intake																			
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")		ø15.88(5/8")										
	Gas		ø9.52(3/8")		ø12.7(1/2")														
Air filter (Option)			UM-FL1EF				UM-FL2EF		UM-FL3EF										

Indoor unit	FDUM		22KXE6F	28KXE6F	36KXE6F	45KXE6F	56KXE6F	71KXE6F	90KXE6F	112KXE6F	140KXE6F	160KXE6F					
Power source	1 Phase 220-240V, 50Hz																
Nominal capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0	16.0					
	Heating		2.5	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0	18.0					
Power consumption	Cooling	W	100-100				200-200		290-290	330-330	450-450						
	Heating		60				65		71	72	74						
Sound power level ¹	Cooling	dB(A)	37/32/29/26				38/33/29/25		44/38/36/30	45/40/34/29	47/40/35/30						
	Heating		60				65		71								
Sound pressure level ¹ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	37/32/29/26				38/33/29/25		44/38/36/30	45/40/34/29	47/40/35/30						
	Heating		60				65		71								
Exterior dimensions (H × W × D)	mm		280 × 750 × 635				280 × 950 × 635		280 × 1368 × 740								
Net weight	kg		29				34		54								
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min	13/10/9/8				24/19/15/10		36/28/25/19	39/32/26/20	48/35/28/22						
	Heating		60				65		71								
Available static pressure	Pa		100				Possible										
Outside air intake																	
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")		ø15.88(5/8")								
	Gas		ø9.52(3/8")		ø12.7(1/2")												
Air filter (Option)			UM-FL1EF				UM-FL2EF		UM-FL3EF								

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Duct Connected (thin) -Low Static Pressure- FDUT



New



FDUT15-71

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-KIT4-E2

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E




Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



For this model a relay kit (SV-RLY-E) is required to connect to the shut-off valve.




Motion Sensor	(Option)	Filter kit	(Option)
Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.	LB-KIT2	Filter pressure loss : 5 Pa	



Item	Contents	for FDUT15/22/28/36	for FDUT45/56	for FDUT71
Outlet duct plate	①	UT-SAT1EF	UT-SAT2EF	UT-SAT3EF
Filter set	②+③	UT-FL1EF	UT-FL2EF	UT-FL3EF

Filter pressure loss : 5 Pa



SPECIFICATIONS

Indoor unit	FDUT	15KXZE3-W	22KXZE3-W	28KXZE3-W	36KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W
Power source								
Nominal capacity	Cooling Heating	kW	1.5 1.7	2.2 2.5	2.8 3.2	3.6 4.0	4.5 5.0	5.6 6.0
Power consumption	Cooling Heating	W	57-58	63-66 65-67	67-70 70-72	75-78 72-76	76-80 73-78	80-80 70-70
Sound power level ¹	Cooling Heating	dB(A)	52 51	52	54 55	54	55	56 57
Sound pressure level ¹ (Hi/Me/Lo)	Cooling Heating	dB(A)	28/26/21 28/25/20	28/26/22	30/28/24 31/29/25	30/26/24 30/27/25	31/27/24 31/28/26	32/28/27 32/28/26
Sound pressure level ² (Hi/Me/Lo)	Cooling Heating	dB(A)	32/29/25	32/29/25	37/34/28	36/33/27	38/33/29	41/37/32
Exterior dimensions (H × W × D)	mm		200 × 750 × 500			200 × 950 × 500		220 × 1150 × 565
Net weight	kg	22	21	22		25		31
Air flow (Hi/Me/Lo)	Cooling Heating	m ³ /min	6/5/4	7.5/6/5	8.5/7/5.5	11.5/9/7	12.5/9/7.2	16/13/9.5
External static pressure	Pa		Standard : 10 Max : 35			Standard : 10 Max : 50		
Outside air intake			Possible					
Refrigerant piping size (Flare)	Liquid Gas	mm (in)		ø6.35(1/4") ø9.52(3/8")		ø12.7(1/2")		ø9.52(3/8") ø15.88(5/8")
Air filter (Option)			UT-FL1EF			UT-FL2EF		UT-FL3EF

- The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
- The data of nominal cooling and heating capacity and sound pressure level are measured with 10Pa of external static pressure.
- The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
- Sound Pressure Level shows the value when the supply duct of 2m and the return duct of 1m (except the Bottom air return) are connected to the unit.

Sound pressure level *1:Mike position is 1.5m below the unit, *2:Mike position is 1m in front and 1m below od the air supply duct.

Indoor unit	FDUT		15KXE6F-E	22KXE6F-E	28KXE6F-E	36KXE6F-E	45KXE6F-E	56KXE6F-E	71KXE6F-E				
Power source		1 Phase 220-240V, 50Hz											
Nominal capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1				
	Heating		1.7	2.5	3.2	4.0	5.0	6.0	8.0				
Power consumption	Cooling	W	60-60		70-70		80-80		80-80				
	Heating								70-70				
Sound power level ¹	Cooling	dB(A)	52			57	58	59					
Sound pressure level ¹	Heating					33/30/26	34/32/28	35/33/30	35/31/28				
Sound pressure level ²	Cooling	dB(A)	28/26/22			37/34/28	36/33/27	38/33/29	41/37/32				
Sound pressure level ²	Heating		32/29/25										
Exterior dimensions (H x W x D)		mm	200 x 750 x 500				200 x 950 x 500		220 x 1150 x 565				
Net weight		kg	22	21	22	25	31						
Air flow (Hi/Me/Lo)	Cooling	m ³ /min	6/5/4	7.5/6/5		8.5/7/5.5	11.5/9/7	12.5/9/7.2	16/13/9.5				
	Heating												
External static pressure		Pa	Standard : 10 Max : 35				Standard : 10 Max : 50						
Outside air intake		Possible											
Refrigerant piping size (Flare)	Liquid	mm	ø6.35(1/4")				ø9.52(3/8")						
	Gas	(in)	ø9.52(3/8")				ø12.7(1/2")		ø15.88(5/8")				
Air filter (Option)		UT-FL1EF				UT-FL2EF		UT-FL3EF					

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
2. The data of nominal cooling and heating capacity and sound pressure level are measured with 10Pa of external static pressure.
3. The sound level indicates the value of rear-intake type with duct in anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
4. Sound Pressure Level shows the value when the supply duct of 2m and the return duct of 1m (except the Bottom air return) are connected the unit.

Sound pressure level *1:Mike position is 1.5m below the unit, *2:Mike position is 1m in front and 1m below od the air supply duct.

Duct Connected (Compact & Flexible) FDUH

New



FDUH22-36



Filter kit (Option) UH-FL1E



*Filter pressure loss:5Pa

Drain up kit (Option) (600mm) UH-DU-E



R32 Leak detector and shut-off valve available as an option

Refrigerant
leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-KIT4-E2


For this model a relay kit (SV-RLY-E) is required to connect to the shut-off valve.



*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.

Compact and thin size, light weight

Our leading high technology has created the best solution for air-conditioning in hotels. The compact and thin sized units don't compromise on high energy efficiency all while weighing in at only 20kg. The lowest sound level in the industry can ensure comfortable stay and rest in hotels.



Motion Sensor

(Option)


Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-KIT2

Installation Flexibility

Control box and drain piping can be installed on both side of the unit and air intake to the unit is available from bottom or back side. Our highest technology can satisfy diverse installation requirements.



■ SPECIFICATIONS

Indoor unit	FDUH		22KXZE3-W	28KXZE3-W	36KXZE3-W	22KXE6F	28KXE6F	36KXE6F
Power source								
Nominal capacity	Cooling	kW	2.2	2.8	3.6	2.2	2.8	3.6
	Heating		2.5	3.2	4.0	2.5	3.2	4.0
Power consumption								
Sound power level ¹⁾	Cooling	dB(A)	58			60		
	Heating							
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)		dB(A)	36/33/30/27			39/33/30/27		
Heating								
External dimensions (H × W × D)		mm	256 × 550 × 525			257 × 570 × 530		
Net weight		kg	19			20		
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ / min				8.5/7/6.5/6		
	Heating							
Static pressure		Pa				30		
Outside air intake						Not possible		
Refrigerant piping size (Flare)	Liquid	mm (in)				ø6.35(1/4")		
	Gas		ø9.52(3/8")			ø9.52(3/8")		
Air filter (Option)			UH-FL1E			ø12.7(1/2")		

1. The data are measured under the following conditions (ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Wall Mounted FDK



New



FDK15-56



FDK71-90

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.


Elegant Timeless Design

The FDK series air-conditioners are innovatively designed with rounded contours that beautifully fit into any of Europe's diverse interior settings. Created by an Italian industrial design studio based in Milan, Tensa srl, the design meets a broad range of requirements. (FDK15-56)

Flap control system


Selection of flap position is possible. A flap can be set at different angles.

*The wireless remote control is not applicable to the flap control system.



Lateral Swing ► flap swings from right to left automatically


Up/Down Flap swing + Lateral swing



Jet Technology

FDK models adopt the air flow design that's proven to minimise resistance in a CFD analysis to achieve uniform air-conditioning to the furthest corners of the room.

Fast Slow
Colours in the figure show the air speed.




Motion Sensor

(Option)

Motion sensor is equipped in the ceiling plane or wall plane and detects the presence/absence and activity of humans in a room to improve the comfort and energy saving performance of the unit.



LB-KIT2



Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-K-E2:
FDK15-56



RCN-K71-E2:
FDK71-90

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



■ SPECIFICATIONS

Indoor unit	FDK		15KXZE3-W	22KXZE3-W	28KXZE3-W	36KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	90KXZE3-W			
Power source	1 Phase 220-240V, 50Hz												
Nominal capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1	9.0			
	Heating		1.7	2.5	3.2	4.0	5.0	6.3	8.0	10.0			
Power consumption	Cooling	W	20-20			30-30			40-40	50-50			
Sound power level ¹⁾	Cooling	dB(A)	54	55		58		58	59	61			
	Heating							61					
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	38/34/31/28	38/36/30/27		40/38/33/28	43/41/36/33	43/41/36/33	42/40/37/35	44/42/39/35			
	Heating							44/42/37/33					
Exterior dimensions (H × W × D)	mm	290 × 870 × 230						339 × 1197 × 262					
Net weight	kg	11.5	11		11.5			17					
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	5.7/5/4.5/3.6	8.5/8/6/5		11/10/8/7	12/11/9/8	12/11/9/8	21/19/16/14	23/21/19/16			
	Heating							13/12/10/8					
Outside air intake	Not possible												
Refrigerant piping size (Flare)	Liquid	mm	ø6.35(1/4")						ø9.52(3/8")				
	Gas	(in)	ø9.52(3/8")		ø12.7(1/2")			ø15.88(5/8")					
Air filter, Q'ty	Polypropylene net × 2 (Washable)												

Indoor unit	FDK		15KXZE1	22KXZE1	28KXZE1	36KXZE1	45KXZE1	56KXZE1	71KXZE1	90KXZE1			
Power source	1 Phase 220-240V, 50Hz												
Nominal capacity	Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.6	7.1	9.0			
	Heating		1.7	2.5	3.2	4.0	5.0	6.3	8.0	10.0			
Power consumption	Cooling	W	20-20			30-30			40-40	50-50			
Sound power level ¹⁾	Cooling	dB(A)	54	55		58		58	59	61			
	Heating							61					
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	38/34/31/28	38/36/32/28		40/38/33/28	43/41/36/33	43/41/36/33	42/40/37/35	44/42/39/35			
	Heating							44/42/37/33					
Exterior dimensions (H × W × D)	mm	290 × 870 × 230						339 × 1197 × 262					
Net weight	kg	11.5	11		11.5			17					
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	5.7/5/4.5/3.6	8.5/8/6/5		11/10/8/7	12/11/9/8	12/11/9/8	21/19/16/14	23/21/19/16			
	Heating							13/12/10/8					
Outside air intake	Not possible												
Refrigerant piping size (Flare)	Liquid	mm	ø6.35(1/4")						ø9.52(3/8")				
	Gas	(in)	ø9.52(3/8")		ø12.7(1/2")			ø15.88(5/8")					
Air filter, Q'ty	Polypropylene net × 2 (Washable)												

1. The data are measured under the following conditions (ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Ceiling Suspended FDE

New




FDE36-140

*R32 indoor unit are not compatible with R410A outdoor unit and vice versa.

Flap control system

Selection of flap position is possible.
A flap can be set at different angles.

*The wireless remote control is not applicable to the flap control system.



R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E

Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



Motion Sensor

(Option)

By detecting presence or absence of human activity in a room, the motion sensor improves room comfort and unit energy saving performance.



LB-E

SPECIFICATIONS

Indoor unit	FDE		36KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	112KXZE3-W	140KXZE3-W					
Power source			1 Phase 220-240V, 50Hz										
Nominal capacity	Cooling	kW	3.6	4.5	5.6	7.1	11.2	14.0					
	Heating		4.0	5.0	6.3	8.0	12.5	16.0					
Power consumption			50-50				70-70	100-100	130-130				
Sound power level ¹⁾	Cooling	dB(A)	59	59	59	61	61	64					
	Heating		60	60	60								
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	45/38/31/26	45/38/36/31			46/39/37/32	45/42/38/34	48/43/40/35				
	Heating												
Exterior dimensions (H × W × D)		mm	210 × 1070 × 690				210 × 1320 × 690	250 × 1620 × 690					
Net weight		kg	28				35	43					
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	13/10/7/5.5	13/10/9/7			20/15/13/10	28/25/21/16.5	32/26/23/17				
	Heating												
Outside air intake			Not possible										
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")						
	Gas		ø12.7(1/2")				ø15.88(5/8")						
Air filter, Q'ty			Pocket Plastic net × 2 (Washable)										

Indoor unit	FDE		36KXZE1	45KXZE1	56KXZE1	71KXZE1	112KXZE1	140KXZE1				
Power source			1 Phase 220-240V, 50Hz									
Nominal capacity	Cooling	kW	3.6	4.5	5.6	7.1	11.2	14.0				
	Heating		4.0	5.0	6.3	8.0	12.5	16.0				
Power consumption			50-50				70-70	100-100	130-130			
Sound power level ¹⁾	Cooling	dB(A)	60				62	61	64			
	Heating											
Sound pressure level ¹⁾ (P-Hi/Hi/Me/Lo)	Cooling	dB(A)	46/38/31/26	46/38/36/31			47/39/37/32	45/42/38/34	48/43/40/35			
	Heating											
Exterior dimensions (H × W × D)		mm	210 × 1070 × 690				210 × 1320 × 690	250 × 1620 × 690				
Net weight		kg	28				33	43				
Air flow (P-Hi/Hi/Me/Lo)	Cooling	m ³ /min	13/10/7/5.5	13/10/9/7			20/15/13/10	28/25/21/16.5	32/26/23/17			
	Heating											
Outside air intake			Not possible									
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")				ø9.52(3/8")					
	Gas		ø12.7(1/2")				ø15.88(5/8")					
Air filter, Q'ty			Pocket Plastic net × 2 (Washable)									

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-E-E3

Floor Standing -2way- FDFW



New



FDFW28-56

Sophisticated Design


With an elegant semi flat front panel in stylish white, the new series fit in various kinds of rooms and create relaxing atmosphere. Choice of wall hanging, floor standing or behind gallery installation is available.

Flap control system

Selection of flap position is possible.

A flap can be set at different angles.

*The wireless remote control is not applicable to the flap control system.



Quiet Operation

Thanks to the optimum balance of air outlet direction and sufficient air flow volume, the sound level has been minimized. The level of FDFW28KXZE3-W in the cooling Lo mode is only 27dB(A).

Remote control (Option)

Wired




RC-EX3D



RC-E5



RC-ES1



RCN-FW-E2

Auto air outlet selection



R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E




For this model a relay kit (SV-RLY-E) is required to connect to the shut-off valve.



Convenient to use operation

Simultaneous lower and upper air outlets or upper outlet can be selected by air flow direction button. Further control can be arranged by a remote control.



(In case of use of wireless remote control)

■ SPECIFICATIONS

Indoor unit	FDFW		28KXZE3-W	45KXZE3-W	56KXZE3-W	28KXE6F	45KXE6F	56KXE6F		
Power source			1 Phase 220-240V, 50Hz							
Nominal capacity	Cooling	kW	2.8	4.5	5.6	2.8	4.5	5.6		
	Heating		3.2	5.0	6.3	3.2	5.0	6.3		
Power consumption			20-20		30-30	20-20		30-30		
Sound power level ¹⁾	Cooling	dB(A)	48	51	57	55	57	60		
	Heating		49	52	56					
Sound pressure level ¹⁾ (Hi/Me/Lo)	Cooling	dB(A)	35/33/27	38/36/31	44/37/31	36/34/30	38/36/33	44/37/33		
	Heating		36/34/29	38/36/33	44/37/33					
Exterior dimensions (H x W x D)		mm	600 x 860 x 238							
Net weight		kg	18	19	19	20				
Air flow (Hi/Me/Lo)	Cooling	m ³ / min	9/8/7		11/9/8	9/8/7		11/9/8		
	Heating									
Outside air intake			Not possible							
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")			ø6.35(1/4")				
	Gas		ø9.52(3/8")	ø12.7(1/2")		ø9.52(3/8")	ø12.7(1/2")			
Air filter, Q'ty			Polypropylene net x 1 (Washable)							

1. The data are measured under the following conditions (ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Floor Standing (with casing) FDFL

Floor Standing (without casing) FDFU



New



FDFL71

Remote control (Option)

Wired



RC-EX3D



RC-E5



RC-ES1

Wireless



RCN-KIT4-E2




FDFU28-71 (Concealed type)

Improved comfort with the air flow from a wide outlet

With the 60 degrees angle of the air flow from the front to the upper side the comfort has increased.

Piping could be taken from the side and the bottom leading to an improved serviceability and ease of installation



Wider air flow for optimum comfort

R32 Leak detector and shut-off valve available as an option

Refrigerant leak detector
RLD-KIT-E



Shut-off valve
SV-KIT-S1N-E
SV-KIT-L1N-E



For this model a relay kit (SV-RLY-E) is required to connect to the shut-off valve.



Motion Sensor

(Option)

The optional motion sensor on our floor standing units saves energy by operations by detecting human movement. Our smart technology provides energy saving control by shifting set temperature by detecting human activity.



LB-KIT2

■ SPECIFICATIONS

Indoor unit	FDFL		71KXZE3-W	-	-	-	-	71KXE6F	-	-	-	-			
	FDFU		-	28KXZE3-W	45KXZE3-W	56KXZE3-W	71KXZE3-W	-	28KXE6F	45KXE6F	56KXE6F	71KXE6F			
Power source		1 Phase 220-240V, 50Hz													
Nominal capacity	Cooling	kW	7.1	2.8	4.5	5.6	7.1	7.1	2.8	4.5	5.6	7.1			
	Heating		8.0	3.2	5.0	6.3	8.0	8.0	3.2	5.0	6.3	8.0			
Power consumption	Cooling	W	90-100												
	Heating														
Sound power level ¹ (Hi)	Cooling	dB(A)	61	60			61	62	58	60					
	Heating														
Sound pressure level ¹ (Hi/Me/Lo)	Cooling	dB(A)	45/43/40	44/43/42	42/41/38	45/43/40	43/41/40	41/38/36	43/41/40						
	Heating		46/44/40			46/44/40									
Exterior dimensions (H × W × D)		mm	630 × 1481 × 225	630 × 1087 × 225			630 × 1372 × 225	630 × 1481 × 225	630 × 1087 × 225			630 × 1372 × 225			
Net weight		kg	46	27	29	35	46	27	29	35					
Air flow (Hi/Me/Lo)	Cooling	m ³ /min	18/15/12	12/11/10	14/12/10	18/15/12	18/15/12	12/11/10	14/12/10	18/15/12					
	Heating		46/44/40	44/43/42	42/41/38	46/44/40	43/41/40	41/38/36	46/44/40						
Outside air intake		Not possible													
Refrigerant piping size (Flare)	Liquid	mm (in)	ø9.52(3/8")	ø6.35(1/4")			ø9.52(3/8")	ø9.52(3/8")	ø6.35(1/4")			ø9.52(3/8")			
	Gas		ø15.88(5/8")	ø9.52(3/8")	ø12.7(1/2")	ø15.88(5/8")		ø15.88(5/8")	ø9.52(3/8")	ø12.7(1/2")	ø15.88(5/8")				
Air filter, Q'ty		Polypropylene net × 1 (Washable)													

1. The data are measured under the following conditions(ISO-T1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

2. Sound pressure level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

Outdoor Air Processing unit FDU-F



FDU650-2400F

Remote control (Option)

Wired



RC-EX3D

RC-E5

RC-ES1


Wireless



RCN-KIT4-E2

Create a fresher environment with the Outdoor Air Processing feature


Connect your KXZ system to an Outdoor Air Processing unit with one streamlined system. This advanced technology allows you to enjoy a fresh and comfortable air supply.



Motion Sensor

(Option)


Built into the ceiling or wall plane, our motion sensor smart technology improves energy saving performance and overall room comfort.



Compact design

Compact design at just 280(650, 1100), 379(1800, 2400)mm in height, high static pressure of 200Pa and the industry's lowest noise level can meet various kind of installation locations for offices, refresh rooms, restrooms and kitchens of restaurants etc.

- (1) This unit is the specific unit for processing the outdoor air temperature closer to the room temperature. For conditioning the room temperature a dedicated air-conditioner is required additionally.
- (2) This unit monitors the outdoor air temperature and controls the thermostat's ON/OFF at the setting temperature by the remote controller, which indicates the outdoor air temperature for controlling the thermostat's ON/OFF. When the thermostat is turned OFF, the operation is changed to the fan mode so that unprocessed outdoor air will be blown into the room directly. Therefore place the air outlet port or orient the air outlet direction not to blow air directly to persons in the room, especially in small room such as a restroom and/or sanitary hot water supplying room.
- (3) It is strictly prohibited to monitor the room temperature by switching to the thermistor at the remote controller side and/or the optional remote thermistor. Otherwise dew formation at air outlet port and/or dew dripping may occur during cooling operation due to the lower outdoor air temperature. Therefore keep the remote controller of this unit in place closer to the administrator so as not to be touched freely by the end user.
- (4) Dehumidifying operation with this unit is prohibited.
- (5) When handing over this unit to the end user, make sure to explain sufficiently about the foregoing cautions, the installation place and usage of remote control for this unit and the location of the air outlet.




Connectivity with Outdoor units

FDU-F series are connectable to 8–60HP KXZ2 outdoor units, can not be connected to Micro model (4–6HP), KXZ Lite.


Combination with Outdoor units

	case	Combination
A	Only OA processing units are connected with outdoor units.	The total capacity of FDU-F is 50–100% of outdoor capacity and max quantity of FDU-F is 2 units.
B	Both of OA processing units and dedicated air-conditioner are connected with outdoor units.	The total capacity of FDU-F and dedicated air-conditioners is 50–100% of outdoor capacity and max quantity of FDU-F should be below 30% of outdoor unit capacity.



Concept (Difference between FDU-F and SAF)

SAF is the energy recovery ventilation unit which can recover heat energy from exhaust air to supply air and "has no air processing function, but FDU-F is an air processing unit which can treat the supply air closer to room temperature by cooling or heating in connection with KXZ refrigerant system and exhaust air is discharged to outside of the room.



■ SPECIFICATIONS

Indoor unit	FDU		650FKXZE1	1100FKXZE1	1800FKXZE1	2400FKXZE1
Power source						
Nominal capacity	Cooling kW		9.0	14.0	22.4	28.0
	Heating		6.5	10.5	16.0	21.5
Power consumption	Cooling W		240-250	350-360	1160-1200	
Sound power level ¹ (Hi)	Cooling dB(A)		55	62	68	70
	Heating					
Sound pressure level ¹ (Hi)	Cooling dB(A)		31	37	42	45
	Heating					
Exterior dimensions (H × W × D)	mm	280 × 950 × 635		280 × 1368 × 740	379 × 1600 × 893	
Net weight	kg	34		54	89	
Air flow (Hi)	Cooling m ³ /min		11	18	30	40
Static pressure	Pa	200(at Hi Air flow) Possible				
Outside air intake						
Refrigerant piping size	Liquid mm Gas (in)	ø9.52(3/8") (Flare) ø15.88(5/8") (Flare)		ø19.05(3/4") (Brazing)	ø22.22(7/8") (Brazing)	
Air filter	Procure locally					

1. The data are measured at 33°CDB 28°CWB (68%RH) during cooling and 0°CDB-2.9°CWB (50%RH) during heating (no frost).
2. Temperature range of outdoor air must be 20–40°CDB (32°CWB) during cooling and 0–24°CDB during heating.
3. Sound level indicates the value in an anechoic chamber. During operation these value are somewhat higher due to ambient conditions.
4. The factory E.S.P. setting is set within the range of 10 - 120Pa. If SW8-4 is turned to "ON", E.S.P. setting range can be changed to 10 - 200 Pa. (with RC-EX3D and RC-E5 only)

Hydro Module unit HMU



Remote control (Option)

Wired




RC-EX3H

What is the hydro module unit? (Hydro module unit : HMU)

This unit is an auxiliary device for use with the VRF type multi systems to control water temperatures.

It employs the plate heat exchanger in place of fin heat exchanger, and produces cold or hot water by exchanging heat between refrigerant and water.

Since it can produce hot or cold water using the VRF type multi systems as the heat source, it allows to configure a chiller system in a simple way on the one hand. On the other, it can expand the range of applications of air-conditioner because it can be used mixed with the multiple indoor unit for building.



Target outlet water temperature constant control

- This is achieved by controlling compressor frequency and control of EEVs.
- Controlling the capacity of HMUs in accordance with the load.
- The HMU is designed to achieve a hot water temperature of 55°C.

Mixed operation

- Mixed operation is possible in the air to air indoor unit and HMU.
- During the operation only of HMU, it can accommodate a wide range of outlet water temperature controlled by a dedicated control.
- When the system is in mixed operation, the HMU or air-conditioner can be set as priority.

Antifreeze control

- Anti-freeze protection of plate heat exchanger is enabled during defrost operation.

External equipment linked

- External output of interlocking signal to an external heat source for the secondary heating.
- Possible target setting temperature change from the external input. (3 points)
- Water pump control (ON / OFF) possible.

*HMU is designed for closed loop heat exchange applications. Connections to any other open loop systems (such as domestic water) should be handled via a secondary heat exchanger.

Application example

Heating system using HMU and air-conditioner propose various solutions.



■ SPECIFICATIONS

Indoor unit	HMU		140KXZE1	280KXZE1
Power source			1 Phase 220-240V, 50Hz	
Deviation, incoming supply	%		± 10%(Min.85% at starting)	
Maximum capacity	Cooling	kW	14	28
	Heating			
Power consumption (Rated/Max.)	Cooling	W	220/360	316/360
	Heating			
Current (Rated/Max.)	Cooling	A	1.00-0.92/1.54	1.44-1.32/1.54
	Heating			
Outdoor temperature	Cooling	°C	15-46	
	Heating		-20-32(Mixed Use ^{*1} : -20-20)	
Indoor temperature	°C		0-32(Without freezing)	
Indoor relative humidity	%		≤ 90	
Inlet water temperature	Cooling	°C	12-30(Mixed Use ^{*1} : 19-24)	
	Heating ^{*2}		20-50(Mixed Use ^{*1} : 20-35)	
	Heating ^{*3}		25-50(Mixed Use ^{*1} : 25-35)	
Outlet water temperature	Cooling	°C	7-25(Mixed Use ^{*1} : 14-19)	
	Heating ^{*2}		25-55(Mixed Use ^{*1} : 25-40)	
	Heating ^{*3}		30-55(Mixed Use ^{*1} : 30-40)	
Water flow (Rated/Min.-Max.)	L/min		40/20-40	80/24-80
External water pressure @Rated flow	kPa		98	80
Allowable operating pressure (water)	kPa		30-600	
Minimum suction head at 50°C	kPa		30	
Inlet water pressure	kPa		30-600	
			48	
Sound power level	Cooling ^{*4, 6}	dB(A)	46	49
	Heating ^{*5, 6}			
Sound pressure level	Cooling ^{*4}	dB(A)	32	
	Heating ^{*5}		27	31
Exterior dimensions (HxWxD)	mm		860(110 ^{*7}) x 550 x 400	
Weight (without water)	kg		46	48
Weight (Including water)	kg		47.8	50.6
Minimum amount of water in the water circuit	L		150	230
Set pressure of safety valve	kPa		600	
Water pipe connection			R1-1/2	
Refrigerant piping size	Liquid mm Gas (in)		ø15.88(5/8") (Flare)	ø22.22(7/8") ^{*8} (Brazing)

*1 Mixed use means HMU and air to air indoor unit mixed operation. *2 In case outdoor temperature more than 0°C.(0°C < Outdoor air temperature) *3 In case outdoor air temperature is 0°C or less. (Outdoor temperature ≤ 0°C) *4 Sound test condition for cooling: Cooling condition 1. *5 Sound test condition for heating: Heating condition 3. *6 MIC position: 1m from the center of the HMU.

*7 Outside piping length. *8 Accessory pipe needs to be connected for gas pipe on site.

■ Performance data

Indoor unit			HMU280KXZE1	
Outdoor unit			FDC280KXZE2	
Heating nominal capacity	condition 1	kW	23.00	
	condition 2		23.15	
	condition 3		25.20	
Heating power consumption	condition 1	kW	8.40	
	condition 2		6.90	
	condition 3		6.00	
COP	condition 1	-	2.74	
	condition 2		3.36	
	condition 3		4.20	
ηsh	condition 3 base		151	
Cooling nominal capacity	condition 1	kW	25.80	
	condition 2		18.80	
Cooling power consumption	condition 1	kW	6.35	
	condition 2		6.25	
	condition 3		4.06	
EER	condition 1	-	3.01	
	condition 2			

Note: Heating condition 1: Inlet/outlet water temp. 47°C/55°C, Outdoor temp. 7°CWB/6°CDB. Heating condition 2: Inlet/outlet water temp. 40°C/45°C, Outdoor temp. 7°CWB/6°CDB.

Heating condition 3: Inlet/outlet water temp. 30°C/35°C, Outdoor temp. 7°CWB/6°CDB.

Cooling condition 1: Inlet/outlet water temp. 23°C/18°C, Outdoor temp. 35°CWB/-. Cooling condition 2: Inlet/outlet water temp. 12°C/7°C, Outdoor temp. 35°CWB/-.

Ventilation


Fresh Air Ventilation and Heat Exchange unit SAF-E7



Energy Performance of Building Directive - EPBD

The EPBD function limits electrical/gas power to provide heating or cooling to commercial buildings. To use this function, the building designer needs to select energy efficient heating/cooling equipment and to minimise energy losses through ventilation systems.

SAF smart technology recovers heat energy in the atmosphere which would have otherwise been lost. It then uses this energy to warm air entering the building. The reverse happens in warmer climates where the exhausted cool air is used to partially cool the incoming air.



■ SPECIFICATIONS

Indoor unit		SAF		150E7	250E7	350E7	500E7	800E7	1000E7			
Power source		1 Phase 220-240V, 50Hz										
Exterior dimensions (HxWxD)		mm	270x970x467	270x882x599	317x1050x804	317x1090x904	388x1322x884	388x1322x1134				
Exterior appearance		Galvanized steel sheet										
Power input		W	92-107	108-123	178-185	204-225	360-378	416-432				
Running current		A	0.42-0.45	0.49-0.51	0.81-0.77	0.93-0.94	1.64-1.58	1.89-1.80				
Capacity	UHi	Enthalpy exchange efficiency	Cooling	%	63	66	62	65				
			Heating		70	69	67	71				
		75										
		Enthalpy exchange efficiency	Cooling	%	63	66	62	65				
			Heating		70	69	67	71				
	Hi	75										
		Enthalpy exchange efficiency	Cooling	%	63	66	62	65				
			Heating		70	69	67	71				
	Lo	75										
		Enthalpy exchange efficiency	Cooling	%	66	65	71	68	70			
			Heating		73	72	73	74	76			
Motor & Q'ty		W	10 x 2	20 x 2		40 x 2	70 x 2	180 x 2	180 x 2			
Air handling equipment Fan type & Q'ty		Sirocco fan x 2										
Air flow (UHi/Hi/Lo)		m ³ /h	150/150/120	250/250/190		350/350/240	500/500/440	800/800/630	1000/1000/700			
External static pressure (UHi/Hi/Lo)		Pa	80/70/25	105/95/45		140/60/45	120/60/35	140/110/55	105/80/75			
Net weight		kg	25	29		49	57	71	83			
Air filter	Supply air								Protection for element (Washable) PS400			
	Exhaust air											

Helping you to reduce energy consumption and carbon emissions by capturing waste energy. EFBD also allows for smaller sized units as less heating/cooling requirements are needed!



Switch box (Option)




Remote control

The following functions are newly available.

- ON/OFF Timer – The hour and minute of timer on/off can be set.
- Filter Sign – Announces the due time for cleaning the air filter.

Principle of Operation



Fresh Air DX Assembly

SAF-DX



Drain up kit (Option)
DXA-DU-E
(Built-in type)

Remote control (Option)

Wired




RC-E5

Wireless



RCN-KIT4-E2

- SAF-DX is a heating or cooling coil incorporating KXZ series controls. It can be used in combination with our total heat exchanger. (SAF series)
- Combination of SAF-DX with other indoor units is possible. The capacity code index of each model is shown below and must be used when making the system selection. Total capacity code index must be within 100% of outdoor unit capacity code index.
- Remote control option is the same as other indoor units (see above). Connection to all Superlink controls is also possible.
- Optional condensate lift mechanism is also available (600mm height).
- Return air temp. control or supply air temp. control can be selected.



SAF-DX can provide heating or cooling to the fresh air supplied through a 3rd party air handling unit or total heat exchanger such as our SAF series.

■ SPECIFICATIONS

Indoor unit	SAF-DX		250E6	350E6	500E6	800E6	1000E6
Power source			1 Phase 220-240V, 50Hz				
Nominal capacity	Cooling	kW	2.0	2.8	3.6	5.6	6.3
	Heating		1.8	2.2	2.8	4.5	5.6
Capacity code	22		28	36	56	71	
Power consumption	Cooling	W			7.2-7.2		
	Heating						
Running current	Cooling	A			0.05-0.05		
	Heating						
External dimensions (H x W x D)	mm	315 x 452 x 422		315 x 537 x 422	315 x 682 x 422	315 x 822 x 422	
Net weight	kg	12.3		13.6	16.1	18.4	
Air flow (Standard)	m ³ /h	250	350	500	800	1000	
Internal resistance	Pa	38			66		
Refrigerant piping size (Flare)	Liquid	mm (in)	ø6.35(1/4")		ø9.52(3/8")		
	Gas		ø9.52(3/8")		ø12.7(1/2")		ø15.88(5/8")

(1)The data are measured at the following conditions.



Item	Return/fresh air temperature		Outdoor air temperature		Standard
Operation	DB	WB	DB	WB	
Cooling*1	27°C	19°C	35°C	24°C	ISO-T1
	20°C		7°C	6°C	

(2)The air-conditioner is manufactured and tested in conformity with ISO-T1 "UNITARY AIR-CONDITIONERS".

Electronic Expansion Valve Kit

EEV-KIT

- EEV-KIT is the control kit for operating the locally provided AHU or FCU with direct expansion heat exchanger coils in connection with the KXZ system.
- (AHU : Air Handling Unit, FCU : Fan Coil Unit)
- EEV-KIT is composed of one EEV-Control ASSY and one EEV-Set.



Features

EEV-Control Assy has 2 types.

Refrigeration system	EEV-Control Assy	
	EEVKIT6-E-M	EEVKIT6-E-C
Single		1 box-Many boxes
Multiple	1 box (for master)	Many boxes(for slave)

EEV-Set Select from following 3 types according to the coil capacity.


Type	EEV6-71-E	EEV6-160-E	EEV6-280-E
Capacity	22-71	90-160	224-280

Single refrigerant system

- Single refrigeration system is the one that can have multiple outdoor units on one refrigerant pipe work circuit.
- There are 2 types of EEV-KIT systems that can be built into the single refrigeration system.
- System A : one EEV-KIT.
- System B : multiple EEV-KIT's.

System A

- This system has only one set of EEV-KIT built into one indoor unit with only one heat exchanger. This system can be applied to an indoor unit whose capacity is up to 10HP.




System configuration

- Single refrigeration system EEVKIT6-E-C ... Possible with multiple refrigeration systems
- Multiple refrigeration system EEVKIT6-E-M (1) + EEVKIT6-E-C ... Possible with multiple refrigeration systems (Max32)
- EEVKIT6-E-C is common for both single and multiple refrigeration systems


System B

- System B is a system that has multiple EEV-KIT's built into one indoor unit with multiple heat exchangers on one refrigerant circuit.
- This system can be applied up to 60HP (for KXZ AHU capacity).



Multiple refrigerant system

Multiple refrigeration system is an AHU system with multiple independent refrigerant circuits and one master control to control the whole system.




Advantages

- Large systems are possible [max capacity 896kW]
- External control
- Capacity step control
- Can connect to 32 units


Additional parts over a single refrigeration system

- One master control
- The slave EEV control and EEV set are the same as a single refrigeration system.




Connection to SUPERLINK-II

Single refrigeration system



Multiple refrigeration system



Control Systems

Individual control

Remote Control line up

Wired	Indoor unit	Remote control	Wireless	Indoor unit	Remote control	Indoor unit	Remote control	Indoor unit	Remote control
	All models	RC-EX3D		FDT	RCN-T-5BW(-5BB)-E2	FDTs	RCN-TS-E2	FDE	RCN-E-E3
		RC-E5		FDTc	RCN-TC-5AW-E3	FDK22-56	RCN-K-E2	FDFW	RCN-FW-E2
		RC-ES1		FDTw	RCN-TW-E2	FDK71	RCN-K71-E2	Others*	RCN-KIT4-E2

*FDTQ, FDU, FDUM, FDUT, FDUH, FDU-F

Wired remote control



(Option)

RC-EX3D H120 × W120 × D19 mm


Intuitive touch controller with Liquid Crystal Display

User friendly

- LCD panel with light tap operation introduced as the industry's first
- Simple interface with only three buttons




The desired operation mode can be selected by simply tapping this button.



Easy view

- Big LCD with 3.8 inch full dot display
- Back light function
- Multi language display (9 languages)



You can select the temperature as desired by tapping **▲** **▼** button.

High power operation

The highest capacity operation (Max 15 minutes)

- Increasing compressor speed
- Increasing air flow volume

Energy-saving operation

- Changes set temperature.
- At 28°C in cooling mode and 22°C in heating mode, 25°C in auto mode.
- Operation correction by outdoor temperature

Main functions

	Function name	Description
Economy & Timer	Energy-saving operation	Since the capacity is controlled automatically based on the outdoor temperature, energy can be saved without losing comfort.
	Sleep timer	Set the time period from start to stop of operation. The selectable range of setting time is from 30 to 240 minutes (at 10-minute intervals).
	Set temperature auto return	The temperature automatically returns to the previously set temperature.
	Set ON timer by hour	When the set time elapses, the air-conditioner starts.
	Set OFF timer by hour	When the set time elapses, the air-conditioner stops.
	Set ON timer by clock	The air-conditioner starts at the set time.
	Set OFF timer by clock	The air-conditioner stops at the set time.
	Weekly timer	On or Off timer can be set on a weekly basis.
	Peak-cut timer	Capacity control can be set by using peak cut function on RC-EX3D for better energy saving. Five-step capacity control is available.
Comfort	Home leave operation	When the unit is not used for a long period of time, the room temperature is maintained at a moderate level, avoiding extremely hot or cool temperatures.
	Big LCD & Touch screen panel	Large 3.8 inch screen has resulted in improved visibility and operability.
	Easy modification of individual flap control	User can visually confirm and set the direction of flaps using the visual display on the remote controller.
	Automatic fan speed *1	The micro-computer automatically adjusts the air flow effectively to follow the changes of return air temperature.
	Temp increment setting	Temperature increment for the change of the set temp can be changed.
Convenience	Silent mode	Set the period of time to operate the Outdoor unit with prioritizing the quietness.
	Function switch	The function switch allows user to select and set two functions among available functions.
	Favourite setting	Operation mode, set temperature, fan speed and air flow direction automatically adjust to the programmed favourite setting.
	Adjusting Brightness of the background light	The brightness of the background light can be adjusted by 10 stages.
	LCD contrast setting	This function allows user to adjust LCD display contrast.
	High power operation	High Power Mode increases the unit operating ability for 15 minutes to quickly adjust the room temperature to a comfortable level.
	Back light setting	This convenient function allows user to see controls under low light conditions.
	Administrator settings	This function only allows specific individuals to operate the unit.
Service	Setting temp range	Limited range of setting temperature in the heating or the cooling operation can be selected.
	External Input/Output Function	The external input/output of indoor unit by remote controller can set input/output based on user needs.
	Select the language	Set the language to be displayed on the remote control.
	USB connection (mini-B)	This function allows batch input of schedule timer settings and other settings involving a large amount of data.
	Error code display	This function allows user to check information displayed when abnormal function of the unit occurs.
	Operation data display	Displays various types of air-conditioner operation data in real time.
Contact company display	Contact company display	Address of the service contact is displayed.
	Filter sign	Announces the due time for cleaning of the air filter.
	Static pressure adjustment	Allows user to adjust duct static pressure using the remote control.
	Backup Control	Allows for rotation control, fault backup control, and capacity backup control.

*1 Cannot be used when a centralized control remote is connected.

Wireless remote control

(Option)

For wireless control simply insert the infra-red receiver kit on a corner of the panel

RCN-T-5BW-E2
RCN-T-5BB-E2

RCN-TC-5AW-E3

RCN-TW-E2



RCN-TS-E2

RCN-K-E2,
RCN-K71-E2

RCN-E-E3



RCN-FW-E2

RCN-KIT4-E2



*The wireless remote control is not applicable to the individual flap control system.

Wired remote control

(Option)

RC-E5 H120 x W120 x D19 mm



The RC-E5 controller enables extensive access to service and maintenance technical data combined with easy to use functions and a clear LCD display.

Weekly timer function as standard

RC-E5 provides (as a standard feature) a weekly timer, which allows one-week operation schedules to be registered. A user can specify up to four times a day to start/stop the air-conditioner. (Temperature setting is also possible with the timer).

Design remote control

(Option)

RC-ES1 (wired) New

H86 x W86 x D17 mm

- Simple and sophisticated design
- Compact size (86 x 86 mm)
- Remote control with Bluetooth® wireless technology



Wireless connection



reddot winner 2025



Remote control with Bluetooth® wireless technology.

Easy set-up of indoor units.

Notifications of abnormal conditions or operational data from the remote control will be sent to your smartphone.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by MITSUBISHI HEAVY INDUSTRIES THERMAL SYSTEMS, LTD. is under license.

Thermistor

(Option)

Run hour meters to facilitate maintenance checking

RC-E5 stores operation data when an anomaly occurs and indicates the error on the LCD. It also displays cumulative operation hours of the air-conditioner and compressor since commissioning.

Room temperature controlled by the remote control sensor

The temperature sensor is housed in the top section of the remote control unit. This arrangement has improved the sensitivity of the remote control unit's sensor, which permits more finely controlled air-conditioning.



Changeable set temperature ranges

RC-E5 allows the upper and lower limits of a set temperature range to be specified separately.

By adjusting a set temperature range, you can ensure energy saving air-conditioning by avoiding excessive cooling or heating.

SC-THB-E3

(Option)


In case the sensor integrated in the indoor unit or in the remote controller is unable to sense the room temperature correctly, or an individual controller in each room is not required but a temperature sensor is (as when a central control system is in place), install SC-THB-E3 in an adequate location in the room.



Controls network overview

Our company offers simplicity in installation with the highly sophisticated SUPERLINK-II Control System

This offers building owners and occupiers a comprehensive control and management system while providing complete commissioning and service maintenance assistance for installers and service engineers. The SUPERLINK-II is an advanced high speed data transmission system which can connect up to 128 indoor units and 32 outdoor units onto one network. A wide range of control options are available for the SUPERLINK-II network to suit any application large or small, as well as connection to a new or existing Building Management System (BMS).



Central Control

SC-SL1N-E

Start/stop control of up to 16 indoor units either individually or collectively.
Simple centralised control.


1. The SC-SL1N-E is connected to the Superlink- II network via 2-core, non-polar wires ('AB' connection).
2. It will monitor and control the start/stop function of up to 16 units, with the sixteen operation button.
3. The unit or group numbers in operation or in need of service are displayed with an LED.
4. Collective start/stop is also available through the simultaneous on/off button.
5. Up to 12 SC-SL1N-E units can be connected to a Superlink-II network (consisting of up to 128 indoor units).
6. If a power failure occurs, the SC-SL1N-E will resume the operation of the system according to a stored operation condition, once power is restored.




SC-SL2NA-E

Central control of up to 64 indoor units including weekly timer function as standard.

1. The SC-SL2NA-E is connected to the Superlink- II network via 2-core, non-polar wires ('AB' connection).
2. It will monitor and control the start/stop function of up to 16 units, or 16 groups of units, with the sixteen operation buttons.
3. It also monitors and controls the following functions for individual units, groups of units or the complete network: operation mode, set point temperature, return air temperature, louvre position, error code. Air flow and center lock function.
4. The unit or group numbers in operation or in need of service are displayed with an LCD.
5. Collective start/stop is also available through the simultaneous on/off button.
6. If a power failure occurs, the SC-SL2NA-E will resume the operation of the system according to a stored operation condition, once power is restored.
7. The SC-SL2NA-E can be connected to an external timer to facilitate timed on/off cycles.



Example of control by a central control SC-SL2NA-E




An SC-SL2NA-E performs the start/stop control, monitoring and mode setting of up to 64 units. It is a high quality air-conditioner control system that allows up to 64 indoor units to be freely grouped into 1 to 16 groups.

It allows not only the start/stop control but also the monitoring, display of operation statuses such as in operation or in need of service and mode setting such as switching of operation modes of connected units collectively, by group or individually.

- Outer dimensions: H120 x W215 x D25+35*mm.
- 35* is the measurement including the part contained in a recess.

SC-GIFN-E Interface kit

- Applicable products
Ventilation fan, Air purifier
- By using SC-GIFN-E together with central control such as SC-SL1N-E, SC-SL2NA-E and SC-SL4-AE3,-BE3, you can start-stop, operate & monitor the operation of applicable products.




Note:Please consult dealer for combination of center controls and Building Management Systems interface units.

SC-SL4-AE3,-BE3

Mitsubishi Heavy Industries Thermal Systems introduces the full colour touch screen central control SC-SL4-AE3,-BE3, with 9 inch interactive LCD display. Offers control, monitoring, scheduling and service/maintenance functions for up to 128 indoor units. Control with PC is available by use of Microsoft Edge/Google chrome.


Indoor units can be controlled, scheduled, monitored and either individually, as groups or as blocks of groups with the following functions:

Control	Monitoring	Scheduling	Administration/Service
Run/Stop / Home leave	Operating state	Yearly schedule	Block definition, Floor layout
Mode (cool/heat/fan/dry/Auto)	Mode	Today's schedule	Group definition
Set temperature	Set temperature	Detailed daily schedule	Unit definition
Operation permitted/prohibited	Room temperature	Season setting	Time and date setting
Fan speeds	Operation permitted/prohibited		Alarm history
Air direction	Fan speed		Energy consumption calculation period
Filter sign reset	Air direction		Energy consumption, cumulative operation time
Demand control (3 steps)	Filter sign		Flap control setting
Emergency stop	Maintenance (1, 2 or back-up) Outdoor air temperature		Operation data monitoring
			Data logging (Run / Stop set temperature, room temperature, outdoor air temperature)



System diagram

Indoor unit 128 units



PC requirements: Windows 10, Windows 11
Monitor resolution 1280 x 1024 or higher.
Web browser requirements: Microsoft Edge, Google Chrome

Schedule setting

For each group

Schedule settings for each group are possible. The RUN/STOP/HOME LEAVE time, operation mode, remote control Lock/Unlock setting, temperature setting, energy setting, and silent mode can be set up to 16 times per day.



Yearly Schedule

Schedule settings for a year are also possible. The weekday, holiday, special day 1 or special day 2 can be selected and set. Able to automatically update the yearly schedule.



Alarm history

A maximum of 300 records is displayed for the history of error occurrence and restoration in the unit of air-conditioner. It is possible to output the history data to a CSV data file.

Maintenance code


Able to show the maintenance code

Improved visibility

Compared to the old model the visible angle of the LCD has expanded and the visibility has improved.

High visibility


Increase in size from 7 to 9 inches



Contrast between five colours for icon display and black light base screen has achieved high visibility.

Operation time history

Possible to check operation time history for cooling and heating separately.




Models that can be connected has increased

Can now connect to Q-ton/ HMU. Can have easy centralized control over various modes



*When connecting to Q-ton, an interface(RCI-MDQE2) is necessary.

Block layout function



Web function

You can monitor and control up to 128 indoor units (Max.128 groups) from a PC or tablet PC.




<Example>
Monitoring and operating air-conditioners in a lecture room of a university



New demand control function


With the new demand control, temperature shifts between 1-9°C (Cooling or Drying ; Heating: -1~-9°C), fan mode can be selected.



Electric power calculation function:

(for SC-SL4-BE3 only)

SC-SL4-BE3 gives electric power consumption data (kWh) for each indoor unit, each group, each SUPERLINK-II system, and each watt-hour meter input.



SC-SL4-BE3	
Export data by	USB / LAN
Calculation software	Included
Watt-hour meter pulse input (Maximum)	8
Max connectable indoor units	128

Item	Model	SC-SL4-AE3/SC-SL4-BE3
Ambient temperature during use	0 ~ 40°C	
Power supply	1 Phase 100-240V 50/60Hz	
Power consumption	9W	
External dimensions (Height x Width x Depth)	172mm x 260mm x 23 (+70) mm	
Net weight	2.0kg	
Number of connectable units (indoor units)	up to 128 units	
LCD touch panel	Colour LCD, 9 inches wide	
Inputs	SL (Superlink) signal inputs	1 system (Superlink-II)
	Watt-hour meter pulse input*	8-point, pulse width 80ms or more
	Emergency stop signal input*	1 point, non-voltage a contact input continuous input (closed, forced stop)
	Demand signal input*	2 point, non-voltage a contact input continuous input (closed, demand control)
Outputs	Operation output	1 point, maximum rated current 40mA, DC24 V All units stop; Open, any unit operating; Close
	Error output	1 point maximum rated current 40mA, DC24 V Normal; closed. If even one unit is abnormal; Open (Open/closed can be changed)

* The receiving side power supply is DC 12V (10mA).


The air-conditioning charges calculations of this unit are not based on OIML, the international standard.

IoT Remote monitoring system




RM-CGW-E2 (H140 × W260 × D93mm)

The M-Access Cloud system is a remote monitoring solution for air-conditioning, leveraging IoT technology. The system supports the operation and management from both the software and hardware. The system could also be connected to products such as Q-ton / Hyozan / Hydrolution PRO.



Monitor and control units in various locations



From PC and tablets

Could monitor the conditions of the air-conditioning units in remote locations in real time.




The photos of the devices are an image

The M-Access is a subscription-based service

The M-Access is a subscription-based service with an annual fee applicable only to specific areas. For details on pricing and payment methods, please consult your local installer.


If the service is available in your area, the annual fee can be paid directly through the M-Access portal screen.



Energy Saving Control Function


Energy saving control function automatically controls air-conditioners to save energy based on the user's building profiles and power consumption target. Operation is automatically adjusted while maintaining comfort and taking into account weather conditions and past operations learnt by M-ACCESS's AI program.

Energy saving control setting



AI Demand Forecast


Predicts energy consumption based on operational data and weather forecasts



Logic Control Function

Logic control function allows the user to preset actions that will be executed on targeted units and based on ambient or room temperatures.

With the logic function, the air-conditioners automatically operate according to preset conditions set by the user.



Demand Control Function


The demand control function is a feature that controls the operation of air-conditioning units based on external input signals from a demand controller connected to the gateway. By connecting the gateway to the demand controller, the electricity demand of the indoor and outdoor units* can be managed.

* The function currently is only available for the KXZ3 series

Demand control




Demand control dialog (Indoor unit)




Various Scheduling Function

The M-access has various schedule function making central management of air-conditioners easier. The yearly calendar function provides wide flexibility to set up different operational schedules for weekday, holiday, and other specific occasions. Yearly calendar will be automatically updated according to your standard calendar settings.

Yearly calendar




Schedule template



Error Notifications


1. When detecting malfunction an alert is sent to the user by E-mail.
2. Could register multiple users as the sending address.
3. Could auto send the E-mail to the maintenance company.
4. For systems equipped with R32 safety devices, when a refrigerant leak is detected, an error notification is sent, and an alert is displayed on the screen to inform the user.




History & Export Data Worth 10 years

From the Operation data history Screen 10 years worth of operation data history for all unit on the site could be downloaded. Other information including the error / caution code and service history for all unit on the site could be referred.

Error history



Operation data history



Building Management Systems

Our company offers a wide range of control options for the KXZ system to suit any application, large or small, as well as connection to a new or existing BMS.





SC-WBGW256 (Web & BACnet gateway)

Production by order

SC-WBGW256 controls and monitors up to 256 cells (some cells can have two or more indoor units and total number of indoor units can be up to 256 units) centralised to a network PC using the Superlink-II web gateway. Simple installation is assured with no special software requirements, operation is via Internet Explorer. A low power embedded CPU and compact flash ROM ensure a large storage capacity with high reliability (no moving parts such as a PC fan, etc). An IP address filter function combined with three-level user authentication check also ensures security. Also, SC-WBGW256 can be used as interface devices that convert Mitsubishi Heavy Industries Superlink-II communication data to BACnet code and are controlled centrally from a building management system.





[In case of web gateway]



PC requirements: Windows7, Windows8.1, Windows10, Windows11.
Monitor resolution 1366 x 768 or higher.

Users can manage up to 1024 units by connecting the four devices!!

[In case of BACnet gateway]



INTESiS BMS Interface for Mitsubishi Heavy Industries Thermal Systems Air-Conditioners

All technical support, including specifying work, compatibility issues, product quality (repair and replacement issues), product liability issues and the required after sales service (including spare parts supply) will be provided by Intesis as it is an Intesis product.


Product sales and delivery will be conducted by Intesis as well.

For details concerning such matters please directly contact Intesis.

Integration of Mitsubishi Heavy Industries Thermal Systems VRF in your KNX installation by Superlink

Direct Connection to VRF outdoor units

The gateway is directly connected to the outdoor unit's communication bus and enables the control of all the indoor units connected to the system. This allows not only the control and monitoring of the main AC functions but the access to some internal variables of the outdoor units.



- Scan: Automatic identification of the units presents on the VRF system.
- Energy consumption signals from each indoor unit are available.
- Outdoor unit's signals available for the integration.
- Supports both BACnet/IP and BACnet MS/TP physical layers.
- Configuration through IP or USB (Console) port.
- Easy integration with Intesis MAPS.
- Automatic updates for both Intesis MAPS and interface's firmware.

AC Cloud Control



PAC Model: INWMPMHI001R000

Please access the followings for details.


IntesisTM
BY HMS NETWORKS

URL
email | <http://www.intesis.com>
info@intesis.com

Support tools

BIM (Building Information Modelling)

We can provide high quality Building Information Modelling (BIM) models in three formats:



1. Revit
2. 3D Cad
3. IFC

(IFC provides an interoperability solution between different software applications. The format establishes international standards to import and export building objects and their properties)

How and why BIM is used

BIM enables all disciplines of a project (Architects, engineers, quantity surveyors, contractors, clients etc..) to share a common model and data representing the project they are building.

- Better design visualization
- BIM reduces conflicts and changes during construction
- Increases overall accuracy of project documentation
- Improves cost estimating
- Improves energy analysis
- Simplifies reporting and scheduling



mhiae.com/BIM

e-seasonal

e-seasonal is an application for our Air-cooled VRF Outdoor unit selection.

By selecting a combination of systems, location and occupancy profiles you can simulate:

1. Annual seasonal efficiency calculation
2. Annual energy consumption, cost and CO₂ emission estimation
3. Comparison with multiple solutions including conventional heaters

It is possible to download to your PC for an offline version or using a web browser for an online version. e-seasonal provides solution suggestions according to your requested design conditions.



e-solution

Use our e-solution design software tool to find the latest specifications for our KXZ VRF systems. This software helps to simplify the processes to enable engineers to select the most suitable indoor units, outdoor units, pipework, controls & calculate any additional required refrigerants.

If you're an engineer interested in using e-solution, please register and download the e-solution via <https://mhiae.com/e-solution/> and be sure to download the latest updates when available.



Please be aware that this tool was developed to cater for the design of two and three pipe systems, and specifies the appropriate models and sizes. It also generates wiring diagrams and engineering drawing to export to AutoCAD or PDF. This flexibility allows engineers to print selected design information and technical data to present to potential clients. As well as personalising the design information into their own formats and documents for future proposals.

MHI e-service App

MHI e-service application is available & free to download to both IOS and Android devices.


The application covers "Mitsubishi Heavy Industries Thermal Systems, Ltd" Air-conditioning systems: Split (RAC & PAC), VRF, Q-ton & AtoW.

This "MHI e-service" Application enables field engineers to make:
A quick search of the meaning of error codes that may appear when there is a malfunction in a "Mitsubishi Heavy Industries Thermal Systems, Ltd" Air-conditioning system, and the probable cause for the malfunction.

Scan the unit's QR code and search the meaning of error codes depending on the model type

Additional refrigerant charge calculation for Split (PAC, RAC) & VRF

Currently available in English & Spanish languages and Italian



To download the App go to:



Android™




iPhone

Exterior dimensions



Heat pump systems


FDC224KXZE3A, FDC280KXZE3A, FDC335KXZE3A



All measurements in mm.


Mark	Content	224	280	335
A	Refrigerant gas pipe	ø19.05(Brazing)	ø22.22(Brazing)	
B	Refrigerant liquid pipe	ø9.52(Flare)	ø12.7(Flare)	
C	Refrigerant oil equalization pipe		ø12.7(Flare)	
D	Knockout hole for pipes	175 x 130 (Front), 150 x 90 (Bottom)		
F	Knockout hole for power wiring		ø50	
G	Anchor bolt hole		M10 x 4 places	
H	Drain hole		ø20 x 10 places	
J	Hole for hanging		100 x 29.5	

Installation limitations			
Dimensions	1	2	3
L₁	500	500	Open
L₂	10(50)	50	10
L₃	300	100(300)	300
L₄	10(50)	50	Open
H₁	1500	1500	Open
H₂	No limit	No limit	No limit
H₃	500	500	No limit
H₄	No limit	No limit	Open



1. This installation example assumes operation at an ambient temperature under 43°C.
2. For use at higher ambient temperatures, install according to the dimension in parentheses.
3. If H1 or H3 exceeds the wall height limit in the table, H1/2 and H3/2 should be added to the L1 and L3 respectively.


FDC400KXZE3, FDC450KXZE3, FDC500KXZE3




Mark	Content
A	Refrigerant gas pipe
B	Refrigerant liquid pipe
C	Refrigerant oil equalization pipe
D	Knockout hole for pipes
F	Knockout hole for power wiring
G	Anchor bolt hole
H	Drain hole
J	Hole for hanging

Installation limitations			
Dimensions	1	2	3
L ₁	500	500	Open
L ₂	10(50)	50	10
L ₃	300	100(300)	300
L ₄	10(50)	50	Open
H ₁	1500	1500	Open
H ₂	No limit	No limit	No limit
H ₃	500	500	No limit
H ₄	No limit	No limit	Open

1. This installation example assumes operation at an ambient temperature under 43°C.
2. For use at higher ambient temperatures, install according to the dimension in parentheses.
3. If H₁ or H₃ exceeds the wall height limit in the table, H₁/2 and H₃/2 should be added to the L₁ and L₃ respectively.




FDC530KXZE3, FDC560KXZE3, FDC615KXZE3, FDC670KXZE3



Mark	Content
A	Refrigerant gas pipe
B	Refrigerant liquid pipe
C	Refrigerant oil equalization pipe
D	Knockout hole for pipes 175 x 130 (Front), 150 x 90 (Bottom)
F	Knockout hole for power wiring ø50
G	Anchor bolt hole M10 x 6 places
H	Drain hole ø20 x 12 places
J	Hole for hanging 100 x 29.5

Installation limitations			
Dimensions	1	2	3
L ₁	500	500	Open
L ₂	10(50)	50	10
L ₃	300	100(300)	300
L ₄	10(50)	50	Open
H ₁	1500	1500	Open
H ₂	No limit	No limit	No limit
H ₃	500	500	No limit
H ₄	No limit	No limit	Open


1. This installation example assumes operation at an ambient temperature under 43°C.
2. For use at higher ambient temperatures, install according to the dimension in parentheses.
3. If H1 or H3 exceeds the wall height limit in the table, H1/2 and H3/2 should be added to the L1 and L3 respectively.



Back Dimensions of refrigerant piping connection pipe (ichnography)

All measurements in mm.


Dimensions	MODEL	280	335
AA	142.5	139.5	
AB	261	255	




Mark	Content	280	335
A	Refrigerant gas piping connection pipe	ø22.22(Brazing)	ø25.4(Brazing)
B	Refrigerant liquid piping connection pipe	ø9.52(Flare)	ø12.7(Flare)
C	Refrigerant piping exit hole	ø88(or ø100)	
D	Power supply entry hole	ø50 (right · left · front), long hole 40 x 80 (bottom)	
F	Anchor bolt hole		M10 x 4 places
G	Drain waste water hose hole		ø45 x 3 places
H	Drain hole		ø20 x 11 places
K	Refrigerant oil equalization piping connection pipe		ø9.52(Flare)
L	Carrying in or hole for hanging		230 x 60

Installation example		
Dimensions	1	2
L₁	500	Open
L₂	10(30)	10(30)
L₃	100	100
L₄	10(30)	Open
H₁	1500	Open
H₂	No limit	No limit
H₃	1000	No limit
H₄	No limit	Open


() :In case it is the promised installation location that the outdoor unit is used on conditions with the ambient temperature of 43°C or more.



When more than one unit is installed




Dimensions	1	2
L₁	500	Open
L₂	10(30)	200
L₃	100	300
L₄	10(30)	Open
L₅	10(30)	400
L₆	10(30)	400
H₁	1500	Open
H₂	No limit	No limit
H₃	1000	No limit
H₄	No limit	Open



Mark	Content	400	450, 475, 500, 560
A	Refrigerant gas piping connection pipe	ø25.4(Brazing)	ø28.58(Brazing)
B	Refrigerant liquid piping connection pipe		ø12.7(Flare)
C	Refrigerant piping exit hole		ø88(or ø100)
D	Power supply entry hole	ø50 (right · left · front), long hole 40 x 80 (bottom)	
F	Anchor bolt hole		M10 x 4 places
G	Drain waste water hose hole		ø45 x 3 places
H	Drain hole		ø20 x 11 places
K	Refrigerant oil equalization piping connection pipe		ø9.52(Flare)
L	Carrying in or hole for hanging		230 x 60


Installation example		
Dimensions	1	2
L₁	500	Open
L₂	10(30)	10(30)
L₃	100	100
L₄	10(30)	Open
H₁	1500	Open
H₂	No limit	No limit
H₃	1000	No limit
H₄	No limit	Open

() : In case it is the promised installation location that the outdoor unit is used on conditions with the ambient temperature of 43°C or more.



Installation example		
Dimensions	1	2
L₁	500	Open
L₂	10(30)	200
L₃	100	300
L₄	10(30)	Open
L₅	10(30)	400
L₆	10(30)	400
H₁	1500	Open
H₂	No limit	No limit
H₃	1000	No limit
H₄	No limit	Open


FDC224KXZRE2, FDC280KXZRE2, FDC335KXZRE2



Mark	Content	224	280	335
A	Refrigerant suction gas piping connection entrance	ø19.05(Brazing)	ø22.22(Brazing)	ø25.4(Brazing)
B	Refrigerant liquid piping connection entrance		ø9.52(Flare)	ø12.7(Flare)
C	Refrigerant discharge gas piping connection entrance	ø15.88(Brazing)		ø19.05(Brazing)
D	Power supply entry hole		ø50(right · left · front), long hole 40x80(Bottom)	
F	Anchor bolt hole		M10 x 4 places	
G	Drain waste water hose hole		ø45 x 3 places	
H	Drain hole		ø20 x 11 places	
K	Refrigerant oil equalization piping connection entrance		ø9.52(Flare)	
L	Carrying in or hole for hanging		230x60	
N	Refrigerant piping exit hole		ø88(or ø100)	

Installation example		
Dimensions	1	2
L ₁	500	Open
L ₂	10(30)	10(30)
L ₃	100	100
L ₄	10(30)	Open
H ₁	1500	Open
H ₂	No limit	No limit
H ₃	1000	No limit
H ₄	No limit	Open

() In case it is the promised installation location that the outdoor unit is used on conditions with the ambient temperature of 43°C or more.




Mark	Content	400	450	475	500	560	615	670
A	Refrigerant suction gas piping connection entrance	ø25.4 (Brazing)			ø28.58(Brazing)			
B	Refrigerant liquid piping connection entrance				ø12.7(Flare)			
C	Refrigerant discharge gas piping connection entrance			ø22.22(Brazing)			ø25.4(Brazing)	
D	Power supply entry hole			ø50(right · left · front),long hole 40x80(Bottom)				
F	Anchor bolt hole				M10 x 4 places			
G	Drain waste water hose hole				ø45 x 3 places			
H	Drain hole				ø20 x 11 places			
K	Refrigerant oil equalization piping connection pipe				ø9.52(Flare)			
L	Carrying in or hole for hanging				230x60			
N	Refrigerant piping exit hole				ø88(or ø100)			

Installation example		
Dimensions	1	2
L₁	500	Open
L₂	10(30)	10(30)
L₃	100	100
L₄	10(30)	Open
H₁	1500	Open
H₂	No limit	No limit
H₃	1000	No limit
H₄	No limit	Open


(): In case it is the promised installation location that the outdoor unit is used on conditions with the ambient temperature of 43°C or more.

FDC121KXZEN1-W, FDC140KXZEN1-W, FDC155KXZEN1-W
 FDC121KXZES1-W, FDC140KXZES1-W, FDC155KXZES1-W

All measurements in mm.



Mark	Content	
A	Service valve connection (gas side)	ø15.88 (5/8") (Flare)
B	Service valve connection (liquid side)	ø9.52 (3/8") (Flare)
C	Pipe/cable draw-out hole	
D	Drain discharge hole	ø20 x 3 places
E	Anchor bolt hole	M10 x 4 places
F	Cable draw-out hole	ø30 x 3 places



	I	II	III
L₁	Open	Open	500
L₂	300	5	Open
L₃	150	300	150
L₄	5	5	5


Minimum installation space

Notes:


- (1) It must not be surrounded by walls on the four sides.
- (2) The unit must be fixed with anchor bolts. An anchor bolt must not protrude more than 15mm.
- (3) Where the unit is subject to strong winds, lay it in such a direction that the blower outlet faces perpendicularly to the dominant wind direction.
- (4) Leave 1m or more space above the unit.
- (5) A wall in front of the blower outlet must not exceed the units height.
- (6) The model name label is attached on the lower right corner of the front panel.

FDC121KXZEN1, FDC140KXZEN1, FDC155KXZEN1
 FDC121KXZES1, FDC140KXZES1, FDC155KXZES1

All measurements in mm.



Mark	Content	
A	Service valve connection (gas side)	ø15.88 (5/8") (Flare)
B	Service valve connection (liquid side)	ø9.52 (3/8") (Flare)
C	Pipe/cable draw-out hole	
D	Drain discharge hole	ø20 x 3 places
E	Anchor bolt hole	M10 x 4 places
F	Cable draw-out hole	ø30 x 3 places




Minimum installation space

	I	II	III
L ₁	Open	Open	500
L ₂	300	5	Open
L ₃	150	300	150
L ₄	5	5	5

Notes:

- (1) It must not be surrounded by walls on the four sides.
- (2) The unit must be fixed with anchor bolts. An anchor bolt must not protrude more than 15mm.
- (3) Where the unit is subject to strong winds, lay it in such a direction that the blower outlet faces perpendicularly to the dominant wind direction.
- (4) Leave 1m or more space above the unit.
- (5) A wall in front of the blower outlet must not exceed the units height.
- (6) The model name label is attached on the lower right corner of the front panel.


FDC224KXZME1, FDC280KXZME1, FDC335KXZME1A



Mark	Content	224	280	335
A	Service valve connection of the attached connecting pipe (gas side)	ø19.05 (3/4") (Flare)	ø19.05 (3/4") (Flare)	ø19.05 (3/4") (Flare)
B	Service valve connection (liquid side)	ø9.52 (3/8") (Flare)	ø9.52 (3/8") (Flare)	ø12.7 (1/2") (Flare)
C	Pipe/cable draw-out hole	4places	4places	4places
D	Drain discharge hole	ø20 x 4places	ø20 x 4places	ø20 x 4places
E	Anchor bolt hole	M10 x 4places	M10 x 4places	M10 x 4places
F	Cable draw-out hole	ø30 x 2places (front) ø45 (side) ø30 x 2places (back)	ø30 x 2places (front) ø45 (side) ø30 x 2places (back)	ø30 x 2places (front) ø45 (side) ø30 x 2places (back)
G	Connecting position of the local pipe. (gas side)	ø19.05 (3/4") (Brazing)	ø22.22 (7/8") (Brazing)	ø25.4 (1") (Brazing)

Notes:

- (1) It must not be surrounded by walls on the four sides.
- (2) The unit must be fixed with anchor bolts. An anchor bolt must not protrude more than 15mm.
- (3) Where the unit is subject to strong winds, the blower outlet should face perpendicularly to the dominant wind direction.
- (4) Leave a 1m or more space above the unit.
- (5) A wall in front of the blower outlet must not exceed the units height.
- (6) The model name label is attached on the lower right corner of the front.
- (7) Connect the Service valve with local pipe by using the pipe of the attachment.(Gas side only)
- (8) Mark ✪ shows the connecting position of the local pipe.(Gas side only)




	I	II	III
L₁	Open	Open	1500(500) ¹
L₂	300	5	Open
L₃	300	300	300
L₄	250(5) ²	250(5) ²	250(5) ²

Notes:

- *1 Figure in () shows the value applicable when the flex flow adaptor is installed.
- *2 Under the setting condition as specified in (), it is necessary to secure 250 mm for the dimension L4 when replacing the compressor. Establish this for example by moving the unit during the work.


FDC224KXZPE1, FDC280KXZPE1



Mark	Content
A	Service valve connection of the attached connecting pipe (gas side)
B	Service valve connection (liquid side)
C	Cable draw-out hole (front · side)
D	Cable draw-out hole (front · side)
E	Cable draw-out hole (back)
F	Pipe/cable draw-out hole
G	Drain discharge hole
H	Anchor bolt hole

Notes:

- (1) It must not be surrounded by walls on the four sides.
- (2) The unit must be fixed with anchor bolts.
An anchor bolt must not protrude more than 15mm.
- (3) Where the unit is subject to strong winds, lay it in such a direction that the blower outlet faces perpendicularly to the dominant wind direction.
- (4) Leave 1m or more space above the unit.
- (5) A wall in front of the blower outlet must not exceed the unit's height.
- (6) The model name label is attached on the lower right corner of the front panel.
- (7) Connect the Service valve with local pipe by using the pipe of the attachment.
(Gas side only) (Accessory pipe is used only by FDC280KXZPE1)
- (8) Regarding attaching the pipe of accessories, refer to an attached installation manual.




	I	II	III
L₁	Open	Open	500
L₂	300	5	Open
L₃	150	300	150
L₄	250 (5)*1	250 (5)*1	250 (5)*1

Notes:

- *1 At the time of the installation at () dimension,
Secure space of 250mm in lateral (L4) by unit movement
at the time of the exchange work of the compressor.


FDC224KXZWE1, FDC280KXZWE1, FDC335KXZWE1

All measurements in mm.



Mark	Content	
A	High/low gas line	Refer to piping size
B	—	Not to use.
C	Liquid line	Refer to piping size
D	Oil equalization line	Refer to piping size
F	Water inlet	R1 1/4
G	Water outlet	R1 1/4
H	Drain outlet	Rp 1/2,2places
J	Power source intake	ø35
K	Signal wiring intake	ø35
L	Anchor bolt hole	ø18,4places

Dimension	FDC-KXZWE1	
C1	224	280
C2	142	139


Piping size

	FDC224KXZWE1	FDC280KXZWE1	FDC335KXZWE1	Connection method
High/low gas line	ø19.05	ø22.22	ø25.4	Flange
Liquid line	ø9.52	ø9.52	ø12.7	Flare
Oil equalization line	ø9.52	ø9.52	ø9.52	



Dimension	Installation example	1
L1	600 or more	
L2	20 or more	
L3	500 or more	
L4	20 or more	
L5	300 or more	

PFD refrigerant flow branch control less than 11.2kW / less than 18.0kW



PFD1124-E, PFD1804-E

All measurements in mm.

PFD1124-E



PFD1804-E




PFD refrigerant flow branch control

28.0kW or less / less than 37.1kW (less than 11.2kW x 4 branches)


PFD2804-E, PFD1124x4-E

All measurements in mm.

PFD2804-E




PFD1124X4-E



Ceiling Cassette - 4way - FDT

FDT28KXZE3-W, FDT36KXZE3-W, FDT45KXZE3-W, FDT56KXZE3-W, FDT71KXZE3-W

All measurements in mm.



Make a space of 4000 or more between the units when installing more than one.

Notes (1) The model name label is attached to the control box lid.

(2) Suspension bolt pitch P1, P2 is adjustable by a pattern of the right table.

(3) Draft prevention function (※) is provided on the panel T-PSAE-5CW-E, T-PSAE-5CB-E only.

Suspension bolt pitch range


Symbol	P1	P2
1	770	725-770
2	770-800	725

Symbol	Content		
	Model	28	36,45,56
A	Gas piping	φ9.52(3/8") (Flare)	φ12.7(1/2") (Flare)
B	Liquid piping	φ 6.35(1/4") (Flare)	φ 9.52(3/8") (Flare)
C	Drain piping	VP25 (O.D.32)	
D	Hole for wiring		
F	Suspension bolts	M10 or M8	
G	Outside air opening for ducting	(Knock out)	
H1	Air outlet opening for ducting	φ 125 (Knock out)	
H2		φ 200 (Knock out)	

Ceiling Cassette - 4way - FDT

FDT90KXZE3-W, FDT112KXZE3-W, FDT140KXZE3-W, FDT160KXZE3-W


All measurements in mm.



Ceiling Cassette - 4way - FDT

FDT28KXZE1, FDT36KXZE1, FDT45KXZE1, FDT56KXZE1, FDT71KXZE1


All measurements in mm.



Ceiling Cassette - 4way - FDT

FDT90KXZE1, FDT112KXZE1, FDT140KXZE1, FDT160KXZE1



All measurements in mm.




Ceiling Cassette - 4way Compact FDTC

FDTC15KXZE3-W, FDTC22KXZE3-W, FDTC28KXZE3-W, FDTC36KXZE3-W, FDTC45KXZE3-W, FDTC56KXZE3-W
FDTC15KXZE1, FDTC22KXZE1, FDTC28KXZE1, FDTC36KXZE1, FDTC45KXZE1, FDTC56KXZE1

All measurements in mm.



Make a space of 400 or more between the units when installing more than one.







Notes (1) The model name label is attached to the control box lid.
 (2) This unit is designed for 2x2 grid ceiling.
 If it is installed on a ceiling other than 2x2 grid ceiling,
 provide an inspection opening on the control box side.
 (3) Draft prevention function (※) is provided on the panel TC-PSAE-5AW-E,
 TC-PSAGE-5AW-E only.

Symbol	Content
	Model 15,22,28 36,45,56
A	Gas piping Ø9.52 (3/8") Ø12.7 (1/2") (Flare) (Flare)
B	Liquid piping Ø6.35 (1/4") (Flare)
C	Drain piping VP25 (O.D.32)
D1	Power source connection
D2	Remote control code and signal wiring connection
F	Suspension bolts (M10 or M8)
G	Outside air opening for ducting (Knock out)
H	Air outlet opening for ducting Ø125 (Knock out)
J	Inspection opening 450X450

Ceiling Cassette -2way-FDTW

FDTW28KXZE3-W, FDTW45KXZE3-W, FDTW56KXZE3-W, FDTW71KXZE3-W
FDTW28KXE6F, FDTW45KXE6F, FDTW56KXE6F, FDTW71KXE6F




Symbol	Content			
	Model	28	45,56	71
A	Gas piping	Φ9.52 (3/8") (Flare)	Φ12.7 (1/2") (Flare)	Φ15.88 (5/8") (Flare)
B	Liquid piping	Φ6.35 (1/4") (Flare)		Φ9.52 (3/8") (Flare)
C	Drain piping		VP25 (O.D.32)	
D	Hole for wiring			
E	Suspension bolts		M10	
F	Outside air opening for ducting			(Knock out)
G	Air outlet opening for ducting			(Knock out)





Notes (1) The model name label is attached on the lid of the control box.

Ceiling Cassette -2way- FDTW

FDTW90KXZE3-W, FDTW112KXZE3-W, FDTW140KXZE3-W
FDTW90KXE6F, FDTW112KXE6F, FDTW140KXE6F



All measurements in mm.




Make a space of 5000 or more between the units when installing more than one.

Symbol	Content	
A	Gas piping	ø15.88 (5/8") (Flare)
B	Liquid piping	ø9.52 (3/8") (Flare)
C	Drain piping	VP25 (O.D.32)
D	Hole for wiring	
E	Suspension bolts	M10
F	Outside air opening for ducting	(Knock out)
G	Air outlet opening for ducting	(Knock out)

Notes (1) The model name label is attached on the lid of the control box.

Ceiling Cassette -1way-FDTS

FDTs45KXZE3-W, FDTs71KXZE3-W
FDTs45KXE6F, FDTs71KXE6F



Symbol	Content		
	Model	45,50	71
A	Gas piping	Ø12.7 (1/2") (Flare)	Ø15.88 (5/8") (Flare)
B	Liquid piping	Ø6.35 (1/4") (Flare)	Ø9.52 (3/8") (Flare)
C	Drain piping	VP25 (I.D.25, O.D.32) Note (2)	
D	Hole for wiring		
F	Suspension bolts	(M10)	
G	Outside air opening for ducting	(Knock out)	
H	Drain piping (Gravity drainage)	VP25 (I.D.25, O.D.32)	


Notes (1) The model name label is attached inside the air return grille.
(2) This unit is designed for 2×4 grid ceiling.

Ceiling Cassette -1way Compact-FDTQ



FDTQ22KXZE3-W, FDTQ28KXZE3-W, FDTQ36KXZE3-W
FDTQ22KXE6F, FDTQ28KXE6F, FDTQ36KXE6F

All measurements in mm.

Direct blow panel (TQ-PSA-15W-E)



Decorative panel



Notes

- (1) The model name label is attached on the fan case inside the air return grille.
- (2) This unit is designed for 2X2 grid ceiling.


Symbol	Content		
	Model	22,28	36
A	Gas piping	Φ9.52 (3/8") (Flare)	Φ12.7 (1/2") (Flare)
B	Liquid piping	Φ6.35 (1/4") (Flare)	
C	Drain piping	VP25 (O.D.32)	
D	Hole for wiring	Φ30	
E	Suspension bolts	M10	
F1,2	Outside air opening for ducting (Knock out)		

Ceiling Cassette -1way Compact-FDTQ


FDTQ22KXZE3-W, FDTQ28KXZE3-W, FDTQ36KXZE3-W
FDTQ22KXE6F, FDTQ28KXE6F, FDTQ36KXE6F

All measurements in mm.

Direct blow panel (TQ-PSB-15W-E)



Decorative panel



Space for installation and service


Makro

(1) The model name label is attached on the fan case.

Symbol	Content		
	Model	22,28	36
A	Gas piping	Ø9.52 (3/8") (Flare)	Ø12.7 (1/2") (Flare)
B	Liquid piping	Ø6.35 (1/4") (Flare)	
C	Drain piping	VP25 (O.D.32)	
D	Hole for wiring	Ø30	
E	Suspension bolts	M10	
F1,2	Outside air opening for ducting	(Knock out)	


Duct Connected -High Static Pressure- FDU

FDU45KXZE3-W, FDU56KXZE3-W
FDU45KXE6F, FDU56KXE6F



Symbol	Content
A	Gas piping
B	Liquid piping
C1	Drain piping
C2	Drain piping (Gravity drainage)
D	Hole for wiring
E	Suspension bolts
F	Outside air opening for ducting
G	Air outlet opening for ducting
H	Inspection opening
	Ø12.7 (1/2") (Flare)
	Ø6.35 (1/4") (Flare)
	VP25 (O.D.32)
	VP20 (O.D.26)
	M10
	(Knock out)
	(Knock out)
	(450X450)


Space for installation and service
Select either of two cases to keep space for installation and services.
(Case 1) From side of unit



(Case 2) From bottom of unit


per
ante

2) From bottom of unit Note
||||| t (1) The model name label




Duct Connected -High Static Pressure- FDU

FDU71KXZE3-W, FDU90KXZE3-W
FDU71KXE6F, FDU90KXE6F




Space for installation and service

Select either of two cases to keep space for installation and services.
(Case 1) From side of unit




(Case 2) From bottom of unit



Symbol	Content
A	Gas piping $\phi 15.88$ (5/8") (Flare)
B	Liquid piping $\phi 9.52$ (3/8") (Flare)
C1	Drain piping VP25 (O.D.32)
C2	Drain piping (Gravity drainage) VP20 (O.D.26)
D	Hole for wiring
E	Suspension bolts M10
F	Outside air opening for ducting (Knock out)
G	Air outlet opening for ducting (Knock out)
H	Inspection opening (450X450)

Duct Connected -High Static Pressure- FDU


FDU112KXZE3-W, FDU140KXZE3-W, FDU160KXZE3-W
FDU112KXE6F, FDU140KXE6F, FDU160KXE6F



Symbol	Content	
A	Gas piping	ø15.88 (5/8") (Flare)
B	Liquid piping	ø9.52 (3/8") (Flare)
C1	Drain piping	VP25 (O.D.32)
C2	Drain piping (Gravity drainage)	VP20 (O.D.26)
D	Hole for wiring	
E	Suspension bolts	M10
F	Outside air opening for ducting	(Knock out)
G	Air outlet opening for ducting	(Knock out)
H	Inspection opening	(450X450)

Space for installation and service

Select either of two cases to keep space for installation and services.
(Case 1) From side of unit




Notes (a) There must not be obstacle to draw out 2 fan units. For fan units maintenance refer to the service manual.

(b) Install refrigerant pipes, drain pipe, and wiring so as not to cross marked area.


(c) The case that pipes are installed to upper (bottom) of fan unit, keep space of 60mm or more to upper (bottom) of unit.

Note
(1) The model name label
is attached on the lid
of the control box.




Duct Connected -High Static Pressure- FDU

FDU224KXZE3-W, FDU280KXZE3-W
FDU224KXZE1, FDU280KXZE1




Space for installation and service

Select either of two cases to keep space for installation and services.
(Case 1) From side of unit



(Case 2) From bottom of unit

Notes (1) The model name label is attached on the lid of the control box.




Symbol	Content	
	MODEL	224
A	Gas piping	$\frac{1}{2}$ 19.05 (3/4") (Brazing)
B	Liquid piping	$\frac{1}{2}$ 9.52 (3/8") (Brazing)
C	Drain piping (Gravity drainage)	VP25 (O.D.32)
D	Hole for wiring	
E	Suspension bolts	M10
F	Inspection hole	(450X450)

Duct Connected -Low/Middle Static Pressure- FDUM


FDUM22KXZE3-W, FDUM28KXZE3-W, FDUM36KXZE3-W, FDUM45KXZE3-W, FDUM56KXZE3-W
FDUM22KXE6F, FDUM28KXE6F, FDUM36KXE6F, FDUM45KXE6F, FDUM56KXE6F

All measurements in mm.




Space for installation and service

Select either of two cases to keep space for installation and services.
(Case 1) From side of unit



(Case 2) From bottom of unit




Symbol	Content
	Model 22,28 36,45,56
A	Gas piping $\phi 9.52$ (3/8") (Flare) $\phi 12.7$ (1/2") (Flare)
B	Liquid piping $\phi 6.35$ (1/4") (Flare)
C1	Drain piping VP25 (O.D.32)
C2	Drain piping (Gravity drainage) VP20 (O.D.26)
D	Hole for wiring (M10)
E	Outside air opening ($\phi 150$) (Knock out)
F	Suspension bolts for ducting
G	Air outlet opening ($\phi 125$) (Knock out)
H	Inspection hole (450X450)


Note The model name label is attached on the lid of the control box.

Duct Connected -Low/Middle Static Pressure- FDUM

FDUM71KXZE3-W, FDUM90KXZE3-W
FDUM71KXE6F, FDUM90KXE6F




Space for installation and service
Select either of two cases to keep space for installation and services.
(Case 1) From side of unit



Symbol	Content
A	Gas piping $\phi 15.88(5/8")$ (Flare)
B	Liquid piping $\phi 9.52(3/8")$ (Flare)
C1	Drain piping VP25 (O.D.32)
C2	Drain piping (Gravity drainage) VP20 (O.D.26)
D	Hole for wiring
E	Suspension bolts (M10)
F	Outside air opening for ducting ($\phi 150$)(Knock out)
G	Air outlet opening for ducting ($\phi 125$)(Knock out)
H	Inspection hole (450X450)


Note The model name label is attached on the lid of the control box.



Duct Connected -Low/Middle Static Pressure- FDUM


FDUM112KXZE3-W, FDUM140KXZE3-W, FDUM160KXZE3-W
FDUM112KXE6F, FDUM140KXE6F, FDUM160KXE6F

All measurements in mm.




Space for installation and service

Select either of two cases to keep space for installation and services.
(Case 1) From side of unit



Symbol	Content
A	Gas piping $\phi 15.88$ (5/8") (Flare)
B	Liquid piping $\phi 9.52$ (3/8") (Flare)
C1	Drain piping VP25 (O.D.32)
C2	Drain piping (Gravity drainage) VP20 (O.D.26)
D	Hole for wiring
E	Suspension bolts (M10)
F	Outside air opening for ducting ($\phi 150$) (Knock out)
G	Air outlet opening for ducting ($\phi 125$) (Knock out)
H	Inspection hole (450X450)


Note The model name label is attached on the lid of the control box.



Duct Connected (thin) -Low Static Pressure-FDUT

FDUT15KXZE3-W, FDUT22KXZE3-W, FDUT28KXZE3-W, FDUT36KXZE3-W
FDUT15KXE6F-E, FDUT22KXE6F-E, FDUT28KXE6F-E, FDUT36KXE6F-E


All measurements in mm.



Space for installation and service

Symbol	Content		
	Model	15,22,28	36
A	Gas piping	$\phi 9.52$ (3/8") (Flare)	$\phi 12.7$ (1/2") (Flare)
B	Liquid piping	$\phi 6.35$ (1/4") (Flare)	
C1	Drain piping	VP25 (O.D.32) (Used with attached connector)	
C2	Drain piping (Gravity drainage)	VP25 (O.D.32) (Used with attached connector)	
D	Hole for wiring	$\phi 25$ x 2	
E	Suspension bolts	M10	
F	Inspection opening	(450X450), (270X770)	


Note The model name label is attached on the lid of the control box.



Duct Connected (thin) -Low Static Pressure- FDUT


FDUT45KXZE3-W, FDUT56KXZE3-W
FDUT45KXE6F-E, FDUT56KXE6F-E

All measurements in mm.




Symbol	Content
	45,56
A	Gas piping $\phi 12.7$ (1/2") (Flare)
B	Liquid piping $\phi 6.35$ (1/4") (Flare)
C1	Drain piping VP25 (O.D.32) (Used with attached connector)
C2	Drain piping VP25 (O.D.32) (Gravity drainage) (Used with attached connector)
D	Hole for wiring $\phi 25 \times 2$
E	Suspension bolts M10
F	Inspection opening (450X450), (270X970)

Note: The model name label is attached on the lid of the control box.




Duct Connected (thin) -Low Static Pressure-FDUT

FDUT71KXZE3-W
FDUT71KXE6F-E



Symbol	Content
	Model 71
A	Gas piping $\phi 15.88$ (5/8") (Flare)
B	Liquid piping $\phi 9.52$ (3/8") (Flare)
C1	Drain piping VP25 (O.D.32)
C2	Drain piping (Gravity drainage) VP25 (O.D.32)
D	Hole for wiring $\phi 25 \times 2$
E	Suspension bolts M10
F	Inspection opening (450X450), (270X1170)


Note The model name label is attached on the lid of the control box.



Duct Connected (Compact & Flexible) FDUH

FDUH22KXZE3-W, FDUH28KXZE3-W, FDUH36KXZE3-W
FDUH22KXE6F, FDUH28KXE6F, FDUH36KXE6F

All measurements in mm.




Symbol	Content		
M o d e l	22,28	36	
A	Gas piping	φ9.52 (3/8") (Flare)	φ12.7 (1/2") (Flare)
B	Liquid piping	φ6.35 (1/4") (Flare)	
C ₁	Drain piping	VP20 (I.D.20, O.D.26)	Note (2)
C ₂	Drain piping	To be used instead of "C ₁ "	
D	Hole for wiring	φ30	
E	Suspension bolts	(M10)	
F	Inspection hole	(590X1150) Note (3)	

Notes

- (1) The model name label is attached on the fan case inside the air return grille.
- (2) Prepare the connecting socket (VP20) on site.
(As for drain piping, it is possible to choose C₁ or C₂)
- (3) When control box is located on the reverse side, Installation space should be modified new location.


Space for installation and service



Duct Connected (Compact & Flexible) FDUH

FDUH22KXZE3-W, FDUH28KXZE3-W, FDUH36KXZE3-W
FDUH22KXE6F, FDUH28KXE6F, FDUH36KXE6F

All measurements in mm.




Symbol	Content		
	Model	22.28	36
A	Gas piping	φ9.52 (3/8") (Flare)	φ12.7 (1/2") (Flare)
B	Liquid piping	φ6.35 (1/4") (Flare)	
C ₁	Drain piping	VP20 Note (2)	
C ₂	Drain piping	To be used instead of "C ₁ "	
D	Hole for wiring	φ30	
E	Suspension bolts	(M10)	
F	Inspection hole	(555X1150) Note (3)	

Notes

- (1) The model name label is attached on the fan case inside the air return grille.
- (2) Prepare the connecting socket (VP20) on site.
(As for drain piping, it is possible to choose C₁ or C₂)
- (3) When control box is located on the reverse side, Installation space should be modified new location.

Space for installation and service





Wall Mounted FDK

FDK15KXZE3-W, FDK22KXZE3-W, FDK28KXZE3-W, FDK36KXZE3-W, FDK45KXZE3-W, FDK56KXZE3-W
FDK15KXZE1, FDK22KXZE1, FDK28KXZE1, FDK36KXZE1, FDK45KXZE1, FDK56KXZE1

All measurements in mm.

Symbol	Content	
	Model	15,22,28 36,45,56
A	Gas piping	$\phi 9.52$ (3/8") (Flare) $\phi 12.7$ (1/2") (Flare)
B	Liquid piping	$\phi 6.35$ (1/4") (Flare)
C	Hole on wall for right rear piping	($\phi 65$)
D	Hole on wall for left rear piping	($\phi 65$)
E	Drain hose	VP16 (O.D.22)
F	Outlet for wiring (on both side)	




Note(1) The model name label is attached on the right side of the unit.



FDK71KXZE3-W, FDK90KXZE3-W
FDK71KXZE1, FDK90KXZE1

Symbol	Content	
	A	B
A	Gas piping	$\phi 15.88$ (5/8") (Flare)
B	Liquid piping	$\phi 9.52$ (3/8") (Flare)
C	Hole on wall for right rear piping	($\phi 65$)
D	Hole on wall for left rear piping	($\phi 65$)
E	Drain hose	VP16 (O.D.22)
F	Outlet for wiring (on both side)	
G	Outlet for piping (on both side)	


Note(1) The model name label is attached on the underside of the indoor unit.





Ceiling Suspended FDE

FDE36KXZE3-W, FDE45KXZE3-W, FDE56KXZE3-W
FDE36KXZE1, FDE45KXZE1, FDE56KXZE1


All measurements in mm.



FDE71KXZE3-W
FDE71KXZE1



Make a space of 4000(36-56), 4500(71) or more between the units when installing more than one.





Piping can be connected from 3 different direction.
Remove the cutout using side cutter or similar tool.

Note(1)The model name label is attached on the fan casing inside the air return grille.


Ceiling Suspended FDE

FDE112KXZE3-W, FDE140KXZE3-W
FDE112KXZE1, FDE140KXZE1


All measurements in mm.




Note) The slope of drain piping inside the



Symbol	Content
A	Gas piping
B	Liquid piping
C _{1,2}	Drain piping
D	Hole for suspension bolt
E	Back cutout
F	Top cutout
G	Hole for drain piping (for left back)




Make a space of 5000 or more between the units when installing more than one.



Note(1)The model name label is attached on the fan casing inside the air return grille.

Floor Standing -2way-FDFW

FDFW28KXZE3-W, FDFW45KXZE3-W, FDFW56KXZE3-W
FDFW28KXE6F, FDFW45KXE6F, FDFW56KXE6F



Symbol	Content		
	Model	28	45,56
A	Gas piping	Φ9.52 (3/8") (Flare)	Φ12.7 (1/2") (Flare)
B	Liquid piping	Φ6.35 (1/4") (Flare)	
C	Hole on wall for right rear piping	(Φ65)	
D	Hole on wall for left rear piping	(Φ65)	
E	Drain hose	VP16 (O.D.22)	
F	Screw point fasten the indoor unit	Φ5	
G	Outlet for piping (on both side)		



Notes

- (1) The model name label is attached on the right side of the unit.
- (2) In case of wall installation, leave the unit 150mm or less from the floor.

Floor Standing (with casing) FDL

FDL71KXZE3-W

All measurements in mm.




Symbol	Content	
A	Gas piping (Accessory)	$\phi 15.88$ (5/8") (Flare)
B	Liquid piping	$\phi 9.52$ (3/8") (Flare)
C	Drain piping (Accessory)	PT20A female screw
D	Slot hole for wall mounting	M10
E	Metal plate for floor mounting (Accessory)	M8

Note The model name label is attached on fan casing.


Floor Standing (with casing) FDFL

FDL71KXE6F

All measurements in mm.



Space for installation and service




Symbol	Content	
A	Gas piping (Accessory)	Ø 15.88 (5/8") (Flare)
B	Liquid piping	Ø 9.52 (3/8") (Flare)
C	Drain piping (Accessory)	PT20A female screw, 360mm
D	Slot hole for wall mounting	(M10)
E	Metal plate for floor mounting (Accessory)	(M8)

Note The model name label is attached on the lid of the control box.


Floor Standing (without casing) FDFU

FDFU28KXZE3-W, FDFU45KXZE3-W, FDFU56KXZE3-W

All measurements in mm.




FDFU71KXZE3-W




Floor Standing (without casing) FDFU

FDFU28KXE6F, FDFU45KXE6F, FDFU56KXE6F

All measurements in mm.




FDFU71KXE6F




Outdoor Air Processing unit

FDU-F

FDU650FKXZE1



Symbol	Content
A	Gas piping $\varnothing 15.88$ (5/8") (Flare)
B	Liquid piping $\varnothing 9.52$ (3/8") (Flare)
C1	Drain piping VP25(O.D.32)
C2	Drain piping(Gravity drainage) V20(O.D.26)
D	Hole for wiring
E	Suspension bolts M10
F	Outside air opening for ducting (Knock out)
G	Air outlet opening for ducting (Knock out)
H	Inspection opening (450X450)




Outdoor Air Processing unit


FDU-F

FDU1100FKXZE1

All measurements in mm.




Symbol	Content
A	Gas piping $\varnothing 15.88$ (5/8") (Flare)
B	Liquid piping $\varnothing 9.52$ (3/8") (Flare)
C1	Drain piping VP25(O.D.32)
C2	Drain piping(Gravity drainage) V20(O.D.26)
D	Hole for wiring
E	Suspension bolts M10
F	Outside air opening for ducting (Knock out)
G	Air outlet opening for ducting (Knock out)
H	Inspection opening (450X450)





Outdoor Air Processing unit FDU-F

FDU1800FKXZE1, FDU2400FKXZE1



Symbol	Content	1800	2400
MODEL			
A	Gas piping	ø19.05 (3/4") (Brazing)	ø22.22 (7/8") (Brazing)
B	Liquid piping	ø9.52 (3/8") (Brazing)	
C	Drain piping(Gravity drainage)	VP25(O.D.32)	
D	Hole for wiring		
E	Suspension bolts	M10	
F	Inspection hole	(450X450)	



Hydro Module unit HMU

HMU140KXZE1, HMU280KXZE1

All measurements in mm.









fig. a
Scale : 1:5
(Only for HMU280KXZE1)



(Only for HMU280KXZE1)



Space for installation and service


Symbol	Content	MODEL	
		HMU140KXZE1	HMU280KXZE1
A	Gas piping	$\phi 15.88$ (5/8") (Flare)	$\phi 15.88$ (5/8") (Flare) $\times 1$
B	Liquid piping	$\phi 9.52$ (3/8") (Flare)	$\phi 9.52$ (3/8") (Flare)
C	Drain socket (Gravity drainage)	PVC, $\phi 17$ (O.D.), t1.2	PVC, $\phi 17$ (O.D.), t1.2
D	Hole for power cable	$\phi 20$	$\phi 20$
E	Hole for signal line	$\phi 20$	$\phi 20$
F	Water inlet	PT1-1/4	PT1-1/4
G	Water outlet	PT1-1/4	PT1-1/4

※1 Accessory pipe (fig.a) needs to be connected for gas pipe on site.
Therefore, the diameter of the gas pipe connected with the local piping is $\phi 22.22$ (Brazing) (fig.b).



Fresh Air Ventilation and Heat Exchange unit SAF-E7

SAF150E7

All measurements in mm.





SAF250E7



Fresh Air Ventilation and Heat Exchange unit SAF-E7

SAF350E7

All measurements in mm.




NO.	Name	Qt'y
①	Frame	1
②	Adaptor	4
③	Terminal board	1
④	Inspection Cover	1
⑤	Fan	2 *
⑥	Motor	2 *
Heat Exchange Element		
⑦	SAF150E7	1
	SAF250E7	1
	SAF350E7	2
⑧	Filter	2
⑨	Damper	1
⑩	Damper Motor	1
⑪	Suspension fitting	4
⑫	Electrical components box	1

*Model SAF350E7 have different fan and motor locations.


Fresh Air Ventilation and Heat Exchange unit SAF-E7

SAF500E7

All measurements in mm.





SAF800E7



Fresh Air Ventilation and Heat Exchange unit SAF-E7

SAF1000E7



NO.	Name	Qt'y
①	Frame	1
②	Adaptor	4
③	Terminal board	1
④	Inspection Cover	1
⑤	Fan	2 *
⑥	Motor	2 *
⑦	Heat Exchange Element SAF500E7 SAF800E7 SAF1000E7	2 3 4
⑧	Filter	2
⑨	Damper	1
⑩	Damper Motor	1
⑪	Suspension fitting	4
⑫	Electrical components box	1

*Model SAF500E7 have different fan and motor locations.

Fresh Air DX Assembly



SAF-DX

SAF-DX250E6, SAF-DX350E6


All measurements in mm.

Symbol	Content	
A	Gas piping	$\phi 9.52$ (3/8") (Flare)
B	Liquid piping	$\phi 6.35$ (1/4") (Flare)
C	Drain piping	R1
D	Hole for power source line	
E	Wiring hole for total enthalpy heat exchanger	
F	Hole for communication line	
G	Suspension bolts	M10

Space for installatin and service



View H





View H


SAF-DX500E6

Symbol	Content	
A	Gas piping	$\phi 12.7$ (1/2") (Flare)
B	Liquid piping	$\phi 6.35$ (1/4") (Flare)
C	Drain piping	R1
D	Hole for power source line	
E	Wiring hole for total enthalpy heat exchanger	
F	Hole for communication line	
G	Suspension bolts	M10

Space for installatin and service



View H



View H




Fresh Air DX Assembly SAF-DX

SAF-DX800E6

All measurements in mm.

Symbol	Content
A	Gas piping $\phi 12.7$ (1/2") (Flare)
B	Liquid piping $\phi 6.35$ (1/4") (Flare)
C	Drain piping R1
D	Hole for power source line
E	Wiring hole for total enthalpy heat exchanger
F	Hole for communication line
G	Suspension bolts M10




Space for installatin and service



SAF-DX1000E6

Symbol	Content
A	Gas piping $\phi 15.88$ (5/8") (Flare)
B	Liquid piping $\phi 9.52$ (3/8") (Flare)
C	Drain piping R1
D	Hole for power source line
E	Wiring hole for total enthalpy heat exchanger
F	Hole for communication line
G	Suspension bolts M10

Space for installatin and service



Before starting use

Heating performance

The heating performance values (kW) described in the catalogue are the values obtained by operating at an outdoor temperature of 7°C and indoor temperature of 20°C as set forth in the ISO Standards. Heating performance is reduced as the temperature drops. If the outdoor temperature is too low and the heating performance is insufficient, use other heating appliances as well.

Indication of sound values

The sound values are the values (A scale) measured in a chamber such as an anechoic chamber following the ISO Standards. In the actual installation state, the value is normally larger than the values given in the catalogue due to the effect of surrounding noise and echo. Take this into consideration when installing.

Use in oil atmosphere

Avoid installing this unit in an atmosphere where oil scatters or builds up, such as in a kitchen or machine factory. If the oil adheres to the heat exchanger, the heat exchanging performance will drop, mist may be generated, and the synthetic resin parts may deform and break.

Use in acidic or alkaline atmosphere

If this unit is used in acidic atmosphere such as hot spring areas having high level of sulfuric gases or in alkaline atmosphere including ammonia or calcium chloride, places where the exhaust of the heat exchanger is sucked in, or at coastal areas where the unit is subject to salt breezes, the outer plate or heat exchanger, etc., will corrode. Please ask a dealer or specialist when you use an air-conditioner in places differing from a general atmosphere.

Use in places with high ceilings

If the ceiling is high, install a circulator to improve the heat and air flow distribution when heating.

Refrigerant leakage

The refrigerant (R32, R410A) used for air-conditioner is non-toxic and in its original state.

However, in consideration of a state where the refrigerant leaks into the room, measures against refrigerant leaks must be taken in small rooms where the tolerable level could be exceeded. Take measures by installing ventilation devices, etc.

Use in snowy areas

Take the following measures when installing the outdoor unit in snowy areas.

- Snow prevention

Install a snow-prevention hood so that the snow does not obstruct the air intake port or enter and freeze in the outdoor unit.

- Snow piling

In areas with heavy snow fall, the piled snow could block the air intake port. In this case, a frame that is 50cm or higher than the estimated snow fall must be installed underneath the outdoor unit.

Automatic defrosting device

If the temperature is low, and the humidity is high, frost will stick to the heat exchanger of the outdoor unit. If continued to use, the heating performance will drop.

The "Automatic defrosting device" will function to remove this frost.

After heating for approx. three to ten minutes, it will stop, and the frost will be removed. After defrosting, hot air will be blown again.

Servicing

After the air-conditioner has been used for several seasons, dirt will build up in the air-conditioner causing the performance to drop. In addition to regular servicing, a maintenance contract by a specialist is recommended.

Safety Precautions

Air-conditioner usage target

The air-conditioner described in this catalogue is a dedicated cooling/ heating device for human use.

Do not use it for special applications such as the storage of food items, animals or plants, precision devices or valuable art, etc.

This could cause the quality of the items to drop, etc.

Do not use this for cooling vehicles or ships. Water leakage or current leaks could occur.

Before use

Always read the "User's Manual" thoroughly before starting use.

Installation

Always commission the installation to a dealer or specialist. Improper installation will lead to water leakage, electric shocks and fires.

Make sure that the outdoor unit is stable in installation. Fix the unit to stable base.

Usage place

Do not install in places where combustible gas could leak or where there are sparks.

Installation in a place where combustible gas could be generated, flow or

accumulate, or places containing carbon fibers could lead to fires.

Certified ISO 9001



Mitsubishi Heavy Industries - Mahajak Air Conditioners Co., Ltd. has been certified of Quality Management System in accordance with ISO 9001 by TUV NORD (Thailand) Ltd.

Certified ISO 14001



Mitsubishi Heavy Industries - Mahajak Air Conditioners Co., Ltd. has been certified of Environmental Management System in accordance with ISO 14001 by TUV NORD (Thailand) Ltd.



Mitsubishi Heavy Industries Thermal Systems, Ltd. Participate in the Eurovent certification program for variable refrigerant flow (VRF). Check ongoing validity of certificate: www.eurovent-certification.com



Mitsubishi Heavy Industries Thermal Systems, Ltd.

(Wholly-owned subsidiary of MITSUBISHI HEAVY INDUSTRIES, LTD.)

2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo, 100-8332, Japan

[https://www.mhi-mth.co.jp/en/](http://www.mhi-mth.co.jp/en/)

Because of our policy of continuous improvement, we reserve the right to make changes in all specifications without notice.

26KX01E 2026 F

Edited in Japan